



Bench scales

9065/9066/9067

- ▶ Extra low-profile, ergonomic stainless steel platform; weighed goods only need to be lifted minimally
- ▶ Protection Class IP 42
- ▶ Weight units switchable between kg and lb
- ▶ 5-key operation with freely assignable F key
- ▶ Energy-efficient due to integrated Auto-off function



Features

- ▶ Extra low-profile, ergonomic stainless steel platform; weighed goods only need to be lifted minimally
- ▶ Separate display unit – weighed goods do not conceal the display
- ▶ Large LC display, character height: 25 mm
- ▶ 5-key operation with freely assignable F key
- ▶ Integrated USB interface type B (virtual serial interface)
- ▶ Flexible use at different locations due to battery operation (6x AA batteries) or optional battery operation with battery pack and charging circuit (battery life approx. 50 hrs., depending on settings)
- ▶ Energy-efficient due to integrated Auto-off function of the rechargeable battery with adjustable timer from 1 – 30 minutes or continuous operation
- ▶ Mains operation: 100 – 240 V / 50 – 60 Hz UK or US adapter, see accessories
- ▶ Fast and stable standstill behaviour (filter type 3)
- ▶ Internal user calibration for location-specific adjustments
- ▶ Weight units switchable between kg and lb
- ▶ Functions: Weighing, tare, plus/minus weighing, add, hold, user filter setting, EDP for selection of 5 variants of data sets, auto tare
- ▶ Weighing platform: Stainless steel 1.4301,
Base frame: Painted or galvanized sheetmetal
- ▶ Optional: wall/stand bracket (for versions with separate display)
- ▶ Protection Class IP 42
- ▶ Nominal operating temperature: -10 °C to 40 °C
- ▶ Scale dimensions / scale weight:
310 x 275 x 35 mm, 3 kg
520 x 400 x 70 mm, 23 kg
660 x 545 x 85 mm, 36 kg

Options


All interfaces have factory-preset print images and EDP data records for direct data output and data communication. These can also be individually adapted via the service programme 25641.10.001:

- ▶ Wall/stand bracket 38xx, stainless steel, Order No.: 2503.30.005
- ▶ USB data cable 3m with 2 plugs A plug, B plug, Order No.: 2550.03.022
- ▶ Battery incl. charging circuit installed, Order No.: 2557.40.005
- ▶ UK power adapter, Order No.: 2557.25.002
- ▶ US power adapter, Order No.: 2557.25.004

Products

Order number Variation	Approvable	Division g	Maximum load kg	Model substructure	Platform size mm	Protection class
9065.01.001 Bench scale	No	5	15	Galvanized steel sheet	310 x 275 x 35	IP 42
9065.01.002 Bench scale incl. accu	No	5	15	Galvanized steel sheet	310 x 275 x 35	IP 42
9065.02.001 Bench scale	No	10	30	Galvanized steel sheet	310 x 275 x 35	IP 42
9065.02.002 Bench scale incl. accu	No	10	30	Galvanized steel sheet	310 x 275 x 35	IP 42
9065.03.001 Bench scale	No	20	60	Galvanized steel sheet	310 x 275 x 35	IP 42
9065.03.002 Bench scale incl. accu	No	20	60	Galvanized steel sheet	310 x 275 x 35	IP 42
9066.02.001 Bench scale	No	10	30	Painted anthracite grey	520 x 400 x 70	IP 42
9066.02.002 Bench scale incl. accu	No	10	30	Painted anthracite grey	520 x 400 x 70	IP 42
9066.03.001 Bench scale	No	20	60	Painted anthracite grey	520 x 400 x 70	IP 42
9066.03.001 Bench scale incl. accu	No	20	60	Painted anthracite grey	520 x 400 x 70	IP 42
9066.04.001 Bench scale	No	50	150	Painted anthracite grey	520 x 400 x 70	IP 42
9066.04.002 Bench scale incl. accu	No	50	150	Painted anthracite grey	520 x 400 x 70	IP 42
9067.04.001 Bench scale	No	50	150	Painted anthracite grey	660 x 545 x 85	IP 42
9067.04.002 Bench scale incl. accu	No	50	150	Painted anthracite grey	660 x 545 x 85	IP 42
9067.05.001 Bench scale	No	100	200	Painted anthracite grey	660 x 545 x 85	IP 42
9067.05.002 Bench scale incl. accu	No	100	200	Painted anthracite grey	660 x 545 x 85	IP 42

Accessories

Order number		Description
Variation		
2503.30.005		Wall/stand bracket 38xx, stainless steel (required for bench and floor stand)
2550.03.022		USB 2.0 cable 3 m with 2 plugs A-plug, B-plug, for IP 42 version (for integrated virtual serial USB interface and keyboard wedge)
2564.20.002		Scale Connecting , software for transferring scale data to PC based software
2564.20.005		Scale Connecting Plus, extensive software for transferring scale data to PC-based software (with activation code)
2564.20.006		Software for linking scale to SAP R/3, single-user solution for SAP GUI via RS 232, USB or Ethernet