

SW-1S(ID-U) SERIES

FEATURES | 25mm large

and high-legible LCD display | Rechargeable battery operation | Auto power-off function
 OPTIONS | AC adapter (9V/300mA) | Waterproof cover | Rear display | Stainless steel platter | Fish tray | RS-232C connection

1. Battery Operation

Dry battery, alkaline Mn battery (only SW-1S, SW-1C)
 Rechargeable battery (only ID-U, SW-LR)



2. Dual Display

It is available to watch weighing value in the rear.



Specifications

Model	SW-1S/1C/LR, ID-U					
Max.capacity(kg)	1/2	2.5/5	4/10	10/20	15/30	
Approval	Readability (g)	0.5/1	1/2	2/5	5/10	5/10
	Resolution	1/2,000	1/2,500	1/2,000	1/2,000	1/3,000
Non-approval	Max.capacity(kg)	2	5	10	20	-
	Readability (g)	0.2	0.5	1	2	-
	Resolution	1/10,000				
Display digit	5 (Weight)					
Display type	LCD (SW-1S/1C) or LED (SW-LR, ID-U)					
Operating temperature(°C)	-10~ +40					
Power	DC 9V (SW-1S, SW-1C) or Rechargeable battery (SW-LR, ID-U)					
Battery life	Dry battery (SW-1S, SW-1C): Alkaline :800 hrs, Mn: 400 hrs Rechargeable battery (SW-LR, ID-U) : 20 hrs					
Platter Size (mm)	SW-1S/1C/LR: 230(W) x 190(D), ID-U: 293(W) x 218(D)					
Dimensions (mm)	SW-1S/1C/LR: 260(W) x 287(D) x 137(H), ID-U: 320(W) x 361(D) x 444(H)					
Product weight (kg)	SW-1S /1C/ LR: 2.8, ID-U: 5.5					

I Basic Scale



ID-U (LED)



SW-1S (LCD)



SW-1S (Fish tray)



SW-LR (LED)



SW-1W SERIES

FEATURES | IP66 DUST & Wash Down | 25mm

large and high-legible LCD display | Rechargeable battery option | Auto power-off option
 OPTIONS | AC adapter (9V/300mA) | Rear display | Fish tray | Recharge Battery

1. Rechargeable Battery (only SW-1WR)

It is convenient to use and move the scale by rechargeable battery.



2. Waterproof (IP-66)

It is protected from moisture and dust



Specifications

Model	SW-1W/1WR				
Max.capacity(kg)	2.5/5	4/10	10/10	12/30	
Approval	Readability (g)	1/2	2/5	5/10	5/10
	Resolution	1/2,500	1/2,000	1/2,000	1/3,000
Non-approval	Max.capacity(kg)	5	10	20	-
	Readability (g)	0.5	1	2	-
	Resolution	1/10,000			
Display digit	5 digits				
Display type	LCD (SW-1W) or LED (SW-1WR)				
Operating temperature(°C)	-10~ +40				
Power	DC 9V/300mA (SW-1W) or DC 12V/Rechargeable battery (SW-1WR)				
Battery life	Dry battery (SW-1W): Alkaline: 800 hrs, Mn: 400 hrs Rechargeable battery (SW-1WR): 20 hrs				
Platter Size (mm)	247(W) x 195(D)				
Dimensions (mm)	278(W) x 317(D) x 141(H)				
Product weight (kg)	3.7				

I Basic Scale



SW-1W (LCD)



SW-1WR (LED)

