SOEHNLE
PROFESSIONAL

ACCU | CE | Class IIII | industrial ETHER NET | IP 42 | M | OIML | Rost-frei | RS232 | S TQM

Bench scale Standard

753x/953x

- ▸ Bench scale with separate display and 2.5 m cable
- ▸ Includes wall bracket
- ▸ Flexible control using 5 control keys
- ▸ Integrated RS 232 interface and print function
- ▸ PLU memory

MADE IN GERMANY

Features

- ▶ Bench scale with separate display and 2.5 m cable, includes wall bracket
- ▶ Approvable two or three-range scale (accuracy class III) and high-resolution single-range scale, not approvable
- ▶ Flexible control using 5 control keys with customizable shortcut via user-programmable function key
- ▶ Fast data transfer via integrated RS 232 interface and print function
- ▶ Connection for large display via optional RS 232 interface, decoupled
- ▶ Optionally with control light display connection for quality assurance by pass / fail control
- ▶ Functions: Weighing, taring, count check (checking and counting), plus / minus weighing, adding, checking, counting, neutral measuring, percent weighing, GLP / GMP protocol
- ▶ PLU memory
- ▶ Includes software for PLU management for unit weights and tare (compatible with Windows XP and Vista, see accessories for matching data cable)
- ▶ Backlit LC display (dimmable), character height: 16 mm
- ▶ Realtime clock with date
- ▶ Power supply mode: 100 – 240 V / 50 – 60 Hz, UK power adapter see accesories
- ▶ Weighing platform: Stainless steel 1.4301
- ▶ Base frame: Stainless steel 1.4301 or powder-coated steel
- ▶ Terminal housing: Plastic
- ▶ Scale dimensions / scale weight:
- ▶ 310 x 275 x 70 mm, 6 kg
- ▶ 400 x 300 x 75 mm, 10 kg
- ▶ 520 x 400 x 75 mm, 20 kg
- ▶ 520 x 400 x 100 mm, 23 kg
- ▶ 660 x 550 x 105 mm, 40 kg
- ▶ 660 x 550 x 130 mm, 25 kg
- ▶ 800 x 600 x 130 mm, 30 kg
- ▶ Terminal: 270 x 85 x 58 mm, 1.2 kg
- ▶ Protection class IP 42
- ▶ Scale leveling up to 10 mm with 4 adjustable feet (for appr.)
- ▶ Nominal operating temperature: -10°C to 40°C
- ▶ Recommended minimum reference weight for counting parts: 3 divisions

Products

Order number Variation	Approvable	Division g	Maximum load kg	Model substructure	Platform size mm
7530.01.010 Bench scale Standard	Yes	0.5 │ 1	1.5 │ 3	Powder coated	310 x 275
7530.02.010 Bench scale Standard	Yes	1 │ 2	3 │ 6	Powder coated	310 x 275
7530.02.020 Bench scale Standard	Yes	0.5 │ 1 │ 2	1.5 │ 3 │ 6	Powder coated	310 x 275
7530.03.010 Bench scale Standard	Yes	2 │ 5	6 │ 15	Powder coated	310 x 275
7530.03.020 Bench scale Standard	Yes	1 │ 2 │ 5	3 │ 6 │ 15	Powder coated	310 x 275
7530.04.010 Bench scale Standard	Yes	5 │ 10	20 │ 35	Powder coated	310 x 275
7530.04.020 Bench scale Standard	Yes	2 │ 5 │ 10	6 │ 15 │ 30	Powder coated	310 x 275
7530.11.010 Bench scale Standard	Yes	0.5 │ 1	1.5 │ 3	Stainless steel	310 x 275
7530.12.010 Bench scale Standard	Yes	1 │ 2	3 │ 6	Stainless steel	310 x 275
7530.12.020 Bench scale Standard	Yes	0.5 │ 1 │ 2	1.5 │ 3 │ 6	Stainless steel	310 x 275
7530.13.010 Bench scale Standard	Yes	2 │ 5	6 │ 15	Stainless steel	310 x 275
7530.13.020 Bench scale Standard	Yes	1 │ 2 │ 5	3 │ 6 │ 15	Stainless steel	310 x 275
7530.14.010 Bench scale Standard	Yes	5 │ 10	15 │ 30	Stainless steel	310 x 275
7530.14.020 Bench scale Standard	Yes	2 │ 5 │ 10	6 │ 15 │ 30	Stainless steel	310 x 275
9530.01.040 Bench scale Standard	No	0.1	3	Powder coated	310 x 275
9530.02.040 Bench scale Standard	No	0.2	6	Powder coated	310 x 275

Products

Order number Variation	Approvable	Division g	Maximum load kg	Model substructure	Platform size mm
9530.03.040 Bench scale Standard	No	0.5	15	Powder coated	310 x 275
9530.04.040 Bench scale Standard	No	1	32	Powder coated	310 x 275
7531.02.010 Bench scale Standard	Yes	1 │ 2	3 │ 6	Powder coated	400 x 300
7531.02.020 Bench scale Standard	Yes	0.5 │ 1 │ 2	1.5 │ 3 │ 6	Powder coated	400 x 300
7531.03.010 Bench scale Standard	Yes	2 │ 5	6 │ 15	Powder coated	400 x 300
7531.04.010 Bench scale Standard	Yes	5 │ 10	20 │ 35	Powder coated	400 x 300
7531.04.020 Bench scale Standard	Yes	2 │ 5 │ 10	6 │ 15 │ 30	Powder coated	400 x 300
7531.05.010 Bench scale Standard	Yes	10 │ 20	30 │ 60	Powder coated	400 x 300
7531.12.010 Bench scale Standard	Yes	1 │ 2	3 │ 6	Stainless steel	400 x 300
7531.12.020 Bench scale Standard	Yes	0.5 │ 1 │ 2	1.5 │ 3 │ 6	Stainless steel	400 x 300
7531.13.010 Bench scale Standard	Yes	2 │ 5	6 │ 15	Stainless steel	400 x 300
7531.14.010 Bench scale Standard	Yes	5 │ 10	15 │ 30	Stainless steel	400 x 300
7531.14.020 Bench scale Standard	Yes	2 │ 5 │ 10	6 │ 15 │ 30	Stainless steel	400 x 300
9531.02.040 Bench scale Standard	No	0.2	6	Powder coated	400 x 300
9531.03.040 Bench scale Standard	No	0.5	15	Powder coated	400 x 300
9531.04.040 Bench scale Standard	No	1	32	Powder coated	400 x 300

Products

Order number Variation	Approvable	Division g	Maximum load kg	Model substructure	Platform size mm
9531.05.040 Bench scale Standard	No	2	60	Powder coated	400 x 300
7532.04.010 Bench scale Standard	Yes	5 | 10	15 | 30	Powder coated	520 x 400
7532.05.010 Bench scale Standard	Yes	10 | 20	30 | 60	Powder coated	520 x 400
7532.06.010 Bench scale Standard	Yes	20 | 50	60 | 150	Powder coated	520 x 400
7532.14.010 Bench scale Standard	Yes	5 | 10	15 | 30	Stainless steel	520 x 400
7532.15.010 Bench scale Standard	Yes	10 | 20	30 | 60	Stainless steel	520 x 400
7532.15.020 Bench scale Standard	Yes	5 | 10 | 20	15 | 30 | 60	Stainless steel	520 x 400
7532.16.010 Bench scale Standard	Yes	20 | 50	60 | 150	Stainless steel	520 x 400
9532.04.040 Bench scale Standard	No	1	32	Powder coated	520 x 400
9532.05.040 Bench scale Standard	No	2	60	Powder coated	520 x 400
9532.06.040 Bench scale Standard	No	5	150	Powder coated	520 x 400
7533.05.010 Bench scale Standard	Yes	10 | 20	30 | 60	Powder coated	660 x 550
7533.05.020 Bench scale Standard	Yes	5 | 10 | 20	15 | 30 | 60	Powder coated	660 x 550
7533.06.010 Bench scale Standard	Yes	20 | 50	60 | 150	Powder coated	660 x 550
7533.06.020 Bench scale Standard	Yes	10 | 20 | 50	30 | 60 | 150	Powder coated	660 x 550
7533.07.010 Bench scale Standard	Yes	50 | 100	150 | 300	Powder coated	660 x 550

Products

Order number Variation	Approvable	Division g	Maximum load kg	Model substructure	Platform size mm
9533.05.040 Bench scale Standard	No	2	60	Powder coated	660 x 550
9533.06.040 Bench scale Standard	No	5	150	Powder coated	660 x 550
9533.07.040 Bench scale Standard	No	10	300	Powder coated	660 x 550
7534.06.010 Bench scale Standard	Yes	20 │ 50	60 │ 150	Powder coated	800 x 600
7534.07.010 Bench scale Standard	Yes	50 │ 100	150 │ 300	Powder coated	800 x 600
9534.06.040 Bench scale Standard	No	5	150	Powder coated	800 x 600
9534.07.040 Bench scale Standard	No	10	300	Powder coated	800 x 600

Accessories

Order number Variation		Description
2550.03.014		IT data cable for Basic and Standard 3 m, 9 pin, data cable for Professional 2 m, 5-9 pin (for not decoupled interface)
2550.03.015		Printer cable 2 m, 9 pin - 25 pin, (for not decoupled interface)
2550.03.030		Printer cable 1.8 m 9 pin (printer 2795.20.001)
2563.21.002		RS 232 IT interface installed, 5 pin (decoupled, must be included in the purchase order, no retrofit possible)
2550.03.002		IT cable 2 m, 5-9 pin, (for decoupled interface)
2550.00.008		IT cable 2-10 m, 5-9 pin, (for decoupled interface)
2550.03.007		Printer cable 5 pin - 25 pin, (for decoupled interface)
2550.00.009		Printer cable 5 pin - 25 pin, 2 - 10 m (for decoupled interface)
2795.12.001		Label printer with cut-off device, print width up to 104 mm (thermo-direct)
2795.20.001		Label printer, print width up to 108 mm (thermo-direct)
2795.14.001		Tape printer, paper width up to 76 mm (9 pin)
2563.45.002		Ethernet interface installed incl. 10m patch cable (not combined with rechargeable battery pack, musst be included in the purchase order, retrofit not possible)
2563.10.003		WLAN module configured (only in connection with installed Ethernet interface, must be included in the purchase order, no retrofit possible)
2563.47.004		USB / second display interface, incl. 3 m USB cable (must be included in the purchase order, no retrofit possible)
2562.70.002		Second display installed , protection class IP65, dimensions: 270 x 85 x 58 mm, cable 2 m, 5 pin plug, incl. interface, no backlighting, power supplied by scale (must be included in the purchase order, no retrofit possible)
2562.01.003		Large display LED 100 mm, 5 pin plug with 15 m cable

Accessories

Order number Variation		Description
2562.12.001		Second display LED 38 mm, 5 pin plug with 15 m cable
2563.12.001		BluetoothTM interface installed (must be included in the purchase order, no retrofit possible)
2792.20.002		Alibi memory installed (must be included in the purchase order, no retrofit possible)
2551.04.001		Control light, 4 lights (must be included in the purchase order, no retrofit possible)
2551.50.002		Control light, 3 lights (must be included in the purchase order, no retrofit possible)
2557.40.001		Rechargeable battery set installed for mains-independent operation (not combined with ethernet interface, must be included in the purchase order, no retrofit possible)
2564.50.001		Pricing software
2563.00.008		Keyboard wedge USB for RS232 scale interface to PC USB interface (for terminal professional data cable 2550.03.002 required)
2564.20.005		Scale Connecting Plus, extensive software for transferring scale data to PC-based software (with activation code)
2564.20.002		Scale Connecting, software for transferring scale data to PC-based software
2564.20.006		Software for linking scale to SAP R/3, to link scale via RS232, USB or Ethernet
2564.10.001		PC service software
2557.25.002		UK power adapter
2512.06.002		Name plate, with entries