



Compact scale Dual Standard

7195

- ▶ Approvable to accuracy class III
- ▶ Protection class IP 42
- ▶ Flexible control using 5 control keys
- ▶ USB interface
- ▶ Backlit LC display (dimnable), character height: 16 mm
















Features

- ▶ Approvable dual-range scale with extra-high overall resolution
- ▶ Approvable to accuracy class III
- ▶ Flexible control using 5 control keys with customizable shortcut via programmable function key
- ▶ Ideal for use in logistics, transportation, and shipping applications, optionally for determining shipping fees for mail and packages (minimum load: 5 g)
- ▶ High-speed data transfer via integrated RS 232 interface and print function
- ▶ Functions: Weighing, taring
- ▶ Backlit LC display (dimnable), character height: 16 mm
- ▶ Power supply mode: 100 – 240 V / 50 – 60 Hz, UK power adapter see accessories
- ▶ Weighing platform: Stainless steel 1.4301
- ▶ Base frame: Powder-coated steel
- ▶ Terminal housing: Plastic
- ▶ Scale dimensions / scale weight:
 - ▶ 350 x 328 x 120 mm, 9.5 kg
- ▶ Protection class IP 42
- ▶ Scale leveling up to 10 mm with 4 adjustable feet and spirit level
- ▶ Nominal operating temperature: -10°C to 40°C




Products

Order number Variation	Approvable	Division g	Maximum load kg	Model substructure	Platform size mm
7195.04.101 Compact scale Dual Standard 7195	Yes	1 10	3 32	Powder coated	350 x 248

Accessories

Order number Variation		Description
2550.03.014		IT data cable for Basic and Standard 3 m, 9 pin, data cable for Professional 2 m, 5-9 pin (for not decoupled interface)
2550.03.015		Printer cable 2 m, 9-25 pin, (for not decoupled interface)
2550.03.030		Printer cable 1,8 m, 9 pin, (printer 2795.20.001)
2563.21.002		RS 232 PC interface installed, 5 pin (decoupled, must be included in the purchase order, no retrofit possible)
2550.03.002		IT cable 2 m, 5-9 pin, (for decoupled interface)
2550.00.008		IT cable 2-10 m, 5-9 pin, (for decoupled interface)
2550.03.007		Printer cable 5-25 pin, 2 m (for decoupled interface)
2550.00.009		Printer cable 5-25 pin, 2-10 m (for decoupled interface)
2795.12.001		Label printer with cutter, printing width up to 104 mm (thermo direct)
2795.20.001		Label printer, printing width up to 108 mm (thermo direct)
2795.14.001		Tape printer, paper width up to 76 mm (9 pin)
2563.45.002		Ethernet interface installed incl. 10m patch cable (not combined with rechargeable battery pack, must be included in the purchase order, retrofit not possible)
2563.10.003		WLAN module configured (only in connection with installed Ethernet interface, must be included in the purchase order, no retrofit possible)
2563.47.004		USB/second display interface, incl. 3 m USB cable (must be included in the purchase order, no retrofit possible)
2562.70.002		Second display installed IP 65, dimensions 270 x 85 x 58 mm, cable 2 m, 5 pin plug, incl. interface, non-backlit, power supply by scale (must be included in the purchase order, no retrofit possible)
2562.01.003		Large display LED 100 mm, 5 pin connector with 15 m cable

Accessories

Order number Variation		Description
2562.12.001		Second display LED 38 mm, 5 pin connector with 15 m cable
2563.12.001		Bluetooth™ interface installed (must be included in the purchase order, no retrofit possible)
2792.20.002		Alibi memory installed (must be included in the purchase order, no retrofit possible)
2551.04.001		Control light indicator, 4 lights (must be included in the purchase order, no retrofit possible)
2551.50.002		Control light indicator, 3 lights (must be included in the purchase order, no retrofit possible)
2557.40.001		Rechargeable battery set installed for mains-independent operation (not combined with ethernet interface, must be included in the purchase order, no retrofit possible)
2564.50.001		Pricing software
2563.00.008		Keyboard wedge USB for RS232 scale interface to PC USB interface (for terminal professional data cable 2550.03.002 required)
2564.20.005		Scale Connecting Plus, extensive software for transferring scale data to PC-based software (with activation code)
2564.20.002		Scale Connecting PC software, basic software program for transferring scale data to PC-based software
2564.20.006		Software for linking scale to SAP R/3 via RS232, USB or Ethernet
2564.10.001		PC service software
2557.25.002		UK power adapter
2512.06.002		Name plate, with entries