



# Standard Gastro scale

7135

- ▶ Flexible control using 5 control keys
- ▶ Backlit operator LC display (dimnable), character height: 16 mm
- ▶ Customer display (no backlighting), character height: 16 mm
- ▶ Includes software for PLU management
- ▶ Integrated RS 232 interface



## Features














---

- ▶ For self-service restaurants, experiential catering, in confectionery and pastry shops, highway restaurants, snack bars, cinemas and coffee shops, cafeterias, canteens and schools
- ▶ The scale can be used as a salad scale, candy scale, check scale, portioning scale, and as a basis for pricing
- ▶ Intended for point of sale integration
- ▶ Standard configuration as approvable dual-range scale (accuracy class III)
- ▶ Flexible control using 5 control keys with customizable shortcut via user-programmable function key and fixed tare value memory
- ▶ Fast data transfer via integrated RS 232 interface and print function
- ▶ Functions: Weighing, taring, zero reset, plus / minus weighing, adding, checking, neutral measuring
- ▶ PLU memory
- ▶ Includes software for PLU management (compatible with Windows XP and Vista, see accessories for matching data cable)
- ▶ Backlit operator LC display (dimnable), character height: 16 mm
- ▶ Customer display (no backlighting), character height: 16 mm
- ▶ Integrated realtime clock with date
- ▶ Power supply mode: 100 – 240 V / 50 – 60 Hz, UK power adapter see accessories
- ▶ Weighing platform: Stainless steel 1.4301
- ▶ Base frame: Powder-coated steel
- ▶ Terminal housing: Plastic
- ▶ Scale dimensions / scale weight: 310 x 430 x 70 mm, 6 kg
- ▶ Protection class IP 42
- ▶ Scale leveling up to 10 mm with 4 adjustable feet and spirit level
- ▶ Nominal operating temperature: -10°C to 40°C




## Products

Order number Variation	Approvable	Division	Maximum load	Model	Model substructure	Platform size mm
	Yes	g	kg			
7135.02.011 Standard Gastro scale	Yes	1   2	3   6	Variable model, second display with wall bracket	Powder coated	310 x 275
7135.02.010 Standard Gastro scale	Yes	1   2	3   6	Compact model, second display mounted to the weighing platform	Powder coated	310 x 275
7135.02.015 Standard Gastro scale	Yes	1   2	3   6	Retail scale, second display on a stand	Powder coated	310 x 275

## Accessories

Order number Variation		Description
2550.03.014		IT data cable for Basic and Standard 3 m, 9 pin, data cable for Professional 2 m, 5-9 pin (for not decoupled interface)
2550.03.015		Printer cable 2 m, 9-25 pin, (for not decoupled interface)
2550.03.030		Printer cable 1,8 m, 9 pin, (printer 2795.20.001)
2563.21.002		RS 232 PC interface installed, 5 pin (decoupled, must be included in the purchase order, no retrofit possible)
2550.03.002		IT cable 2 m, 5-9 pin, (for decoupled interface)
2550.00.008		IT cable 2-10 m, 5-9 pin, (for decoupled interface)
2550.03.007		Printer cable 5-25 pin, 2 m (for decoupled interface)
2550.00.009		Printer cable 5-25 pin, 2-10 m (for decoupled interface)
2795.12.001		Label printer with cutter, printing width up to 104 mm (thermo direct)
2795.20.001		Label printer, printing width up to 108 mm (thermo direct)
2795.14.001		Tape printer, paper width up to 76 mm (9 pin)
2563.45.002		Ethernet interface installed incl. 10m patch cable (not combined with rechargeable battery pack, must be included in the purchase order, retrofit not possible)
2563.10.003		WLAN module configured (only in connection with installed Ethernet interface, must be included in the purchase order, no retrofit possible)
2563.47.004		USB/second display interface, incl. 3 m USB cable (must be included in the purchase order, no retrofit possible)
2562.70.002		Second display installed IP 65, dimensions 270 x 85 x 58 mm, cable 2 m, 5 pin plug, incl. interface, non-backlit, power supply by scale (must be included in the purchase order, no retrofit possible)
2562.01.003		Large display LED 100 mm, 5 pin connector with 15 m cable

## Accessories

Order number Variation		Description
2562.12.001		Second display LED 38 mm, 5 pin connector with 15 m cable
2563.12.001		Bluetooth™ interface installed (must be included in the purchase order, no retrofit possible)
2792.20.002		Alibi memory installed (must be included in the purchase order, no retrofit possible)
2551.04.001		Control light indicator, 4 lights (must be included in the purchase order, no retrofit possible)
2551.50.002		Control light indicator, 3 lights (must be included in the purchase order, no retrofit possible)
2557.40.001		Rechargeable battery set installed for mains-independent operation (not combined with ethernet interface, must be included in the purchase order, no retrofit possible)
2564.50.001		Pricing software
2563.00.008		Keyboard wedge USB for RS232 scale interface to PC USB interface (for terminal professional data cable 2550.03.002 required)
2564.20.005		Scale Connecting Plus, extensive software for transferring scale data to PC-based software (with activation code)
2564.20.002		Scale Connecting PC software, basic software program for transferring scale data to PC-based software
2564.20.006		Software for linking scale to SAP R/3 via RS232, USB or Ethernet
2564.10.001		PC service software
2557.25.002		UK power adapter
2512.06.002		Name plate, with entries