













Terminal Basic

3700

- Not approvable, resolution up to 32.000 d
- ▶ Permanently defined weighing ranges from 2 kg − 3,000 kg (single range)
- ▶ Protection class IP 42 or IP 65
- Large LC display, character height: 20 mm
- ► Fast single-key operation



Features

- Not approvable, resolution up to 32.000 d
- ▶ Permanently defined weighing ranges from 2 kg − 3,000 kg (single range)
- ▶ Protection class IP 42 or IP 65
- Large LC display, character height: 20 mm
- Fast single-key operation
- Dimensions: 270 x 85 x 58 mm
- Scale weight: 0.4 kg
- Functions: Weighing, taring, adding, plus / minus check, hold
- Units in kg or lb
- ▶ Power supply mode: 100 240 V / 50 60 Hz
- Rechargeable battery mode
- ▶ Incl. wall bracket / stand bracket



Products

Order number Variation	Approvable	Model	Protection class
3700.01.001 Terminal Basic	No	Cable output at top	IP 42
3700.01.101 Terminal Basic	No	Cable output at top	IP 65
3700.50.001 Terminal Basic	No	Cable output at bottom	IP 42
3700.50.101 Terminal Basic	No	Cable output at bottom	IP 65



Accessories

L	Bench stand, powder-coated
	RS 232 PC interface installed, 9 pin, (not decoupled)
	PC/computer data cable for Basic and Standard 3 m, 9 pin, data cable for Professional 2 m, 5-9 pin (For not decoupled interface)
	Scale Connecting Plus PC software, extensive software porgram for transferring scale data to PC based software (with activation code)
	UK power adapter
	Floor stand with floor plate 200 x 200 mm, stainless steel, approx. height: 1,150mm
	Stand base, painted, 390 x 390 mm
	Floor stand with floorplate 200 x 200 mm, stainless steel, height ~ 1,150 mm
	Stand base, stainless steel, 390 x 390 mm
	Keyboard wedge USB for RS232 scale interface to PC USB interface (for terminal professional data cable 2550.03.002 required)