



# Terminal Standard

3710

- ▶ Approvable class III up to 10.000 e or not approvable
- ▶ Protection class IP 42
- ▶ Backlit LC display, character height: 16 mm
- ▶ 5-key operator control with user-programmable function key
- ▶ PLU memory for item weights and tare
- ▶ Integrated RS 232 interface and print function
- ▶ Incl. wall bracket / stand bracket



## Features











---

- ▶ Approvable class III up to 10.000 e or not approvable
- ▶ Weighing range up to 100,000 kg
- ▶ Protection class IP 42
- ▶ Backlit LC display, character height: 16 mm
- ▶ 5-key operator control with user-programmable function key
- ▶ Dimensions: 270 x 85 x 58 mm
- ▶ Scale weight: 0.4 kg
- ▶ Functions: Weighing, taring, counting, checking, count check, neutral measuring, percent weighing, plus / minus weighing, adding, GLP protocol
- ▶ PLU memory for item weights and tare
- ▶ Integrated RS 232 interface and print function
- ▶ Power supply mode: 100 – 240 V / 50 – 60 Hz
- ▶ Incl. wall bracket / stand bracket









## Products

Order number Variation	Approvable	Model	Protection class
3710.01.001 Terminal Standard	Yes	Cable output at top	IP 42
3710.50.001 Terminal Standard	Yes	Cable output at bottom	IP 42

## Accessories

Order number Variation		Description
2550.03.014		PC/computer data cable for Basic and Standard 3 m, 9 pin, data cable for Professional 2 m, 5-9 pin (For not decoupled interface)
2564.20.005		Scale Connecting Plus PC software, extensive software program for transferring scale data to PC based software (with activation code)
2557.25.002		UK power adapter
2504.10.001		Floor stand with floor plate 200 x 200 mm, stainless steel, approx. height: 1,150mm
2504.11.001		Stand base, painted, 390 x 390 mm
2504.20.001		Floor stand with floorplate 200 x 200 mm, stainless steel, height ~ 1,150 mm
2504.21.001		Stand base, stainless steel, 390 x 390 mm
2504.09.001		Bench stand, powder-coated
2550.03.015		Printer cable 2 m, 9-25 pin, (for not decoupled interface)
2550.03.030		Printer cable 1,8 m, 9 pin, (printer 2795.20.001)
2563.21.002		RS 232 IT interface installed, 5 pin (decoupled)
2550.03.002		IT cable 2 m, 5-9 pin, (for decoupled interface)
2550.00.008		PC/computer data cable 2-10 m, 5-9 pin, (for decoupled interface)
2550.03.007		Printer cable 5-25 pin, 2 m (for decoupled interface)
2550.00.009		Printer cable 5-25 pin, 2-10 m (for decoupled interface)
2795.12.001		Label printer with cutter, printing width up to 104 mm (thermo direct)

## Accessories

Order number Variation		Description
2795.20.001		Label printer, printing width up to 108 mm (thermo direct)
2795.14.001		Tape printer, paper width up to 76 mm (9 pin)
2563.45.002		Ethernet interface installed incl. 10m patch cable*
2563.10.003		WLAN module configured (only in connection with installed Ethernet interface)*
2563.47.004		USB/second display interface, incl. 3 m USB cable*
2562.70.002		Second display installed , protection class IP65, dimensions: 270 x 85 x 58 mm, cable 2 m, 5 pin plug, incl. interface, no backlighting, power supplied by scale*
2562.01.003		Large display LED 100 mm, 5 pin plug with 15 m cable
2562.12.001		Second display LED 38 mm, 5 pin plug with 15 m cable
2563.12.001		Bluetooth™ interface installed*
2792.20.002		Alibi memory installed*
2551.04.001		Control light indicator, 4 lights*, (not retrofit possible)
2551.50.002		Control light indicator, 3 lights*, (not retrofit possible)
2557.40.001		Battery set installed for mains-independent operation*
2564.50.001		Pricing software
2563.00.008		Keyboard wedge USB for RS232 scale interface to PC USB interface (for terminal professional data cable 2550.03.002 required)
2564.20.002		Scale Connecting , software for transferring scale data to PC based software

## Accessories

---

Order number  
Variation

Description

---

2564.20.006

Software for connecting scales to SAP R/3 via RS232, USB or Ethernet

---

2564.10.001

PC service program

---

2512.06.002

Nameplate, with entries

---