



Wall-mounted scale

7624

- ▶ Approvable, class III
- ▶ Hinged weighing platform made from 1.4301 stainless steel
- ▶ Terminal 3010 with bench / wall bracket
- ▶ Integrated power supply







Features

- ▶ Approvable, class III
- ▶ Wall-mounted scale for dry operating environments in catering and hotel operations and in commercial kitchens
- ▶ Terminal: protected against dust and water spray, protection class IP 67
- ▶ Aluminum load cell, protection class IP 65
- ▶ Functions: Weighing and taring, zero reset, totaling, order picking, checking, plus / minus weighing
- ▶ Hinged weighing platform made from 1.4301 stainless steel
- ▶ Terminal 3010 with bench / wall bracket
- ▶ Integrated power supply
- ▶ Version 1, Order No.: .001: No interface,
- ▶ Version 2, Order No.: .002: With RS 232 interface, data transfer to printer or IT
- ▶ Scale weight: 64 kg






Products

Order number Variation	Approvable	Division g	Maximum load kg	Model	Platform size mm
7624.22.001 Wall-mounted scale approvable	Yes	20	60	Standard	550 x 440
7624.23.001 Wall-mounted scale approvable	Yes	50	150	Standard	550 x 440
7624.22.002 Wall-mounted scale approvable	Yes	20	60	With RS232	550 x 440
7624.23.002 Wall-mounted scale approvable	Yes	50	150	With RS232	550 x 440





Accessories

Order number Variation		Description
2509.01.001		Hook hanger made from 1.4301 stainless steel, with hook made from anodized aluminum
2507.01.002		Protective cover 3010
2504.08.001		Bench stand made of stainless steel
2503.40.001		Wall bracket/stand bracket stainless steel
2570.02.004		Custom configuration ATEX zone 2/22, incl. documentation, name plate and 30 m power supply cable without plug
2792.40.001		Alibi memory Micro-SD 4GB, as installation kit (also for fixed value memory and software update)
2792.40.002		Alibi memory Micro-SD 4GB, installed (also for fixed value memory and software update)
2563.21.001		RS 232 interface as installation kit
2563.21.002		RS 232 interface installed
2563.21.005		3rd RS 232 interface as installation kit
2563.21.006		3rd RS 232 interface installed
2550.03.002		Data cable, 9 pin connection 30xx – PC, cable length 2 m
2550.00.008		Data cable, 9 pin connection 30xx – PC, cable length 2–10 m
2795.12.001		Label printer with cutter, printing width up to 104 mm (thermo direct), RS 232
2795.12.003		Label printer with cutter, printing width up to 104 mm (thermo direct), USB
2795.20.001		Label printer, print width up to 108 mm (thermo-direct)







Accessories

Order number Variation		Description
2795.14.001		Tape printer, paper width up to 76 mm (9 pin), RS 232
2795.14.003		Tape printer, paper width up to 76 mm (9 pin), USB
2553.20.003		Portable scanner, wire connection, incl. bench stand bracket and power supply
2553.23.002		Wireless portable scanner Bluetooth, incl. rechargeable battery, base station, RS 232 cable and power supply
2550.03.007		Printer cable 25 pin for printer 2795.14 and 12.001, cable length 2 m
2550.00.009		Printer cable 25 pin for printer 2795.14 and 12.001, cable length 2–10 m
2550.03.010		Data cable for scanner / Precisa / printer 2795.20, cable length 2m
2563.47.001		USB interface as installation kit
2563.47.002		USB interface installed
2550.03.011		USB data cable, connector 30xx – PC, cable length 2 m
2563.45.004		Ethernet interface as installation kit, incl. 10 m patch cable
2563.45.005		Ethernet interface installed incl. 10m patch cable*
2563.49.001		RS422/RS485 interface module as installation kit
2563.49.002		RS422/RS485 interface module installed
2563.10.003		WLAN module configured (only in conjunction with installed Ethernet interface), power supply: 230 VAC
2563.12.001		Bluetooth™ module

Accessories

Order number Variation		Description
2554.40.004		Measuring point as installation kit
2554.40.005		Measuring point installed
2550.05.001		Plug-in connection with ID chip installed, approvable section point between scales and display, e.g. for in-ground installation
2550.05.002		Plug-in connection with ID chip installed, approvable section point between scale and display, e.g. for in-ground installation
2550.05.004		Plug-in connection with ID chip, straight plug D=20 mm installed, approvable section point between scale and display
2563.20.004		I/O module relay, as installation kit with socket and cable fitting
2563.20.006		I/O module relay installed with cable fitting
2563.20.007		I/O module PNP, as installation kit with socket
2563.20.009		I/O module PNP, installed with cable fitting
2552.40.001		Relay box (I/O module required) 2 outputs / 4 inputs
2552.41.002		Relay box (I/O module required) with power supply, 6 outputs / 4 inputs
2563.42.007		Profibus DP, as installation kit
2563.42.008		Profibus DP, installed
2563.48.002		Ethernet IP (CIP) interface 3010
2563.44.003		Analog interface as installation kit
2563.44.004		Analog interface installed

Accessories

Order number Variation	Description
2561.40.003	DC/DC converter 12 V - 60 V as installation kit with 5 m cable
2561.40.004	DC/DC converter 12 V - 60 V installed with 5 m cable
2570.01.001	UK power supply installed
2570.01.002	US power supply installed
2570.01.003	CH power supply installed
2563.00.008	Keyboard wedge USB, for RS232 scale interface to PC USB interface (data cable 2550.03.002 required)
	
2550.03.020	USB Converter USB to RS232
2564.20.005	Scale Connecting Plus, extensive software for transferring scale data to PC-based software (with activation code)
2564.20.002	PC software Scale Connecting, software for transferring scale data to PC-based software
2564.20.006	Software for linking scale to SAP R/3, to link scale via RS232, USB or Ethernet
2564.10.003	CD PC service software for print format design, dataset, printer installation
2562.01.003	Large display LED 100 mm, 5 pin plug with 15 m cable
	
2562.12.001	Second display LED 38 mm, 5 pin plug with 15 m cable
	
2562.70.002	Second display LCD 20 mm, 5 pin plug with 2 m cable
	
2551.50.001	Control light 30xx, power supply cable 2 m, interface cable 1.5 m (I/O module required)
	
2551.40.001	Control light 30xx, power supply cable 2 m, interface cable 1.5 m (I/O module required)
	

Accessories

Order number Variation	Description
2563.40.011	I/O module, as installation kit for control light 2551.50.001
2563.40.012	I/O module, installed for control light 2551.50.001
2507.01.002	Protective cover
2504.10.001	Floor stand with floor plate 200 x 200 mm, painted, approx. height: 1,150 mm
2504.11.001	Stand base, painted, 390x 390 mm
2504.20.001	Floor stand with floor plate 200 x 200 mm, stainless steel, approx. height: 1,150mm
2504.21.001	Stand base, stainless steel, 390 x 390 mm
2512.09.001	Name plate, blank
2512.09.002	Name plate, with entries
5751.01.001	Print format design, customer-specific
5751.01.002	Dataset format, customer-specific
5751.01.004	Dataset/print format installation of existing or provided data