

# Waste Gas Evacuation

## Ventilator/Blower

### FEATURES

- Can be used to scavenge waste gas for up to 8 anesthesia machines
- Is designed to work with one passive scavenger interface per anesthesia machine
- Can be installed on the wall or ceiling, or in the attic
- 110 V ; .75 amps
- UL Certified



### SPECIFICATIONS



**Bearing Type:** Ball

**Motor Type:** Permanent Split Capacitor

**Motor Enclosure:** Open

**Motor Insulation:** Class B

**Wheel Type:** Forward Curve

**Drive Type:** Direct

**Mounting:** All Position

**Housing Finish:** Gray Enamel

**Housing Material:** Rolled Steel

**Agency Compliance:** UL Recognized US and Canada (E47479), CE

**Includes:** Discharge Mounting Flange



**Height:** 6.75"

**Width:** 9.88"

**Length:** 11.75"

**Depth:** 6"

**Wheel Dimensions:** 2" Diameter / 1" Width

**Lead Length:** 13"

**Inlet Diameter:** 1.88"



**Voltage:** 110

**Hz:** 50/60

**Phase:** 3 Phase

**Full Load Amps:** 0.75

**RPM:** 2800 - 3300

**Conduit Box:** No



**Ambient Temperature:** 104°F

**Maximum Inlet Temperature:** 104°F

**Thermal Protection:** Auto

2137-2023-02-10