



by Honeywell

Technical Specifications

SAFESCAPE ELITE WITH HANDWHEEL

Description:

The next generation rescue solution.

Miller Safescape ELITE complies with the new EN 341/2008 standard.

Thanks to its durable high-quality anodized aluminium housing, our units remains in optimum condition of use, even in the toughest environments.

8000m descent for 100kg, maximum descent height of 500m, use in emergency by 2 people weighing up to 250kg.

Recertification by factory or Miller Service Point is required only after seven years, thanks to its robust and highly resistant components.

Available in several lengths (see references below) and also a range of accessories for rescuing.



Features:

Housing : Anodized Aluminium

Mécanisme : Aluminium Pulley

Weight (without rope) : 1.8 Kg

Karabiner : Dim. : 134 * 75 mm, Opening : 20 mm

Descend speed: 1m / second



HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com



by Honeywell

References:

Available lengths :

Ref	Miller SafEscape ELITE TM w/ Handwheel
1028769	SAFESCAPE ELITE +Handwheel w/ 20m rope
1028770	SAFESCAPE ELITE +Handwheel w/ 30m rope
1028771	SAFESCAPE ELITE +Handwheel w/ 40m rope
1028772	SAFESCAPE ELITE +Handwheel w/ 50m rope
1028773	SAFESCAPE ELITE +Handwheel w/ 60m rope
1028774	SAFESCAPE ELITE +Handwheel w/ 70m rope
1028775	SAFESCAPE ELITE +Handwheel w/ 80m rope
1028776	SAFESCAPE ELITE +Handwheel w/ 90m rope
1028777	SAFESCAPE ELITE +Handwheel w/ 100m rope
1028778	SAFESCAPE ELITE +Handwheel w/ 110m rope
1028779	SAFESCAPE ELITE +Handwheel w/ 120m rope
1028780	SAFESCAPE ELITE +Handwheel w/ 130m rope
1028781	SAFESCAPE ELITE +Handwheel w/ 140m rope
1028782	SAFESCAPE ELITE +Handwheel w/ 150m rope
1028783	SAFESCAPE ELITE +Handwheel w/ 160m rope
1028784	SAFESCAPE ELITE +Handwheel w/ 170m rope
1028785	SAFESCAPE ELITE +Handwheel w/ 180m rope
1028786	SAFESCAPE ELITE +Handwheel w/ 190m rope
1028787	SAFESCAPE ELITE +Handwheel w/ 200m rope



Comply with New standard EN 341: 2008
EN 1496
ISO 22159
ANSI Z359.4-2007

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com