

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7105-2AC71-1RA1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Engineering data | | Mechanical data | | | |
|---|---------------------------|-----------------------------|------------------------------------|------------------------|---|
| Rated speed (100 K) | 2000 rpm | Motor type | Permanent-magnet synchronous motor | | |
| Number of poles | 8 | Motor type | Compact | | |
| Rated torque (100 K) | 37.0 Nm | Shaft height | 100 | | |
| Rated current | 16.0 A | Cooling | Natural cooling | | |
| Static torque (60 K) | 40.00 Nm | Radial runout tolerance | 0.050 mm | | |
| Static torque (100 K) | 48.0 Nm | Concentricity tolerance | 0.10 mm | | |
| Stall current (60 K) | 16.2 A | Axial runout tolerance | 0.10 mm | | |
| Stall current (100 K) | 20.0 A | Vibration severity grade | Grade A | | |
| Moment of inertia | 154.000 kgcm ² | Connector size | 1.5 | | |
| Efficiency | 93.0 % | Degree of protection | IP65 | | |
| <th colspan="2">Physical constants</th> | | Physical constants | | Design acc. to Code I | IM B5 (IM V1, IM V3) |
| | | Torque constant | 2.37 Nm/A | Temperature monitoring | Pt1000 temperature sensor |
| | | Voltage constant at 20° C | 157.5 V/1000*min ⁻¹ | Electrical connectors | Connectors for signals and power rotatable |
| | | Winding resistance at 20° C | 0.17 Ω | Color of the housing | Standard (Anthracite RAL 7016) |
| | | Rotating field inductance | 4.5 mH | Holding brake | without holding brake |
| | | Electrical time constant | 25.50 ms | Shaft extension | Feather key |
| | | Mechanical time constant | 1.40 ms | Encoder system | Encoder AM20DQI: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions) |
| | | Thermal time constant | 70 min | | |
| | | Shaft torsional stiffness | 125000 Nm/rad | | |
| | | Net weight of the motor | 39.0 kg | | |



Figure similar

MLFB-Ordering data

1FK7105-2AC71-1RA1

| Optimum operating point | | Recommended Motor Module | |
|-----------------------------------|----------|--------------------------|-----------|
| Optimum speed | 2000 rpm | Rated inverter current | 30 A |
| Optimum power | 7.7 kW | Maximum inverter current | 72 A |
| Limiting data | | Maximum torque | 150.00 Nm |
| Max. permissible speed (mech.) | 5000 rpm | | |
| Max. permissible speed (inverter) | 3650 rpm | | |
| Maximum torque | 150.0 Nm | | |
| Maximum current | 71.0 A | | |