



## NAKEDFLOOR - HARD WAX OIL

Durable surface treatment protection for wood, cork and stone in the interior, especially for flooring and furniture. NakedFloor Hard Wax Oil is made by melting Camauba Wax and colophonium resin into a mixture of linseed oil and tung oil. Linseed oil ensures deep penetration of even the smallest wood pores thanks to a small molecule size and a long processing time. The contingent of solid bodies is 100% (pure solid). This means that the product does not contain water or solvents, but is solely made from natural oils, resins and waxes.

### SUITABILITY

Suitable for interior application. Not suitable for humid rooms.

**Prior to application on your surface, the suitability of this product should be tested on a small, inconspicuous area.**

### PROPERTIES

- Free of solvents and water, high yielding
- Single coat application (most surfaces)
- Breathable, antistatic
- Silky-matte, appealing to touch, "warm" surface
- Easy to apply, easy to repair
- Excellent permeation
- Suitable for the treatment of toys (in accordance to DIN EN 71, part 3)
- Does not tear or become brittle
- Durable, dirt and water repellent
- Transparent, honey tinge
- Emphasizes the color of the wood
- Long "open" processing time
- Not suitable for humid rooms

### NOTE

Do NOT pour directly onto surface. Wipe excess off after 20 minutes. Room temperature during application must be at least 50°F.

### PRECAUTIONS

Use proper precautions when disposing of cloths soaked with NakedFloor Hard Wax Oil. Cloths used to apply the product must be spread out to dry in a fire-safe location or sealed in an airtight glass container. Bunching the saturated cloth will increase the risk of self-ignition. Do not throw cloths soaked with NakedFloor directly in the garbage. Once cloth is dry, it is then safe to be disposed of in the garbage.

### INGREDIENTS (FULL DECLARATION)

Linseed oil, Camauba wax, tung oil, linseed oil-stand oil, tung oil-stand oil, colophonium glycerine ester, lead-free drying agents.

### SUITABLE TOOLS

Quality rollers, brushes, lint-free cloth.  
For large surfaces, floor machines with soft pads.

### YIELD

We estimate about 420 sq. ft. of coverage per 2.5 liter can and 62 sq. ft. of coverage per 375 ml can.

### SURFACE PREPARATIONS

- The surface must be untreated, clean, dry, chemically neutral and absorbent.
- Always mix cans with different batch numbers before application.
- NakedFloor must not be poured onto the surface!
- Clean and grind (P 120- P 180) untreated wood, round off edges and clean up dust.

### APPLICATION

Apply NakedFloor evenly and thinly with a short-piled roller, lint-free cloth or paint brush. After 20 minutes polish the whole surface thoroughly with a dry, lint-free cloth until the treated surface shows an even, semi-gloss appearance.

\*Thoroughly remove all extra oil while polishing the surface. If not wiped off this could lead to glossy, sticky spots. NakedFloor should permeate completely into the wood and must not form a layer on top of the wood.

### WAX TREATMENT

Floors finished with NakedFloor can be treated with Unearthed Camauba Wax Emulsion. Application has to take place at least 48 hours after NakedFloor is applied to increase gloss. Wipe surface down first with a damp, moist rag first. Dilute emulsion at a ratio of 1:1 with water. Apply thin and evenly. Let dry and polish.

### DRYING TIME

Dry and safe to overwork with the same product after 24 hours at 68°F and 60% relative humidity. Higher humidity, cold temperatures, surfaces containing tannin (oak, etc.) and thick layers of oil can increase the drying time significantly. The hardening process takes approximately 4 weeks. Treat surfaces gently during this time.

### STORAGE

If stored above 32°F and sealed airtight, the product can be kept for at least 2 years.

### CLEANING OF TOOLS

Clean tools immediately after use with a turpentine oil, then rinse with warm, soapy water.

### CLEANING AND CARE

Sweep/vacuum clean only with soft broom or vacuum cleaner with a wood floor attachment. Never use hot water when wiping. Use a soft cotton wipe with lukewarm water. Do not use microfibre cloths or pads as they will wear away the oil. Remove liquid stains immediately - do not let them dry.

Unlike conventional plastic floor finishes, Unearthed NakedFloor can easily be spot repaired. Simply sand the area in need and reapply the NakedFloor.

### NOTES

With drying of natural oil products a typical smell may be present, however, this will disappear after a while.

### HAZARD CLASSIFICATION

Not applicable, non-hazardous product.

### SAFETY ADVICE / NOTES

Cloths containing oils can self-ignite! Let drenched cloths dry outside or keep them in a closed, fire-proof container (glass or tin can). Ensure that NakedFloor does not come into contact with porous or absorbent insulation materials like expanded clay or cellulose insulation during application. There is also danger of self-ignition!! Keep out of reach of children. Consider possible allergies to natural substances.

**Be sure to check [www.unearthedpaints.com](http://www.unearthedpaints.com) for the latest product information and application updates.**