

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

1 Identification

- **1.1 Product identifier**
- **Trade name:** JSK 8
- **Application of the substance / the mixture** Racing Fuel
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Haltermann Carless US Inc.
 901 Wilshire Drive - Suite 570
 Troy, MI 48084 - United States
 Tel : +1 (248) 422 6548
 Email: FDS@h-c-s-group.com
- **1.4 Emergency telephone number:**
 4/7 Worldwide Emergency Telephone Number for Hazardous Materials Incident, Spill, Leak, Fire, Exposure or Accident: CHEMTREC on +1 703-741-5970 / +1-800-424-9300

2 Hazard(s) identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation US OSHA & Haz Com 2012 :**



Flam. Liq. 1 H224 Extremely flammable liquid and vapor.



Muta. 2 H341 Suspected of causing genetic defects.
 Carc. 2 H351 Suspected of causing cancer.
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Acute Tox. 4 H312 Harmful in contact with skin.
 Skin Irrit. 2 H315 Causes skin irritation.
 STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation US OSHA & Haz Com 2012 :**
 The product is classified and labeled according to the CLP regulation.
- **Hazard pictograms**



- **Signal word** Danger

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: JSK 8

(Contd. of page 1)

· **Hazard-determining components of labeling:**

Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).

tert-butyl methyl ether

· **Hazard statements**

H224 Extremely flammable liquid and vapor.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P331 Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: JSK 8

· vPvB: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- **Description:** Mixture: consisting of the following components.

- **Dangerous components:**

CAS: 86290-81-5 EINECS: 289-220-8 Index number: 649-378-00-4	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C). ⚠ Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	50-100%
CAS: 1634-04-4 EINECS: 216-653-1 Index number: 603-181-00-X RTECS: KN 5250000	tert-butyl methyl ether ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H311; ⚠ Skin Irrit. 2, H315	10-25%

· SVHC -

4 First-aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **5.1 Suitable extinguishing agents:**
CO₂, sand, extinguishing powder. Do not use water.
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:**
Water with full jet
Water
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: JSK 8

(Contd. of page 3)

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 86290-81-5	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).	200 ppm
CAS: 1634-04-4	tert-butyl methyl ether	50 ppm

· **PAC-2:**

CAS: 86290-81-5	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).	1,000 ppm
CAS: 1634-04-4	tert-butyl methyl ether	570 ppm

· **PAC-3:**

CAS: 86290-81-5	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).	4000* ppm
CAS: 1634-04-4	tert-butyl methyl ether	5300* ppm

7 Handling and storage

· **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: JSK 8

(Contd. of page 4)

- Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- 7.3 **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **8.1 Control parameters**

- **Components with limit values that require monitoring at the workplace:**

CAS: 86290-81-5 Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C). (50-100%)

REL See Pocket Guide App. A

TLV Short-term value: 1480 mg/m³, 500 ppm
Long-term value: 890 mg/m³, 300 ppm
bulk handling

CAS: 1634-04-4 tert-butyl methyl ether (10-25%)

TLV Long-term value: 180 mg/m³, 50 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

- **Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

- **Material of gloves** Butyl rubber, BR

- **Eye protection:**



Tightly sealed goggles

US

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: JSK 8

(Contd. of page 5)

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	<-30 °C (<-22 °F)
Boiling point/Boiling range:	30-260 °C (86-500 °F)

· Flash point: -60 °C (-76 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 300 °C (572 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	1.4 Vol %
Upper:	7.6 Vol %

· Vapor pressure at 37.8 °C (100 °F): 500 hPa (375 mm Hg) (EN 13016-1)

· Density at 15 °C (59 °F): 0.767 g/cm³ (6.40062 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C (68 °F):	0.75 cst
Kinematic:	Not determined.

· 9.2 Other information: No further relevant information available.

10 Stability and reactivity

· 10.1 Reactivity: No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions: No dangerous reactions known.

· 10.4 Conditions to avoid: No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: JSK 8

(Contd. of page 6)

11 Toxicological information

- **11.1 Information on toxicological effects**

- **Acute toxicity:**

Harmful in contact with skin.

- **LD/LC50 values that are relevant for classification:**

CAS: 86290-81-5 Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,610 mg/l (rat)

CAS: 1634-04-4 tert-butyl methyl ether

Oral	LD50	4,000 mg/kg (rat)
Dermal	LD50	1,000 mg/kg (rabbit)
Inhalative	LC50/4 h	142 mg/l (rat)

- **Primary irritant effect:**

- **on the skin:**

Causes skin irritation.

- **on the eye:** Based on available data, the classification criteria are not met.

- **Sensitization:** Based on available data, the classification criteria are not met.

- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

CAS: 86290-81-5	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).	2B
CAS: 1634-04-4	tert-butyl methyl ether	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

CAS: 86290-81-5 Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).

LC50 48h	4.5 mg/l (daphnia)
LC50 96h	10 mg/l (fish)
EC50 72h	3.1 mg/l (plt)

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: JSK 8

(Contd. of page 7)

- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water



Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation:**



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1203
- **14.2 UN proper shipping name**
- **ADR** UN1203 MOTOR SPIRIT, ENVIRONMENTALLY HAZARDOUS
- **IMDG** MOTOR SPIRIT, MARINE POLLUTANT
- **IATA** MOTOR SPIRIT

- **14.3 Transport hazard class(es)**
- **Label** 3
- **ADR**



- **Class** 3 (F1) Flammable liquids

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: JSK 8

(Contd. of page 8)

· **Label** 3

· **IMDG**



· **Class** 3 Flammable liquids

· **Label** 3

· **IATA**



· **Class** 3 Flammable liquids

· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances: Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).

· **Marine pollutant:**

Yes
Symbol (fish and tree)

· **Special marking (ADR):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Flammable liquids

· **Danger code (Kemler):**

33

· **EMS Number:**

F-E,S-E

· **Stowage Category**

E

· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **Remarks:**

Special marking with the symbol (fish and tree).

· **ADR**

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: JSK 8

(Contd. of page 9)

· UN "Model Regulation":	UN 1203 MOTOR SPIRIT, 3, II, ENVIRONMENTALLY HAZARDOUS
--------------------------	--

15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

- Section 355 (extremely hazardous substances):

None of the ingredient is listed.

- Section 313 (Specific toxic chemical listings):

CAS: 1634-04-4 tert-butyl methyl ether

- TSCA (Toxic Substances Control Act):

CAS: 1634-04-4 tert-butyl methyl ether

- Hazardous Air Pollutants

CAS: 1634-04-4 tert-butyl methyl ether

- Proposition 65

- Chemicals known to cause cancer:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Cancerogenity categories

- EPA (Environmental Protection Agency)

None of the ingredients is listed.

- TLV (Threshold Limit Value established by ACGIH)

All components have the value A3.

- NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 86290-81-5	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).
-----------------	--

- National regulations:

- Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Date of preparation / last revision 06/20/2019 / -

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: JSK 8

(Contd. of page 10)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 1: Flammable liquids – Category 1
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Muta. 1B: Germ cell mutagenicity – Category 1B
Muta. 2: Germ cell mutagenicity – Category 2
Carc. 1B: Carcinogenicity – Category 1B
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

US