

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

1 Identification

- **1.1 Product identifier**
- **Trade name:** PX11
- **Application of the substance / the mixture** Racing Fuel
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Haltermann Carless US Inc.
 901 Wilshire Drive - Suite 570
 Troy, MI 48084 - United States
 Tel : +1 (248) 422 6548
 Email: FDS@h-c-s-group.com
- **1.4 Emergency telephone number:**
 4/7 Worldwide Emergency Telephone Number for Hazardous Materials Incident, Spill, Leak, Fire, Exposure or Accident: CHEMTREC on +1 703-741-5970 / +1-800-424-9300

2 Hazard(s) identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation US OSHA & Haz Com 2012 :**



Flam. Liq. 1 H224 Extremely flammable liquid and vapor.



Muta. 2 H341 Suspected of causing genetic defects.
 Carc. 1B H350 May cause cancer.
 Repr. 1A H360 May damage fertility or the unborn child.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.
 STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation US OSHA & Haz Com 2012 :**
 The product is classified and labeled according to the CLP regulation.
- **Hazard pictograms**



- **Signal word** Danger
- **Hazard-determining components of labeling:**
 Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: PX11

(Contd. of page 1)

lead

diisopropyl ether

· Hazard statements

H224 Extremely flammable liquid and vapor.

H315 Causes skin irritation.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P330 Rinse mouth.

P331 Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:
· NFPA ratings (scale 0 - 4)


Health = 1

Fire = 4

Reactivity = 0

· HMIS-ratings (scale 0 - 4)


Health = *1

Fire = 4

Reactivity = 0

· 2.3 Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: **PX11**· **vPvB**: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- **Description:** Mixture: consisting of the following components.

- **Dangerous components:**

CAS: 86290-81-5 EINECS: 289-220-8 Index number: 649-378-00-4	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C). ⚠ Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	50-100%
CAS: 108-20-3 EINECS: 203-560-6 Index number: 603-045-00-X RTECS: TZ 5425000	diisopropyl ether ⚠ Flam. Liq. 2, H225; ⚠ STOT SE 3, H336	10-25%
CAS: 1634-04-4 EINECS: 216-653-1 Index number: 603-181-00-X RTECS: KN 5250000	tert-butyl methyl ether ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H311; ⚠ Skin Irrit. 2, H315	10-25%
CAS: 7439-92-1 EINECS: 231-100-4 Index number: 082-013-00-1 RTECS: OF 7525000	lead ⚠ Repr. 1A, H360; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332 Specific concentration limit: Repr. 1A; H360D: C ≥ 0.03 %	<0.25%

- **SVHC**

CAS: 7439-92-1 | lead

4 First-aid measures

- **4.1 Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:**
Do not induce vomiting; immediately call for medical help.
Immediately call a doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **5.1 Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: **PX11**

(Contd. of page 3)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

CAS: 86290-81-5	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).	200 ppm
CAS: 108-20-3	diisopropyl ether	310 ppm
CAS: 1634-04-4	tert-butyl methyl ether	50 ppm
CAS: 7439-92-1	lead	0.15 mg/m ³

· PAC-2:

CAS: 86290-81-5	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).	1,000 ppm
CAS: 108-20-3	diisopropyl ether	1700* ppm
CAS: 1634-04-4	tert-butyl methyl ether	570 ppm
CAS: 7439-92-1	lead	120 mg/m ³

· PAC-3:

CAS: 86290-81-5	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).	4000* ppm
CAS: 108-20-3	diisopropyl ether	10000** ppm
CAS: 1634-04-4	tert-butyl methyl ether	5300* ppm
CAS: 7439-92-1	lead	700 mg/m ³

US

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: **PX11**

(Contd. of page 4)

7 Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.
Keep respiratory protective device available.

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not gas tight seal receptacle.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **8.1 Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

CAS: 86290-81-5 Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C). (50-100%)

REL	See Pocket Guide App. A
TLV	Short-term value: 1480 mg/m ³ , 500 ppm Long-term value: 890 mg/m ³ , 300 ppm bulk handling

CAS: 108-20-3 diisopropyl ether (10-25%)

PEL	Long-term value: 2100 mg/m ³ , 500 ppm
REL	Long-term value: 2100 mg/m ³ , 500 ppm
TLV	Short-term value: 1300 mg/m ³ , 310 ppm Long-term value: 1040 mg/m ³ , 250 ppm

CAS: 1634-04-4 tert-butyl methyl ether (10-25%)

TLV	Long-term value: 180 mg/m ³ , 50 ppm
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: **PX11**

(Contd. of page 5)

- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

- **Material of gloves** Butyl rubber, BR
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Color:	According to product specification
- **Odor:** Characteristic
- **Odor threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
- **Flash point:** -60 °C (-76 °F)
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** 220 °C (428 °F)
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not selfigniting.
- **Danger of explosion:** May form explosive peroxides.
- **Explosion limits:**

Lower:	1.0 Vol %
Upper:	21.0 Vol %
- **Vapor pressure at 20 °C (68 °F):** 532 hPa (399 mm Hg)
- **Density at 15 °C (59 °F):** 0.741 g/cm³ (6.18365 lbs/gal)
- **Relative density** Not determined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: **PX11**

(Contd. of page 6)

· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	79.5 %
· 9.2 Other information	No further relevant information available.

10 Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

CAS: 86290-81-5 Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,610 mg/l (rat)

CAS: 108-20-3 diisopropyl ether

Oral	LD50	8,470 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	162 mg/l (rat)

CAS: 1634-04-4 tert-butyl methyl ether

Oral	LD50	4,000 mg/kg (rat)
Dermal	LD50	1,000 mg/kg (rabbit)
Inhalative	LC50/4 h	142 mg/l (rat)

CAS: 7439-92-1 lead

Oral	LD50	500 mg/kg (ATE)
Inhalative	LC50/4 h	11 mg/l (ATE)

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: **PX11**

(Contd. of page 7)

- **Primary irritant effect:**
- **on the skin:**
Causes skin irritation.
- **on the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

CAS: 86290-81-5	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).	2B
CAS: 1634-04-4	tert-butyl methyl ether	3
CAS: 7439-92-1	lead	2B

· NTP (National Toxicology Program)

CAS: 7439-92-1	lead	R
----------------	------	---

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· 12.1 Toxicity
· Aquatic toxicity:

CAS: 86290-81-5 Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).	
LC50 48h	4.5 mg/l (daphnia)
LC50 96h	10 mg/l (fish)
EC50 72h	3.1 mg/l (plt)

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· Ecotoxicological effects:
· Remark: Toxic for fish

· Additional ecological information:
· General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

US

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: **PX11**

(Contd. of page 8)

13 Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation:**



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA** UN1203

· **14.2 UN proper shipping name**

· **ADR** UN1203 MOTOR SPIRIT, ENVIRONMENTALLY HAZARDOUS
 · **IMDG** MOTOR SPIRIT, MARINE POLLUTANT
 · **IATA** MOTOR SPIRIT

· **14.3 Transport hazard class(es)**

· **Label** 3

· **ADR**



· **Class** 3 (F1) Flammable liquids
 · **Label** 3

· **IMDG**



· **Class** 3 Flammable liquids
 · **Label** 3

· **IATA**



· **Class** 3 Flammable liquids
 · **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances: lead, Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin,

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: **PX11**

(Contd. of page 9)

·	cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).
· Marine pollutant:	Yes (DOT)
· Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-E
· Stowage Category	E
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· Remarks:	Special marking with the symbol (fish and tree).
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1203 MOTOR SPIRIT, 3, II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

CAS: 1634-04-4 tert-butyl methyl ether

CAS: 7439-92-1 lead

TSCA (Toxic Substances Control Act):

CAS: 108-20-3 diisopropyl ether

ACTIVE

CAS: 1634-04-4 tert-butyl methyl ether

ACTIVE

CAS: 7439-92-1 lead

ACTIVE

Hazardous Air Pollutants

CAS: 1634-04-4 tert-butyl methyl ether

CAS: 7439-92-1 lead

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: PX11

(Contd. of page 10)

- **Proposition 65**

- **Chemicals known to cause cancer:**

CAS: 7439-92-1	lead
----------------	------

- **Chemicals known to cause reproductive toxicity for females:**

CAS: 7439-92-1	lead
----------------	------

- **Chemicals known to cause reproductive toxicity for males:**

CAS: 7439-92-1	lead
----------------	------

- **Chemicals known to cause developmental toxicity:**

CAS: 7439-92-1	lead
----------------	------

- **Carcinogenicity categories**

- **EPA (Environmental Protection Agency)**

CAS: 7439-92-1	lead	
----------------	------	--

B2

- **TLV (Threshold Limit Value established by ACGIH)**

CAS: 86290-81-5	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).	A3
-----------------	--	----

CAS: 1634-04-4	tert-butyl methyl ether	A3
----------------	-------------------------	----

CAS: 7439-92-1	lead	A3
----------------	------	----

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

CAS: 86290-81-5	Naphtha (petrol) with a low boiling point ("Complex combination of hydrocarbons made up mainly of paraffin, cycloparaffin, aromatic and olefinic hydrocarbons, with a number of atoms of carbon, prevalently C3 - C12 and boiling point between 30°C and 260°C).	
-----------------	--	--

- **National regulations:**

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Date of preparation / last revision** 06/20/2019 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 06/12/2019

Trade name: PX11

(Contd. of page 11)

NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 1: Flammable liquids – Category 1
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Muta. 1B: Germ cell mutagenicity – Category 1B
Muta. 2: Germ cell mutagenicity – Category 2
Carc. 1B: Carcinogenicity – Category 1B
Repr. 1A: Reproductive toxicity – Category 1A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

US