

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 09/26/2017

1 Identification

· **1.1 Product identifier**

· **Trade name:** XPRODRAG 3

· **Application of the substance / the mixture**
Racing Fuel

This product is a mixture. All its components have been/will be pre-registered/registered for REACH in due time or are exempt.

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Haltermann Carless US Inc.
901 Wilshire Drive - Suite 570
Troy, MI 48084 - United States
Tel : +1 (248) 422 6548
Email: FDS@h-c-s-group.com

· **1.4 Emergency telephone number:**

4/7 Worldwide Emergency Telephone Number for Hazardous Materials Incident, Spill, Leak, Fire, Exposure or Accident: CHEMTREC on +1 703-741-5970 / +1-800-424-9300

2 Hazard(s) identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation US OSHA & Haz Com 2012 :**



GHS02

Flam. Liq. 1 H224 Extremely flammable liquid and vapor.



GHS08

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 1B H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **2.2 Label elements**

· **Labelling according to Regulation US OSHA & Haz Com 2012 :**

The product is classified and labeled according to the CLP regulation.

· **Hazard pictograms**



GHS02

GHS07

GHS08

· **Signal word** *Danger*

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 09/26/2017

Trade name: XPRODRA[®]G 3

(Contd. of page 1)

· Hazard-determining components of labeling:

toluene
isoprene (stabilized)
2,2,4-trimethylpentane
ethanol

· Hazard statements

H224 Extremely flammable liquid and vapor.
H315 Causes skin irritation.
H341 Suspected of causing genetic defects.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection / face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P331 Do NOT induce vomiting.
P302+P352 If on skin: Wash with plenty of water.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P391 Collect spillage.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:
· NFPA ratings (scale 0 - 4)

· HMIS-ratings (scale 0 - 4)

· 2.3 Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 09/26/2017

Trade name: XPRODRAG 3

· vPvB: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- **Description:** Mixture: consisting of the following components.

- **Dangerous components:**

CAS: 1634-04-4 EINECS: 216-653-1 Index number: 603-181-00-X RTECS: KN 5250000	tert-butyl methyl ether ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H311; ⚠ Skin Irrit. 2, H315	30-50%
CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3 RTECS: XS 5250000	toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H336	20-40%
CAS: 540-84-1 EINECS: 208-759-1 Index number: 601-009-00-8 RTECS: SA 3320000	2,2,4-trimethylpentane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	5-20%
CAS: 78-79-5 EINECS: 201-143-3 Index number: 601-014-00-5 RTECS: NT 4037000	isoprene (stabilized) ⚠ Flam. Liq. 1, H224; ⚠ Muta. 2, H341; Carc. 1B, H350	1-10%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 RTECS: KQ 6300000	ethanol ⚠ Flam. Liq. 2, H225; ⚠ Carc. 1A, H350; ⚠ Eye Irrit. 2A, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	5-10%

· SVHC -

4 First-aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **5.1 Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

US

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 09/26/2017

Trade name: XPRODRAG 3

(Contd. of page 3)

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**



Keep ignition sources away - Do not smoke.

- Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not gas tight seal receptacle.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **8.1 Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 1634-04-4 tert-butyl methyl ether (25-50%)

TLV Long-term value: 180 mg/m³, 50 ppm

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 09/26/2017

Trade name: XPRODRAG 3

(Contd. of page 4)

CAS: 108-88-3 toluene (25-50%)

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI

CAS: 540-84-1 2,2,4-trimethylpentane (10-25%)

TLV	Long-term value: 1401 mg/m ³ , 300 ppm
-----	---

CAS: 78-79-5 isoprene (stabilized) (5-10%)

WEEL	Long-term value: 2 ppm
------	------------------------

CAS: 64-17-5 ethanol (5-10%)

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm

CAS: 78-93-3 butanone (<0.5%)

PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI

CAS: 67-63-0 propan-2-ol (<0.5%)

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

· Ingredients with biological limit values:
CAS: 108-88-3 toluene (25-50%)

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 09/26/2017

Trade name: XPRODRAG 3

(Contd. of page 5)

CAS: 78-93-3 butanone (<0.5%)

BEI 2 mg/L
 Medium: urine
 Time: end of shift
 Parameter: MEK

CAS: 67-63-0 propan-2-ol (<0.5%)

BEI 40 mg/L
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Acetone (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Wash hands before breaks and at the end of work.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Protective gloves

· **Material of gloves** Butyl rubber, BR

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· Form:	Liquid
· Color:	Colorless
· Odor:	Characteristic
· Odor threshold:	Not determined.

· pH-value:	Not determined.
--------------------	-----------------

· **Change in condition**

· Melting point/Melting range:	<-30 °C (<-22 °F)
· Boiling point/Boiling range:	120 °C (248 °F)

· Flash point:	-60 °C (-76 °F)
-----------------------	-----------------

· Flammability (solid, gaseous):	Not applicable.
---	-----------------

(Contd. on page 7)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 09/26/2017

Trade name: XPRODRAG 3

(Contd. of page 6)

· Ignition temperature:	300 °C (572 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.4 Vol %
Upper:	7.6 Vol %
· Vapor pressure at 37.8 °C (100 °F):	20.5 kPa (EN 13016-1)
· Density at 15 °C (59 °F):	0.7845 g/cm ³ (6.54665 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	0.75 cst
Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

CAS: 1634-04-4 tert-butyl methyl ether

Oral	LD50	4,000 mg/kg (rat)
Dermal	LD50	1,000 mg/kg (rabbit)
Inhalative	LC50/4 h	142 mg/l (rat)

CAS: 108-88-3 toluene

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/4 h	12,124 mg/kg (rabbit)
		5,320 mg/l (mouse)

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 09/26/2017

Trade name: XPRODRAG 3

(Contd. of page 7)

		<20 mg/l (rat)
CAS: 540-84-1 2,2,4-trimethylpentane		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>33.5 mg/l (rat)
CAS: 64-17-5 ethanol		
Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)
CAS: 78-93-3 butanone		
Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
CAS: 67-63-0 propan-2-ol		
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:**
Causes skin irritation.
- **on the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

CAS: 108-88-3	toluene	3
CAS: 64-17-5	ethanol	1

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

CAS: 108-88-3 toluene	
LC50 96h	5.5 mg/l (fish)
EC50 72h	10 mg/l (Aquatic plants)
EC50 48h	5.46-9.83 mg/l (Crustaceans)
	3.78 mg/l (daphnia)
CAS: 64-17-5 ethanol	
EC50 72h	275 mg/l (Algae)
EC50 48h	12,340 mg/l (daphnia)
EC50 96h	13,000 mg/l (fish)
CAS: 78-93-3 butanone	
LC50 96h	>400 mg/l (fish)

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 09/26/2017

Trade name: XPRODRAG 3

(Contd. of page 8)

EC50 48h 4,025-6,440 mg/l (Crustaceans)

CAS: 67-63-0 propan-2-ol

LC50 48h 8,970 mg/l (fish)

EC50 72h >1,000 mg/l (Algae)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water



Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation:**



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1203
- **14.2 UN proper shipping name**
- **ADR** UN1203 MOTOR SPIRIT, ENVIRONMENTALLY HAZARDOUS
- **IMDG** MOTOR SPIRIT, MARINE POLLUTANT
- **IATA** MOTOR SPIRIT

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 09/26/2017

Trade name: XPRODRAG 3

(Contd. of page 9)

· **14.3 Transport hazard class(es)**

· **Label** 3

· **ADR**



· **Class** 3 (F1) Flammable liquids

· **Label** 3

· **IMDG**



· **Class** 3 Flammable liquids

· **Label** 3

· **IATA**



· **Class** 3 Flammable liquids

· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances:
2,2,4-trimethylpentane

· **Marine pollutant:**

Yes
Symbol (fish and tree)

· **Special marking (ADR):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Flammable liquids

· **Danger code (Kemler):**

33

· **EMS Number:**

F-E,S-E

· **Stowage Category**

E

· **14.7 Transport in bulk according to Annex II of**

MARPOL73/78 and the IBC Code Not applicable.

· **Transport/Additional information:**

· **Quantity limitations**

On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

· **Remarks:**

Special marking with the symbol (fish and tree).

· **ADR**

· **Excepted quantities (EQ)**

Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ)**

5L

(Contd. on page 11)

Printing date 06/20/2019

Reviewed on 09/26/2017

Trade name: XPRODRA³

(Contd. of page 10)

 · **Exempted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

 · **UN "Model Regulation":**

 UN 1203 MOTOR SPIRIT, 3, II, ENVIRONMENTALLY
 HAZARDOUS

15 Regulatory information

 · **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

 · **Sara**

 · **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

 · **Section 313 (Specific toxic chemical listings):**

CAS: 108-88-3 | toluene

 · **TSCA (Toxic Substances Control Act):**

CAS: 26635-64-3 | isooctane

CAS: 108-88-3 | toluene

CAS: 64-17-5 | ethanol

 · **Proposition 65**

 · **Chemicals known to cause cancer:**

None of the ingredients is listed.

 · **Chemicals known to cause reproductive toxicity for females:**

CAS: 108-88-3 | toluene

 · **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

 · **Chemicals known to cause developmental toxicity:**

CAS: 108-88-3 | toluene

CAS: 64-17-5 | ethanol

 · **Cancerogenity categories**

 · **EPA (Environmental Protection Agency)**

CAS: 108-88-3 | toluene

II

 · **TLV (Threshold Limit Value established by ACGIH)**

CAS: 108-88-3 | toluene

A4

CAS: 64-17-5 | ethanol

A3

 · **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

 · **National regulations:**

 · **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

 · **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/20/2019

Reviewed on 09/26/2017

Trade name: XPRODRA[®]G 3

(Contd. of page 11)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 06/20/2019 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 1: Flammable liquids – Category 1

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Muta. 2: Germ cell mutagenicity – Category 2

Carc. 1A: Carcinogenicity – Category 1A

Carc. 1B: Carcinogenicity – Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1