APPLICATION:		PRODUCT NAME:	SPEC.
		PRE-RINSE SPRING STYLE, SINGE WALL MOUNT	-C 27
JOB NAME:		SPECIAL CONFIGURATION  CHECK BASE MODEL AND OPTIONS	2710 REV. B
QUANTITY:	ITEM NO.	MODEL:  □ 2710 ULTRA SPRAY VALVE, NO WALL BRACKET □ 2710-WB ULTRA SPRAY VALVE, WALL BRACKET	< π
38" [965mm] ROUGH-IN:	12" 12" [306mm] 12" [306mm]	OPTIONS OR MODIFICATIONS:  SUPPLY LINES (24" OR 36") CIRCLE LENGTH  ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE  IN-LINE DUAL CHECK VALVE  BRUSH  NIPPLES  ELBOWS  VANDAL RESISTANT KIT  HANDLES (CROSS OR WRIST) CIRCLE STYLE  OTHER  FEATURES  CONTROL VALVE  SINGLE WALL MOUNT  SWIVELING SEAT DISK  STEM - RIGHT HAND  STAINLESS STEEL SEAT  STAINLESS STEEL SEAT  STAINLESS STEEL SEAT  STAINLESS STEEL SEAT  STAINLESS STEEL SEAT SCREW  HOT AND COLD INDEX BUTTONS  HOSE  36" LENGTH  STAINLESS STEEL EXTERNAL JACKET  3 PLY FIBER REINFORCED INTERNAL RUBBER HOSE  REPAIRABLE IN FIELD WITH SIMPLE TOOLS  ULTRA SPRAY VALVE  LOWEST ENERGY USER - 1.15 GPM @ 60 PSI  CLEANS FASTER - TEST PROVEN  ENGINEERED TO LAST - NO 'O' RINGS TO LEAK  INTERCHANGEABLE - FITS ALL BRANDS  WALL BRACKET  ADJUSTS FROM 2" TO 12"  SYSTEM LIMITS  "TEMP: 40"F MIN. TO 140"F MAX.  PRESSURE: 200 PSI MAX. STATIC  SHIPPING WEIGHT  * 10.0 LBS	
EPAct 2005 Compliant	SP ANSI/A112.18.1M	FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com	
· · · · · · · · · · · · · · · · · · ·		anomation@netering.com - www.netering.com	