

## YOU MAKE THE DOUGH WHILE WE SAVE YOU DOUGH

Since 1981 Starline warewashers have been engineered specifically for New Zealand conditions and are supported nationwide by the best service network in the industry.

Washtech Warewashers:

(() 0800 782 754

- Provide unrivalled product reliability and longevity;
- Are hand made from heavy duty stainless steel;
- Feature intuitive controls with easy to read displays;
- Are constructed locally to be easy to maintain and service;
- Can be customised to your requirements; and,
- Have multiple cycle options for various wash needs.
- Heat Recovery solutions available on select models, providing reductions in emissions and operating costs.

Talk to a Starline dealer today about how the latest warewashing solutions will benefit you and your customers

Componentry Wash power Capacity Chamber size Heavy duty stainless steel 4.0HP 480 baking trays per hour Width: 1100mm Depth: 50mm Height: 750mm

PW2







**BAKERY RANGE** 

	тw	AL8	PW1	PW2	PW3	СК100
Standard cycle times (seconds)	120	120, 240, 360	120, 240, 360	120, 240, 360	120, 240, 360	continuous
Bakery trays per hour* (up to 40mm deep)	120		240	480		
Wash pump power (HP)	2 x 0.5	2.0	2.0	2 x 2.0	2 × 2.0	2.0
width (mm) External dimensions: depth (mm) height (mm)	860 660 845	905 760 1750	680 780 1850	1235 855 1850	1330 855 1750	1500+ 875+ 1585+
Bench gap	865	795	680	1235	1195	1500+
width (mm) Internal dimensions: depth (mm) height (mm)	800 545 470	700 540 650	565 595 750	1100 650 750	1050 640 650	620 variable 450 to 800
						7
Dual chemical pumps (externally adjustable det. and rinse fluid pumps)	Y	Y	Υ	Υ	Y	
Full stainless steel componentry	Υ	Y	Υ	Y	Y	Y
Enhanced stainless steel filtration (scrap trays in addition to wash inlet filter)	Υ	Υ	Υ	Υ	Y	Y
Heat recovery unit (reduce emission and operating costs)		Optional	Optional	Optional	Optional	Optional
Break tank and rinse pump fitted (suitable for sites with low water temp and pressure		Y	Υ	Υ	Y	Optional
Drain pump installed	Υ	Optional	Optional	Optional	Optional	
Hot water consumption (litres) (per cycle)	3.3	2.7	2.7	4.0	4.0	5.0 (per minute)
Power requirements (higher ratings improve rinse recovery time)	1p/15A	3p/25A	3p/25A	3p/30A	3p/30A	3p/25A (base machine only)
List price (\$) (excluding GST)	12,500	13,500	14,500	21,900	26,900	POA

\*Bakery trays per hour based on 35mm deep trays equivalents, and 80% operational efficiency through the Potwasher



