



### **Specifications**

# SMART Board® 6065 Pro interactive display with iQ

**Model SPNL-6265P** 

### Overview

The SMART Board® 6065 Pro interactive display with iQ is the hub of your meeting room. PC-free embedded computing provides one-touch access to collaborative tools, including a whiteboard, wireless screen sharing and a web browser. There's no need for wires, cables or manual software and firmware updates.

The 65" 4K ultra-high-definition LED display provides optimal image clarity and wide viewing angles. With the Pen  $ID^{\text{TM}}$  feature, you can assign different appearances to the two pens and write or draw over any application in digital ink.




Object awareness™ allows you to perform mouse functions with your finger, write in digital ink with the pen, and erase with your palm or eraser—all without switching tools or modes. You can use a variety of gestures in applications, and two users can write or draw at the same time.

See smarttech.com for more information about this product.

# Dimensions and weights<sup>1</sup>

# **Dimensions**



# Weight

134 lb. (60.9 kg)

# Shipping dimensions (including pallet)

69 1/4" × 49 5/8" × 11 7/8" (175.8 cm × 126.1 cm × 30.3 cm)

### **Shipping weight**

181 lb. (82.1 kg)



As an ENERGY STAR® certified signage display, the SMART Board 6065 Pro interactive display with iQ meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

 $^{1}$ All dimensions  $\pm$  1/8" (0.3 cm). All weights  $\pm$  2 lb. (0.9 kg).

### Hardware

#### Interaction

Touch technology DViT® (Digital Vision Touch) technology

8 touches<sup>2</sup> Multitouch capabilities

Object awareness Behavior adjusts automatically to the tool or object you're using, whether it's a pen, finger,

eraser or palm.

Pen ID Two people can write independently and simultaneously, using different colored ink.

Display

LED Type

Aspect ratio 16:9

Optimal resolution 3840 × 2160 at 30 Hz (HDMI®) or 60 Hz (DisplayPort)

Horizontal frequency 26.97-75.0 kHz

Vertical frequency 23.9-60.32 Hz

Contrast ratio (typical) 1200:1

338 cd/m<sup>2</sup> Brightness (maximum)

Pixel dimensions 0.372 mm × 0.372 mm

Gamut 68% of NTSC

Viewing angle 178°

Response time (typical) 8 ms

Presence detection Presence detection sensor on the bottom frame

Audio 10 W integrated speakers (×2)

Noise level <35 dBA

Included cables and

iQ appliance

8' (2.4 m) country-specific power cable accessories

16' 5" (5 m) USB cable

Pen (×2)

iQ appliance

Bluetooth® 4.0 dual mode (backwards compatible with Bluetooth 2.1 + EDR) Wireless technology

Capture options Establish a Bluetooth wireless connection with a supported mobile device (see below) by

scanning the interactive display's unique QR code

<sup>&</sup>lt;sup>2</sup>Requires SMART Product Drivers to be installed. Some applications might not support 8 touches.

USB 3.0 Type-A (×2)

RJ45

HDCP encrypted HDMI out

Supported languages French

German Italian Japanese Korean Norwegian

Simplified Chinese

Spanish Swedish

Traditional Chinese

**Mounting holes** For a standard VESA® 300 mm × 400 mm mounting plate

Lower mounting holes 13 3/4" (35 cm) from the bottom of the interactive display

Mounting bracket depth Minimum depth of 15/8" (4.2 cm) for all components on the back of the interactive display to

clear the wall

# Connectors

Side Connector panel iQ appliance

OPS slot (for the iQ appliance) HDMI1 input connectors

HDMI in USB Type-B

HDMI2 input connectors

HDMI in USB Type-B

DisplayPort input connectors

DisplayPort in USB-Type-B Stereo 3.5 mm out

RS-232 in

Bottom USB 2.0 Type-A

Back AC power inlet

# Installation requirements

Interactive display See the SMART Board 6000 and 6000 Pro series interactive displays installation and

maintenance guide (smarttech.com/kb/171167)

SMART kapp® app

Apple devices iOS 9 or later operating system software

50 MB of storage iPhone 4S or later

Third-generation iPad or later First-generation iPad mini or later Fifth-generation iPod touch or later

#### SMART BOARD 6065 PRO INTERACTIVE DISPLAY WITH IQ - MODEL SPNL-6265P

Android™ devices Android 4.4.4 (KitKat) or later operating system

50 MB of storage (internal or SD card)

1024 MB of RAM

720p or better screen resolution

Bluetooth 2.1 + EDR

3 megapixel or better rear-facing camera (recommended)

### SMART kapp viewer

Mobile Safari for iOS 9 or later operating system software

Chrome™ for Android 39.0.2171.93 or later

Desktop Internet Explorer® 10 or later

Chrome 39.0.2171.95 or later Firefox® 34.0.5 or later Safari 8.0 or later

### Room computers and guest laptops

General requirements See the SMART Meeting Pro software release notes

4K UHD Graphics card that can support 3840 × 2160 resolution at 30 Hz and that has 1 GB DDR 5 memory

See Minimum requirements for Ultra High Definition or 4K on your interactive flat panel

### Mini-computers

General requirements See the SMART Meeting Pro software release notes

Dimensions Smaller than 10"  $\times$  10"  $\times$  2" (25.4 cm  $\times$  25.4 cm  $\times$  5.1 cm)

Weight Less than 10 lb. (4.5 kg)

Mounting VESA 75 mm × 75 mm or 100 mm × 100 mm mounting pattern

# Cable requirements

# **HDMI** Maximum length: 23' (7 m)

# NOTES

- Use only certified HDMI cables that have been tested to support the performance standard you require.
- The performance of cables longer than 23' (7 m) is highly dependent on the cable's quality.

# **DisplayPort** DisplayPort 1.2 compliant or better

Maximum length: 23' (7 m)

**USB** Maximum length: 16' (5 m)

# **Important** Using cables that exceed these maximum lengths can produce unexpected results, such as

degraded picture quality or USB connectivity. Refer to *SMART installation standards* (smarttech.com/kb/171035) for comprehensive information about cables and extensions for

SMART hardware products.

# Storage and operating requirements

Power requirements 100V to 240V AC, 50 Hz to 60 Hz

Interactive display and iQ appliance power consumption at 77°F (25°C)

Standby mode 15 W

Normal operating 113 W

Maximum operating 189 W

Standalone interactive display power consumption at 77°F (25°C)

Standby mode <2.2 W

Normal operating

110 W

(out-of-box)

Operating temperature 41–95°F (5–35°C)

Storage temperature -4-140°F (-20-60°C)

**Humidity** 5–80% relative humidity, non-condensing

Certification and compliance

Regulatory certification UL (U.S./Canada), FCC, IC, CE, EAC, RCM, SPRING, PSE

**Environmental compliance** 

European Union REACH, RoHS, WEEE and Packaging

U.S. Packaging and Conflict Minerals

# Purchasing information

Order number

SPNL-6265P SMART Board 6065-V2 interactive display with iQ, one SMART Meeting Pro software room

license and 10 SMART Meeting Pro software personal licenses

Optional accessories

WM-SBID-501 Fixed wall mount for SMART Board interactive displays

Other See smarttech.com/accessories

Warranty Three-year limited equipment warranty

**Extended warranty** 

EWY1-SPNL-6265P One-year warranty extension

EWY2-SPNL-6265P Two-year warranty extension

