

## Specifications

# SMART Board® 6075 Pro interactive display with iQ

Model SPNL-6275P


## Overview

The SMART Board® 6075 Pro interactive display with iQ is the hub of your meeting room. PC-free embedded computing provides one-touch access to collaborative tools, including a whiteboard, wireless screen sharing and a web browser. There's no need for wires, cables or manual software and firmware updates.

The 75" 4K ultra-high-definition LED display provides optimal image clarity and wide viewing angles. With the Pen ID™ feature, you can assign different appearances to the two pens and write or draw over any application in digital ink.


Object awareness™ allows you to perform mouse functions with your finger, write in digital ink with the pen, and erase with your palm or eraser—all without switching tools or modes. You can use a variety of gestures in applications, and two users can write or draw at the same time.

See [smarttech.com](http://smarttech.com) for more information about this product.



## Dimensions and weights<sup>1</sup>

### Dimensions



4 3/4"  
(12 cm)

### Weight

185 lb. (84 kg)

### Shipping dimensions (including pallet)

75 3/8" × 54 3/8" × 14"

(191.6 cm × 138 cm × 35.5 cm)

### Shipping weight

238 lb. (108 kg)



As an ENERGY STAR® certified signage display, the SMART Board 6075 Pro interactive display with iQ meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

<sup>1</sup>All dimensions ± 1/8" (0.3 cm). All weights ± 2 lb. (0.9 kg).

## Hardware

### Interaction

Touch technology	DViT® (Digital Vision Touch) technology
Multitouch capabilities	8 touches <sup>2</sup>
Object awareness	Behavior adjusts automatically to the tool or object you're using, whether it's a pen, finger, eraser or palm.
Pen ID	Two people can write independently and simultaneously, using different colored ink.

### Display

Type	LED
Aspect ratio	16:9
Optimal resolution	3840 × 2160 at 30 Hz (HDMI®) or 60 Hz (DisplayPort)
Horizontal frequency (typical)	135 kHz
Vertical frequency (typical)	60 Hz
Contrast ratio (typical)	5000:1
Brightness (maximum)	360 cd/m <sup>2</sup>
Pixel dimensions	0.429 mm × 0.429 mm
Gamut	72% of NTSC
Viewing angle	178°
Response time (typical)	8 ms

**Presence detection** Presence detection sensor on the bottom frame

**Audio** 10 W integrated speakers (×2)

**Noise level** <35 dBA

**Included cables and accessories**  
 iQ appliance  
 8' (2.4 m) country-specific power cable  
 16' 5" (5 m) USB cable  
 Pen (×2)

### iQ appliance

Wireless technology	Bluetooth® 4.0 dual mode (backwards compatible with Bluetooth 2.1 + EDR)
Capture options	Establish a Bluetooth wireless connection with a supported mobile device (see below) by scanning the interactive display's unique QR code

<sup>2</sup>Requires SMART Product Drivers to be installed. Some applications might not support 8 touches.

Supported languages	French German Italian Japanese Korean Norwegian Simplified Chinese Spanish Swedish Traditional Chinese
<b>Mounting holes</b>	For a standard VESA® 600 mm × 400 mm mounting plate Lower mounting holes 13 3/4" (35 cm) from the bottom of the interactive display
<b>Mounting bracket depth</b>	Minimum depth of 1 5/8" (4.2 cm) for all components on the back of the interactive display to clear the wall

## Connectors

<b>Side</b>	<p><b>Connector panel</b></p> <p>OPS slot (for the iQ appliance) HDMI1 input connectors HDMI in USB Type-B HDMI2 input connectors HDMI in USB Type-B DisplayPort input connectors DisplayPort in USB-Type-B Stereo 3.5 mm out RS-232 in</p>	<p><b>iQ appliance</b></p> <p>USB 3.0 Type-A (×2) HDCP encrypted HDMI out RJ45</p>
<b>Bottom</b>	USB 2.0 Type-A	
<b>Back</b>	AC power inlet	

## Installation requirements

<b>Interactive display</b>	See the <i>SMART Board 6000 and 6000 Pro series interactive displays installation and maintenance guide</i> ( <a href="http://smarttech.com/kb/171167">smarttech.com/kb/171167</a> )
<b>SMART kapp® app</b>	
Apple devices	iOS 9 or later operating system software 50 MB of storage iPhone 4S or later Third-generation iPad or later First-generation iPad mini or later Fifth-generation iPod touch or later

**SMART BOARD 6075 PRO INTERACTIVE DISPLAY WITH IQ – MODEL SPNL-6275P**

Android™ devices	Android 4.4.4 (KitKat) or later operating system 50 MB of storage (internal or SD card) 1024 MB of RAM 720p or better screen resolution Bluetooth 2.1 + EDR 3 megapixel or better rear-facing camera (recommended)
------------------	---

**SMART kapp viewer**

Mobile	Safari for iOS 9 or later operating system software Chrome™ for Android 39.0.2171.93 or later
Desktop	Internet Explorer® 10 or later Chrome 39.0.2171.95 or later Firefox® 34.0.5 or later Safari 8.0 or later

**Room computers and guest laptops**

General requirements	See the <a href="#">SMART Meeting Pro software release notes</a>
4K UHD	Graphics card that can support 3840 × 2160 resolution at 30 Hz and that has 1 GB DDR 5 memory See <a href="#">Minimum requirements for Ultra High Definition or 4K on your interactive flat panel</a>

**Mini-computers**

General requirements	See the <a href="#">SMART Meeting Pro software release notes</a>
Dimensions	Smaller than 10" × 10" × 2" (25.4 cm × 25.4 cm × 5.1 cm)
Weight	Less than 10 lb. (4.5 kg)
Mounting	VESA 75 mm × 75 mm or 100 mm × 100 mm mounting pattern

**Cable requirements**

**HDMI** Maximum length: 23' (7 m)

 **NOTES**

- Use only certified HDMI cables that have been tested to support the performance standard you require.
- The performance of cables longer than 23' (7 m) is highly dependent on the cable's quality.

**DisplayPort** DisplayPort 1.2 compliant or better  
Maximum length: 23' (7 m)

**USB** Maximum length: 16' (5 m)

**Important** Using cables that exceed these maximum lengths can produce unexpected results, such as degraded picture quality or USB connectivity. Refer to *SMART installation standards* ([smarttech.com/kb/171035](http://smarttech.com/kb/171035)) for comprehensive information about cables and extensions for SMART hardware products.

## Storage and operating requirements

<b>Power requirements</b>	100V to 240V AC, 50 Hz to 60 Hz
<b>Interactive display and iQ appliance power consumption at 77°F (25°C)</b>	
Standby mode	19 W
Normal operating	190 W
Maximum operating	315 W
<b>Standalone interactive display power consumption at 77°F (25°C)</b>	
Standby mode	<2 W
Normal operating (out-of-box)	<131 W
<b>Operating temperature</b>	41–95°F (5–35°C)
<b>Storage temperature</b>	-4–140°F (-20–60°C)
<b>Humidity</b>	5–80% relative humidity, non-condensing

## Certification and compliance

<b>Regulatory certification</b>	UL (U.S./Canada), FCC, IC, EMC, LV, VCCI, PSE
<b>Environmental compliance</b>	
European Union	REACH, RoHS, WEEE and Packaging
U.S.	Packaging and Conflict Minerals

## Purchasing information

<b>Order number</b>	
SPNL-6275P	SMART Board 6075 interactive display with iQ, one SMART Meeting Pro software room license and 10 SMART Meeting Pro software personal licenses
<b>Optional accessories</b>	
WM-SBID-501	Fixed wall mount for SMART Board interactive displays
Other	See <a href="https://www.smarttech.com/accessories">smarttech.com/accessories</a>
<b>Warranty</b>	
Three-year limited equipment warranty	
<b>Extended warranty</b>	
EWY1-SPNL-6275P	One-year warranty extension
EWY2-SPNL-6275P	Two-year warranty extension

SPECIFICATIONS

**SMART BOARD 6075 PRO INTERACTIVE DISPLAY WITH IQ – MODEL SPNL-6275P**

---

[smarttech.com/support](http://smarttech.com/support)  
[smarttech.com/contactsupport](http://smarttech.com/contactsupport)

© 2017–2018 SMART Technologies ULC. All rights reserved. SMART Board, SMART Meeting Pro, DVIT, Pen ID, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. HDMI and all associated logos are trademarks of HDMI Licensing, LLC. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: [www.smarttech.com/patents](http://www.smarttech.com/patents). Contents are subject to change without notice. 04/2018.