# 65" Full HD Direct-lit LED Commercial Display



**CDE6502** 













The ViewSonic<sup>®</sup> CDE6502 is a 65" (64.5" viewable) Full HD commercial display with 1920 x 1080 resolution, 350-nit brightness, wide viewing angles and dual 10W speakers, providing high-impact messaging in hotels, restaurants, and other businesses. In addition to HDMI and VGA inputs to connect with various high definition devices, the display utilizes an integrated quad-core processor and 8GB of internal memory, allowing customers to playback multimedia content via USB or web browsing through RJ45 connectivity without the need for a PC. To make life even easier, the bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop, and its flicker-free and blue light filter technologies help provide a comfortable viewing environment.

#### Advanced media player

Integrated customized Android-based media player, the display provides flexible content loading options and web browsing via LAN connectivity, without the need of an external media player or a PC.

#### **USB Multimedia Playback**

This display features a convenient USB multimedia playback function. Now photos, music, and 1080p video can be quickly displayed on-screen directly from a USB drive.





# Quad-core Processor and RJ45 Connectivity

Integrated with a powerful quad-core processor and RJ45 connectivity, the display offers web browsing functionality. Users can search for information online and display media content on the display directly without the need to connect with other computing devices. In addition, RJ45 connectivity also provides intranet and wireless capabilities when connecting to a wireless router.



#### Free Bundled vController Software

Included vController software provides a simple and intuitive interface for remote management, OSD-related settings, and scheduling on deployed displays through RS232 or LAN.



### **Control Multiple Devices**

RS232 IR pass-through offers local control for settop boxes, and other RS232 connected devices, directly with the display's remote controller. HDMI CEC functionality offers local control of DVD players, sound systems, and other HDMI connected devices, directly with the display's remote controller.

#### **Enhanced Viewing Comfort**

Flicker-Free technology and a Blue Light Filter help to eliminate eye strain from extended viewing periods.





## **Dual Integrated Speakers**

Designed with dual integrated speakers, this display combines incredible screen performance with stereo sound for an immersive multimedia experience.



**Panel Size** 

**Surface Treatment** 

Orientation

# **Technical Specifications**

**DISPLAY** 

Type/ Tech	TFT LCD Module. with LED Backlight
Display Area (mm)	1428.48(H) x 803.52 (V) (65" diagonal)
Aspect Ratio	16:9
Resolution	1920x1080
Colors	16.7M
Brightness	350 nits (typ.)
Contrast Ratio	4000:1 Typ.
Response Time	8ms
Viewing Angles	H = 178, V = 178 (typ.)
Backlight Life	30,000 Hours (typ.)

Anti-Glare, 3H, Haze=2%

Landscape/Portrait

65"

INPUT	HDMI	x2 (Support MHL x1)
	RGB / VGA	x1
	Audio	x1 PC audio(3.5mm)
	RS232	x1
ОИТРИТ	Audio	x1 Earphone Out
LAN	RJ45	x1
USB	Type A	x3 (USB3.0 x2, USB2.0 x1)
SPEAKERS		10W x2
COMPATIBILITY RGB PC/HDMI PC HDMI	RGB PC/HDMI PC	480i, 480p,720p,1080i,1080p
	HDMI	480i, 480p,720p,1080i,1080p
_	Voltage	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
	Consumption	150W (typ), 180 W (max)
		< 0.5 W ("Off")
ERGONOMICS	Wall MounWall Mount (VESA)	400x400mm
	Temperature (° C)	0°C to 40°C
	Humidity	20%~80% @40℃ non-condensing
DIMENSIONS (W x H x D)	Physical (inch / mm)	59.53 x 39.53 x 11.81 / 1512 x1004 x 300 (w/ Stand)
	Packaging (inch / mm)	53.74 x 34.02 x 7.28 / 1365 x864 x185 (w/o Stand)
WEIGHT	Net (lb / kg)	103.62 / 47 (w/o Stand)
REGULATIONS		cTUVus, FCC, Energy Star 7.0, Mexico Energy, CE, CB, RoHS, ErF WEEE
PACKAGE CONTENTS		CDE6502 commercial display / Remote Control with batteries / User manual CD wizard / Quick Start Guide / Power Cables *Actual contempt may differ from market to market

05162017