

Key **Features**

5,500 Lumen Brightness | Vertical/Horizontal Lens Shift with Centered Lens | Stackable Design | 360degree Installation | SuperColor: Amazing Color Accuracy



Product **Description**

Bright and versatile for any professional installation, the ViewSonic® Pro9800WUL WUXGA projector delivers everything you need for big screens in big venues. Delivering 5,500 lumens of advanced high brightness, this projector is ideal for auditoriums, large boardrooms, houses of worship, and more. Thanks to SuperColor™ technology, content is brought to life with captivating color, crisp graphics, and stunning videos no matter the environment. Designed for installers, this top-notch performer is also easy to deploy and manage with its wide 1.7x optical zoom adjustment, a centered lens design, and a vertical/horizontal lens shift feature that provides extreme flexibility in even the most challenging installations. Thanks to the stackable design of these projectors, light output can be doubled by simply placing one projector on top of the other - perfect for large venues with high ambient light.









call: 888.881.8781Contact Salesemail: salesinfo@viewsonic.comvisit: viewsonic.com

Display:

Display:	
Type:	DLP
Resolution Type:	WUXGA
Resolution:	1920 x 1200
Brightness (ANSI Lumens):	5,500
Throw Distance:	4 - 55.8 ft / 1.2 - 17m
Throw Ratio:	1.25 - 2.13:1
Display Size (in.):	26.2 - 371.4 in. / 0.67 - 9.43m
Keystone:	Vertical (± 30°) / Horizontal (± 30°)
Lens:	1.7x Manual optical zoom / manual optical focus
Light Source (watt):	370
Light Source Life, Normal (hours):	1500
Light Source Life, Dynamic Eco- Mode (hours):	3500
Color Depth:	30 bits, 1.07B Color (10+10+10)
Dynamic Contrast Ratio:	15,000:1
Aspect Ratio:	16:10
Lens Shift:	Vertical (-12.1%/+20.8%) / Horizontal (+/- 10.3%)
Video Signal:	
Frequency Horizontal:	15-100kHz
Frequency Vertical:	24-120Hz
Compatibility:	
PC Resolution (max):	Up to 1920x1200
Mac® Resolution (max):	Up to 1920x1200
Connector:	

Connector:

USB 2.0 Type A(1), USB 2.0 Type B(1), Ethernet LAN (RJ45)(1), 3.5mm 12V Trigger(1), 3.5mm Audio Out(1), 3.5mm Audio In(3), Control (RS232)(1), HDMI 1.4(1), HDMI MHL(1), DVI-D(1), VGA In(2), VGA Out(1), Composite RCA Video In(1), S-Video In(1), RCA Audio In (L/R)(1), RCA Audio Out(1), 3D VESA(1), Wired Remote In(1), Wired Remote Out(1), 5-BNC(1)

Audio:

On Screen Display:

Internal Speakers:	7W (x2)
Power:	
Voltage:	100~240VAC (Auto Switching), 50-60Hz (universal)
Consumption (max):	480W
Stand-by:	<0.5W
Controls:	
Physical Controls:	Power, H/V lens shift, focus, zoom, keystone/arrow keys, left/blank, right/panel key lock, menu/exit,

mode/enter, source

Advanced

Display, Image, Video, Audio, Basic,

Operating Conditions:

Temperature:	41-104° F (5-40° C)
Humidity (non-condensing):	10-85%
Additional Hardware:	
Kensington Lock Slot:	1
Weight (imperial):	
Net (lbs):	18.26
Gross (lbs):	27.31
Weight (metric):	
Net (kg):	8.29
Gross (kg):	12.4
Dimensions (imperial) (WxHxD):	
Packaging (in.):	22.68 x 17.17 x 11.46
Physical (in.):	17.51 x 12.81 x 5.82
Dimensions (metric) (WxHxD):	

Dimensions (metric) (WxHxD):

Packaging (mm):	576 x 436 x 291
Physical (mm):	445 x 325.5 x 147.8

General:

Regulations: UL, cUL, FCC, CE, EMC, CB, ROHS, REACH, SVCH, WEEE, ErP, Mexico NOM/ENERGY, PSB, RCM, CCC

PACKAGE CONTENTS: Pro9800WUL projector, power cable, VGA cable, laser remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange* service**

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907848212

Accessories:

HB10B, PJ-WMK-006, RLC-106, VIEWSTICK2, VIEWSYNC3

Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (11/06/2017 09:27 PM PST)