

# **Specifications**

# SMART Board® 7075 Pro interactive display with iQ

Model SBID-7275P

## Overview

The SMART Board® 7075 Pro interactive display with iQ is the hub of your meeting room. PC-free embedded computing provides one-touch access to collaborative tools, including a whiteboard, wireless screen sharing and a web browser. There's no need for wires, cables or manual software and firmware updates.






Object Awareness™ allows you to perform mouse functions with your finger, write in digital ink with the pen, and erase with your palm or eraser—all without switching tools or modes. You can use a variety of gestures in applications, and four users can write or draw at the same time.

See smarttech.com for more information.

# Dimensions and weights<sup>1</sup>

## **Dimensions**



## Weight

174 lb. (79 kg)

# Shipping dimensions (including pallet)

75 3/8" × 54 1/4" × 11 3/4" (191.6 cm × 137.8 cm × 30 cm)

## **Shipping weight**

227 lb. (103 kg)



As an ENERGY STAR® certified signage display, the SMART Board 7075 Pro interactive display with iQ meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

## Hardware

#### Interaction

Touch technology HyPr Touch™ (Hybrid Precision Touch) proprietary hybrid system, which greatly improves upon its InGlass™ core by optimizing both touch and pen performance, resulting in virtually no lag and zero contact detect height Multitouch capabilities Up to 16 simultaneous interaction points (combination of 10 finger touch points, four pen touch points and two eraser touch points) **Object Awareness** Behavior adjusts automatically to the tool or object you're using, whether it's a pen, finger, eraser or palm. Pen ID Four people can write independently and simultaneously, using different colored ink. Display Type LED Aspect ratio 16:9 Optimal resolution 3840 × 2160 at 60 Hz Horizontal frequency 135 kHz (typical) Vertical frequency 60 Hz (typical) Contrast ratio (typical) 5000:1 Brightness (maximum) 360 cd/m<sup>2</sup> Pixel dimensions 0.429 mm × 0.429 mm Gamut 72% of NTSC 178° Viewing angle Response time (typical) 8 ms 1000BASE-T Ethernet Two external ports for a four-port Gigabit Ethernet switched network connecting the interactive display and the iQ appliance to an external network and an external device, such as a computer Presence detection Dual sensors that reduce startup time and power consumption during inactivity

Audio 10 W integrated speakers (×2)

Noise level <30 dBA

Included cables and accessories

iQ appliance

Country-specific power cable

USB cable Pen (×4) Eraser

## iQ appliance

Wireless technology Bluetooth® 4.0 dual mode (backwards compatible with Bluetooth 2.1 + EDR)

Capture options Establish a Bluetooth wireless connection with a supported mobile device (see below) by

scanning the interactive display's unique QR code

Supported languages French

German Italian Japanese Korean Norwegian

Simplified Chinese

Spanish Swedish

Traditional Chinese

**Mounting holes** For a standard VESA® 600 mm × 400 mm mounting plate

Lower mounting holes 13 3/4" (35 cm) from the bottom of the interactive display

Mounting bracket depth Minimum depth of 2" (5.1 cm) for all components on the back of the interactive display for airflow

## Connectors

**Connector panel** OPS slot (for the iQ appliance)

Stereo 3.5 mm out

S/PDIF out

VGA input connectors

VGA in

Stereo 3.5 mm in USB Type-B

**HDMI 1 input connectors** 

HDMI 2.0 in USB Type-B

Display Port input connectors

in

USB Type-B USB Type-A<sup>2</sup> RJ45 (×2)

Convenience panel HDMI 2 input connectors

HDMI 1.4 in USB Type-B USB Type-A (×2)

**Bottom** AC power in

AC power out RS-232 in RS-232 out

**HDCP support** Version 1.4/2.2

<sup>&</sup>lt;sup>2</sup>For service use only

# Installation requirements

Interactive display See the SMART Board 7000 and 7000 Pro series interactive displays installation and

maintenance guide (smarttech.com/kb/171164)

SMART kapp® app

Apple devices iOS 9 or later operating system software

50 MB of storage iPhone 4S or later

Third-generation iPad or later First-generation iPad mini or later Fifth-generation iPod touch or later

Android™ devices Android 4.4.4 (KitKat) or later operating system

50 MB of storage (internal or SD card)

1024 MB of RAM

720p or better screen resolution

Bluetooth 2.1 + EDR

3 megapixel or better rear-facing camera (recommended)

SMART kapp viewer

Mobile Safari for iOS 9 or later operating system software

Chrome™ for Android 39.0.2171.93 or later

Chrome 39.0.2171.95 or later Firefox® 34.0.5 or later Safari 8.0 or later

Room computers and guest laptops

General requirements See SMART Meeting Pro software release notes

4K UHD Graphics card that can support 3840 × 2160 resolution at 60 Hz and that has 1 GB DDR 5 memory

See Minimum requirements for Ultra High Definition or 4K on your interactive flat panel

Mini-computers

General requirements See SMART Meeting Pro software release notes

Dimensions Smaller than 10"  $\times$  10"  $\times$  2" (25.4 cm  $\times$  25.4 cm  $\times$  5.1 cm)

Weight Less than 10 lb. (4.5 kg)

Mounting VESA 75 mm  $\times$  75 mm or 100 mm  $\times$  100 mm mounting pattern

## Cable requirements

**HDMI** Maximum length: 23' (7 m)

## **NOTES**

- Use only certified HDMI cables that have been tested to support the performance standard you require.
- The performance of cables longer than 23' (7 m) is highly dependent on the cable's quality.

**DisplayPort** DisplayPort 1.2 compliant or better

Maximum length: 23' (7 m)

**USB** Maximum length: 16' (5 m)

Important Using cables that exceed these maximum lengths can produce unexpected results, such as

degraded picture quality or USB connectivity. Refer to *SMART installation standards* (smarttech.com/kb/171035) for comprehensive information about cables and extensions for

SMART hardware products.

# Storage and operating requirements

Power requirements 100V to 240V AC, 50 Hz to 60 Hz

## Interactive display and iQ appliance power consumption at 77°F (25°C)

Standby mode <2 W

Normal operating 162 W

Maximum operating 260 W

## Standalone interactive display power consumption at 77°F (25°C)

Standby mode <2 W

Normal operating

(out-of-box)

147 W

Operating temperature 41–95°F (5–35°C)

Storage temperature -4-140°F (-20-60°C)

**Humidity** 5–80% relative humidity, non-condensing

# Certification and compliance

Regulatory certification 
EU RED and LV Directives, ISED, cUL, FCC, UL, RCM, CITIC, TRA

## **Environmental compliance**

European Union REACH, RoHS, WEEE, Battery and Packaging

U.S. CONEG Packaging, California Prop 65

Regulatory models SBID-7075 and ID7075-1

# Purchasing information

#### Order number

SBID-7275P SMART Board 7075 Pro interactive display with iQ, one SMART Meeting Pro software room

license and 10 SMART Meeting Pro software personal licenses

**Optional accessories** 

WM-SBID-501 Fixed wall mount for SMART Board interactive displays

Other See smarttech.com/accessories

Warranty Three-year limited equipment warranty

**Extended warranty** 

EWY1-SBID-7275P One-year warranty extension

EWY2-SBID-7275P Two-year warranty extension

smarttech.com/support smarttech.com/contactsupport

© 2017–2018 SMART Technologies ULC. All rights reserved. SMART Meeting Pro, SMART kapp, Pen ID, Object Awareness, HyPr Touch, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. iPhone, iPad, iPod touch and Safari are trademarks of Apple Inc., registered in the U.S. and other countries. Google Play, Android and Chrome are trademarks of Google Inc. The Bluetooth word mark is owned by the Bluetooth SIG, Inc. and any use of such marks by SMART Technologies ULC is under license. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. 07/2018.