

## MODEL

**Model:** BVVCMPEP-RETRO

**CMEP HP:** 1 HP

**CMEP Voltage:** 110-120 VAC

**CMEP Hz:** 60Hz

**CMEP RPM:** 1740

**Compressor Type:** Piston

**Displacement:** 2.72 cfm



## Butane Recovery

**Rate:** 1 lb. / 1:32 min\*

## Maximum Working

**Pressure:** 500 PSIG

## Maximum Outlet

**Pressure:** 300 PSI

## High Pressure

**CutOut Switch:** 360 PSI

## INLET

### VACUUM LEVELS

**0 PSIG Outlet:** 28.8 inch Hg.

**100 PSIG Outlet:** 26.0 inch Hg.

**200 PSIG Outlet:** 23.0 inch Hg.

**300 PSIG Outlet:** 20.0 inch Hg.

**Inlet Port Size:** 3/8" MNPT

**Outlet Port Size:**

**Weight:** 14.0 lbs

## ELECTRIC MOTOR AND CONTROLS

**Electric Motor and Controls:** EX Rated OEM 1740 RPM Motor

**Noise Level:  
Sound Level  
(1m):** 95.3 dB

## FEATURES AND BENEFITS

- Built for up to 5k lbs. of runtime before rebuild
- Equipped with oil-less reciprocating compressors for a clean product
- Designed and Assembled in the U.S.A. with domestic and global parts
- Affordable and highly cost efficient
- 4-Cylinder Configuration
- Comes with a 1-year Manufacturer's Warranty covering Hemp usage
- Equipped with Viton O-Ring Seals for Butane/Propane gas and oil compatibility
- Update your existing CMEP unit to a more dependable unit.
- Spark-free construction meets ISA 12.12.01:2016 standards

\* Recovery rate results based on a minimum collection vessel pressure of 30 psi or greater, storage tank pressure >10 psi, and a dry ice coil between the outlet on the pump, and the storage tank.