


Single Pin Heavy Duty Clamp With Cross Hole Wing Nut

- Available in 304 only

Tube O.D.	Service Pressure Rating @ 70°F	Service Pressure Rating @ 250°F	A	Part Number (Style 13MHM)	Inch/Pounds Max Torque
1" & 1-1/2"	500	300	2.122	C150	30 in/lb
2"	450	250	2.654	C200	30 in/lb
3"	350	175	3.717	C300	30 in/lb
4"	300	150	4.82	C400	30 in/lb
6"	150	75	6.695	C600	30 in/lb
8"	100	50	8.695	C800	40 in/lb
10"	75	40	10.74	C1000	40 in/lb
12"	50	25	12.74	C1200	45 in/lb



High Pressure Clamp with 5/8" Brass Nut

- Available in 304 only

Tube O.D.	Service Pressure Rating @ 70°F	Service Pressure Rating @ 250°F	A	Part Number (Style 13MHM)	Inch/Pounds Max Torque	Bolt/Nut
1/2" & 3/4"	1500	1200	1.062	--	--	--
1" & 1-1/2"	1500	1200	2.046	HPC150	100 In/lb	3/8"-16 / 5/8"
2"	1000	800	2.578	HPC200	100 In/lb	3/8"-16 / 5/8"
2-1/2"	1000	800	3.11	HPC250	100 In/lb	3/8"-16 / 5/8"
3"	1000	800	3.64	HPC300	100 In/lb	3/8"-16 / 5/8"
4"	800	600	4.744	HPC400	100 In/lb	3/8"-16 / 5/8"
6"	300	200	6.632	HPC600	130 In/lb	3/8"-16 / 5/8"
8"	250	150	8.638	HPC800	130 In/lb	3/8"-16 / 5/8"
10"	200	125	10.74	HPC1000	160 In/lb	3/8"-16 / 5/8"
12"	150	100	12.74	HPC1200	160 In/lb	3/8"-16 / 5/8"