

Installation and Use Instructions for GRIPPS® Dropped Tool Prevention Equipment.

> **GRIPPS®** Coil Tether Models: H01062, H01068, H01069



H01062

Length: 17-77cm/7-30"

Max Load: 1.0kg/2.2lbs



H01068

Coil Wrist Tether Single-Action Coil Tether Single-Action Length: 40-160cm/16-63" Max Load: 1.0kg/2.2lbs



H01069

Coil Tether Dual-Action Length: 50-170cm/20-67" Max Load: 2.3kg/5.0lbs

For product support contact us at:

support@gripps.com.au | +61 3 8383 9458

WWW.GRIPPS.COM.AU | @GRIPPSGLOBAL | #CONQUERGRAVITY

GRIPPS® Coil Tether

SAFETY INFORMATION

MARNING Before using GRIPPS® Coil Tethers, read all provided safety information pertaining to the use of your Dropped Tool Prevention (DTP) device. FAILURE TO DO SO COULD RE-SULT IN INJURY OR DEATH.

The user of a DTP device bears the responsibility of reading all safety information contained herein. Keep this manual for future reference.

Intended Use:

When used properly, GRIPPS® Coil Tethers can prevent workplace hazards resulting from dropped tools. These may include personal injury and material damage.

GRIPPS® does not approve use of this device for any activities not described in the User Instructions. This device is not intended to be used in any recreational activity, as a personal fall-arrest device or in any other manner not described herein.

MARNING Misuse of this device could result in serious injury or death.

Adhere to all manufacturer recommendations regarding the operation and maintenance of this device. For additional information, contact GRIPPS® customer support.

Read and adhere to the following in order to ensure correct operational functionality:

- Your DTP should never be used as a personal fall-arrest device or restraint system.
- Do not use this device with tools that exceed the specified maximum load/weight.
- A DTP device used in applications that exceed the limits of operation specified by the manufacturer should be considered unsafe and should be replaced.
- Do not tether a tool over 2.5kg/5.5lbs directly to your clothing or person.
- Inspect your DTP device before each use.
- Ensure the DTP device is securely connected to a load rated tool connector or anchor point before use.
- Inspect any tool connector point before it is connected to the DTP device
- Modification of the DTP device voids all warranties and violates manufacturer recommendations.
- Do not use a tool that cannot be connected to your DTP in the manner specified by GRIPPS®.
- It is unsafe to extend the length of the DTP product by any
- Do not use this product if it will create an unsafe working
- Ensure the tether does not become entangled with other workers, yourself or surrounding objects. Leave enough space between yourself and any hazards so that a tool on a fully extended tether can swing unobstructed should it fall.
- Avoid contact between the tether and rough or sharp edges.
- Use extra precaution around moving machinery, moving parts, electrical hazards, extreme temperatures, chemical hazards. or combustion hazards.

- All connected tools and equipment, including connection points, must be compatible for use with this DTP device.
- Always wear appropriate personal protective equipment.
- If a tether has arrested a dropped tool or object, it should be taken out of service and replaced.
- All procedures shown in this instruction are for GRIPPS® Coil Tether products only.

GENERAL USE AND CARE

GRIPPS® Coil Tethers are designed to be used with most tools. They are engineered to stay out of the way when not in use and provide versatility and access when the attached tool is required. Dual carabiners provide flexible tethering options.

Recommended Use of GRIPPS® Coil Tethers:

- Only use in combination with GRIPPS® Tool Connectors.
- Use H01062 & H01068 Coil Tethers on tools under 1.0kg/2.2lbs.
- Use H01069 Coil Tether on tools under 2.3kg/5.0lbs.
- H01068 & H01062 Coil Tethers are suitable for use with the full range of GRIPPS® Gloves.
- If working in electrical environments, use the H01062 model Coil Tether.

Before Use:

Thoroughly inspect your GRIPPS® DTP device before each use. Do not use any component that presents deformities or deterioration. Inspect all material including the carabiner and tether.

Coil Tether Installation:

To attach to Tool Connector point

1. If using carabiner model, twist the carabiner lock in a counterclockwise direction to unlock. Push the carabiner latch in and away from the carabiner opening. Connect the carabiner to the connector on the tool



2. If using single-action poly or metal models, push tool connector into the carabiner until it clicks shut



To attach to Tether Anchor point

1. If using the poly single-action model, connect the carabiner to the load rated anchor point on the back of the glove.



2. Alternatively attach tether to another load-rated anchor point such as holster D-Rinas or a GRIPPS® Belt-Loop Anchor.



Clean and inspect the Coil Tether and connected tool. For tougher stains, use warm water and a mild soap or detergent. Do not use again until dry.

Store in a clean and dry environment. Proper care will help to ensure that it will operate effectively and extend its service.





instagram.com/grippsglobal



facebook.com/grippsglobal



Contact Support On support@gripps.com.au +61 3 8383 9458 #ConquerGravity