Assembly Instructions



600 Gun Cabinet

Components List:

Upper Cabinet

B.	Top Panel	1pc
C.	Upper Barrel Rest	1pc
D.	Upper Back Panel	1pc
E.	Left Side Panel	1pc
F.	Right Side Panel	1pc
G.	Door Panel	1pc
H.	Drawer Top Panel	1pc
L	Lower Barrel Rest	1pc


Lower Cabinet

J.	Front Panel With Locklpc
	Bottom Back Panel1pc
L.	Bottom Front Rail
M.	Bottom Panel1po
N.	Left Side Panel1pc
A.	Right Side Panel


Hardware List:


1. "L"Wrench	1pc
2. Threaded Pin:	2pcs
3. Arch Nut:	2pcs
4, Round Head Wood Screw:	33pcs
5. Flat Head Hinge Screw:	20pcs
6. Dowel:	22pcs
7. Drawer Pull	1pc
8. Pull Screw:	2pcs
9. Door Spacer Block:	1pc
10. Metal Bullet:	10pcs
11. Machine Screw:	8pcs
12. Wrench	1pc
13. Keys	2pcs
14. Tipping restraint	1pcs
15. Hinges	5pcs
16. Leveler	4 pcs

Upper Cabinet



Lower Cabinet






Post Office Box 111 - Webb City, Missouri 64870 - 0111
Toll Free - 888 - 673 - 9080
Fax - 417 - 673 - 9081
To order replacement parts online please visit:
www.AmericanFurnitureClassics.com
or Email:
service@americanfurnitureclassics.com

Production date: August/2016


Page 1 of 6

Unpack carton on a clean, smooth surface and inventory parts.

Important: Always Insert Metal Bullets so that the X in the end of the Bullet faces out of the holes and that the Threaded Hole is turned vertically for alignment with Machine Screws.




Step 1:
Attach Left & Right Side Panel (N & A) to the Bottom Front Rail (L) by inserting Dowel (6).




Step 2:


Attach the assembled unit completed in Step 1 to the Bottom Panel (M) by inserting Dowel (6) into the non-threaded holes. Insert Machine Screw (11) through the bottom of Bottom Panel (M) and into the Metal Bullet (10) inserted into the small holes in Side Panel (N & A). Tighten the Machine Screw (11) using the "L" Wrench (1).




Step 1

Step 2






Assembly Instructions: 600 Gun Cabinet Install the lock of the door



- Step 12:
- 1. Insert Lock (B) into the Lock Hole (A).
- 2. Put Gear Washer (C) on the Lock (B).
- 3. Screw Nut (D) on Lock (B).
- 4. Place Pin (E) onto Lock Barrel (B), make sure the rectangular hole on Pin (E) and on Lock Barrel (B) are aligned properly.
- 5. Place Washer (F) onto Lock Barrel (B) and insert Screw (G) into the end of Lock Barrel (B).
- 6. Tighten or loosen Screw (G) until Pin (E) fits tightly behind the back edge of the Door Frame when door is fully closed and lock is in locked position.

Attach Drawer Pull (7) onto the outside of Front Panel With Lock (J) using Pull Screw (8). Tighten with Phillips Head Screwdriver (Not Provided).



Assembly is now complete.

For extra safety we suggest you install the "Furniture Tipping Restraint" Provided in the separate hardware bag.