

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name: HALO ELITE HARD GEL (SCULPTING CLEAR)

Product Code: N3104, N3105, N3106

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Hard Gel

1.3 Details of the supplier of the safety data sheet

Company Name: Pure Nails

Unit 10 Saracen Close Gillingham Business Park

Gillingham, Kent

ME8 0QN

Telephone: 01634 671122
Website: www.purenails.co
E-mail: marketing@purenails.co

1.4 Emergency telephone number

01634 671122

SECTION 2: HAZARDS IDENTIFICATION

2.1 Hazard Identification

WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. CAUSES EYE IRRITATION. Hazard Statements (H):H317 - May cause an allergic skin reaction. H320 - Causes eye irritation. Precautionary Statements (P): P261 - Avoid breathing fumes/gas/vapors/spray. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves. P302 + P352 - IF ON SKIN - wash with soap and warm water. P305 + P351 + P338 - IF IN EYES - Rinse continually with wa



wash with soap and warm water. P305 + P351 + P338 - IF IN EYES - Rinse continually with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing. P333 + P313 - If skin reaction or a rash occurs, get medical attention. P337 + P313 - if eye irritation persists, P321 - for specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P501 - Dispose of contents/container to a licensed treatment, storage, or disposal facility (TSDF).

2.2 Routes of entry Inhalation: YES Absorption: YES

Ingestion: YES

2.3 Effects of Exposure

Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.

Eyes & Skin: The liquid may produce eye discomfort and can cause temporary impairment of vision and/or transient eye inflammation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns, and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to the skin, especially after prolonged contact. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.

Inhalation: Vapors of this product may be moderately irritating to the nose, throat, and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion and difficulty breathing. Inhalation of concentrated vapors can cause central nervous system depression (e.g., drowsiness, headaches, nausea). Odor may give some warning of exposure, but odor fatigue may occur.



2.4 Symptoms of overexposure

Symptoms of skin overexposure may include redness, itching and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.

2.5 Acute Health Effects

Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.

2.6 Chronic Health Effects

The material may cause an allergic reaction for some sensitive individuals.

2.7 Target Organs

Eyes, skin

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

			EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m3)									
CHEMICAL NAME(S)	CAS No.	RTECS No. EINECS No			ACGIH		NOHSC		OSHA					
	CAS NO.		EINECS NO.		ppm			ppm		ppm			OTHER	
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
Bis-HEA Poly(1,4-														
butanediol)-9 / IPDI	NA	NA	NA	20-60	NA	NA	NF	NF	NF	NA	NA	NA		
Copolymer														
Bis-HEMA														
Poly(neopentyl Glycol	l _{NA}	NA	NA	20.00	N 1 A	NI A	NF	NF	NF	NA	NI A			
Adipate)/ IPDI	INA	INA	NA NA	20-60	INA	NA	INF	INF	NF	INA	NA	NA		
Copolymer									1					
Trimethylolpropane	3290-92-4	NA	NA	5-20	NA	NA	NF	NF	NF	NA	NA	NA		
trimethacrylate	3230-32-4	IVA	INA	3-20	INA	IVA	INF	INF	INF	INA	IVA	IVA		
Tripropyleneglycol	42978-66-5	NA	NA	5-20	NA	NA	NF	NF	NF	NA	NA	NA		
diacrylate	429/0-00-5	42976-00-3	IVA	INA	3-20	INA	INA	INF	INF	INF	INA	INA	IVA	
Silica	60676-86-0	NA	204-337-6	1-8	NA	NA	NF	NF	NF	NA	NA	NA		
1-Hydroxylcyclohexyl														
phenyl ketone	947-19-3	3 NA	213-426-9	0.1-5	NA	NA	NF	NF	NF	NA	NA	NA		
phenyl ketone														
Benzophenone	116-61-9	NA	204-337-6	0.1-5	NA	NA	NF	NF	NF	NA	NA	NA		
•		Aquatic chromic 2; Aquatic acute 1; H411, H400												
bis-trimethylbenzoyl	75980-60-8	NA	423-340-5			NA	NF	NF	NF	NA	NA	NA		
phenyl phosphine							hronic 4;	H317, H4	13					
CL 77001 /Titorium	<u> </u>	<u> </u>	MAY ALSO	J CON	AIN	: 	I		I		l	l	l	
CI 77891 (Titanium Dioxide)	13463-67-7	XR2275000	236-675-5	≤1.0	NA	NA	NF	NF	NF	NA	NA	NA		
CI 15850 (Red 6)	17852-98-1	NI A	241-806-4	≤1.0	NA	NA	NF	NF	NF	NA	NA	NA		
, ,	+	NA NA		≤1.0 ≤1.0	NA	NA	NF NF	NF NF	NF NF	NA	NA	NA		
CI 47005 (Yellow 10)	8004-92-0	NA	305-897-5	51.0	NA	INA	INF	INF	INF	INA	INA	IVA		
CI 77491 (Iron Oxides)	1309-37-1	NO7420000	215-168-2	≤1.0	NA	NA	NF	NF	NF	NA	NA	NA		
·	12227-89-3	NA	215-277-5	≤1.0	NA	NA	NF	NF	NF	NA	NA	NA		
CI77499 (Iron Oxides)														
** Due to trade secret information, more detailed concentrations of the ingredients cannot be provided.														

SECTION 4: FIRST AID MEASURES

4.1 First Aid

Ingestion: If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Skin & Eyes: If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and closeeyelid(s) to ensure thorough irrigation. Seek immediate medical attention. If problem persists, seek immediate medical attention. If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water followed by a thorough washing of the affected area with plenty of soak and waster. Remove all

HALO ELITE HARD GEL (SCULPTING CLEAR)



contaminated clothing including footwear and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately.

Inhalation: Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention.

4.2 Medical Conditions Aggravated by Exposure

Pre-existing dermatitis, other skin conditions and disorders of the target organs (eyes, skin)

The company desiring the contraction of the contraction	the externing derivatively extreme extra constitutions and discontinuous extra tangent or Barrio (eyes) extra f					
HEALTH	1					
FLAMMABILITY	0					
PHYSICAL HAZARDS	0					
PROTECTIVE EQUIPTMENT	В					
EYES SKIN						

SECTION 5: FIREFIGHTING MEASURES

5.1 Flashpoint & Method

>100°C (> 212 °F)

5.2 Autoignition Temperature

NΑ

5.3 Flammability Limits

Lower Explosive Limit (LEL): NA
Upper Explosive Limit (UEL): NA
5.4 Fire & Explosion Hazards

When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO2 and Nox)

5.5 Extinguishing Methods

Water, Foam, CO2, Dry Chemical

5.6 Fire Fighting Procedures

First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH approved, self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water or other environmentally sensitive areas. If necessary, rinse contaminated equipment with soapy water before returning to service.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Spills

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., 1 gallon [3.785 liters]) wear appropriate personal protective equipment (e.g., goggles & gloves). Maximize ventilation (open doors and windows). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state, and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. For large spills (e.g., > 1 gallon [3.785 liters]) deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state, and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse.

SECTION 7: HANDLING AND STORAGE

7.1 Work & Hygiene Practices

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap and water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink, or smoke while handling this product.



7.2 Storage & Handling

Use and store in a cool, dry, well ventilated location. Keep away from excessive heat. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devises. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. KEEP AWAY FROM CHILDREN AT ALL TIMES!

7.3 Special Precautions

Do not store where temperatures can exceed 50 $^{\circ}$ C (122 $^{\circ}$ F).

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Ventilation & Engineering Controls

Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye wash station).

8.2 Respiratory Protection

No special respiratory protections is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR § 1910.134, application U.S. State regulations or the Candaian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC Member States or Australia.

8.3 Eye Protection

Wear protective eyewear (e.g., safety glasses with side shields) always when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.

8.4 Hand Protection

None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., >1 gallon [3.785 liters]), wear nitrile or impervious gloves.



No apron required when handling small quantities. When handling large quantities (e.g., . 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Density

1.1

9.2 Boiling Point

NA

9.3 Melting Point

ND

9.4 Evaporation Rate

NΑ

9.5 Vapor Pressure

ИD

9.6 Molecular Weight

NE

9.7 Appearance & Colour

Clear or pigmented liquid

9.8 Odor Threshold

NE

9.9 Solubility

Not Soluble

9.10 pH

NA



9.11 Viscosity

Approximately 1,500,000 cps

9.12 Other Information

NA

SECTION 10: STABILITY AND REACTIVITY

10.1 Stability

Relatively stable under ambient conditions when stored properly.

10.2 Hazardous Decomposition Products

If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon and nitrogen).

10.3 Hazardous Polymerization

Will not occur

10.4 Conditions to avoid

Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks and flame.

10.5 Incompatible Substances

Strong oxidizers, peroxides, strong acids or alkalis.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Toxicity Data

This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product which are found in scientific literature. These data have not been presented in this document.

11.2 Acute Toxicity

See section 2.5

11.3 Chronic Toxicity

See section 2.6

11.4 Suspected Carcinogen

The ingredients of this product are not listed as carcinogens by the National Toxicology Program and have not been evaluated by the Internail Agency for Research on Cancer or the American Conference of Government Industrial Hygenists.

11.5 Reproductive Toxicity

This product is not reported to cause reproductive toxicity in humans.

11.6 Mutagenicity

This product is not reported to produce mutagenic effects in humans.

11.7 Embryotoxicity

This product is not reported to produce mutagenic effects in humans.

11.8 Teratogenicity

This products is not reported to cause teratogenic effects in humans.

11.9 Irritancy of Product

See Section 2.3

11.10 Biological Exposure Indicies

NE

11.11 Physician Recommendations

Treat syptomatically

SECTION 12: ECOLOGICAL INFORMATION

12.1 Environmental Stability

This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds.

12.2 Effects on Plants & Animals

There is no specific data availble for this product on plant life.



12.3 Effects on Aquatic Life

There is no specific data available for this product on aquatic life.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste Disposal

Dispose inaccordance with local, state and Federal waste laws.

13.2 Special Considerations

This material becomes an inert plastic upon prolonged exposure to sources of UV light and sunlight. Disposal of inert plastics is safer for the environment and is more easily handled for disposal according to local, state and Federal regulations.

SECTION 14: TRANSPORT INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADR and the CTDGR.

14.1 49 CFR (GRD)

NOT REGULATED

14.2 IATA (AIR)

NOT REGULATED

14.3 IMDG (OCN)

NOT REGULATED

14.4 TDGR (Canadian GND)

NOT REGULATED

14.5 ADR/RID (EU)

NOT REGULATED

14.6 MEXICO (SCT)

NOT REGULATED

14.7 ADGR (AUS)

NOT REGULATED

SECTION 15: REGULATORY INFORMATION

15.1 SARA Reporting

NA

15.2 SARA Threshold Planning Quantity

NΑ

15.3 TSCA Inventory Status

All components of this product are listed in the TSCA Inventory or are exempt

15.4 CERCLA Reportable Quantity (RQ)

NA

15.5 Other Federal Requirements

This products complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).

15.6 Other Canadian Regulations

This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are on the Priorities Substances List.



15.7 State Regulatory Information

Ingredients in this mixture are found on the following state criteria lists: Titanium Dioxide is listed on the following state criteria list(s): Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposure List (WA). Benzophenone is listed on the following state criteria list(s): MN. No toher ingredients in this product, present

HALO ELITE HARD GEL (SCULPTING CLEAR)



in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnisota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).

15.8 67/548/EEC (European Union), Australian NOHSC:2011 (2003), and GHS Requirements: The primary cononents of this product are not listed in Annex 1 of EU Directive 67/548/EEC. Irritant (Xi). Risk Phrases (R): 36/37/38 - Irritating to eyes, respiratory system and skin. Safety Phrases (S): 2-23-29 - Keep out of reach of Children. Do not breath gas, fumes, vapor or spray. Do not empty into drains.



SECTION 16: OTHER INFORMATION

16.1 Other Information

WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. Avoid breathing fume, gas, mist, vapors, spray. Wear potective gloves and eye/face protection. IF ON SKIN - Wash with soap and water. IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to docontinue rinsing. If skin irritation or a rash occurs - get medical advice/attention. Do not take internally. Keep away from heat and open flame. KEEP OUT OF THE REACH OF CHILDREN.

16.2 Terms & Definitions

Please see last page of this SDS

16.3 Disclaimer

This Safety Data Sheet (SDS) is offered persuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other governement regulations must be reviewed for applicability to this product. To the best of McConnell Labs' knowledge, the information contained herein is reliable and accurate as of the date it was prepared; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.



DEFINITION OF TERMS

CAS No.	Chemical Abstract Service Number	
EXPOSURE	LIMITS IN AIR:	
ACGIH	American Conference on Governmental Industrial Hygienists	
TLV	Threshold Limit Value	
OSHA	U.S. Occupational Safety and Health Administration	
PEL	Permissible Exposure Limit	
IDLH	Immediately Dangerous to Life and Health	$\overline{}$

FIRST AID MEASURES:

Gerdiopulmonary resuscitation - method is which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood
and provide gaven to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard				
1	1 Slight Hazard				
2	Moderate Hazard				
3	Severe Hazard				
4	Extreme Hazard				



PERSONAL PROTECTION RATINGS:

Α	(
В	(1		
С		1		
D	1	1		
E	(3)	1	☻	
F	(3)	1		0







Full Face Respirator Dust & Vapor Half-Mask Respirator OTHER STANDARD ABBREVIATIONS:


NA.	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

DOGODA DOLIDAD

0	Minimal Hazard
- 1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
- 4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Redicactive



TOXICOLOGICAL INFORMATION:

LD ₀₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₆₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TO _{to}	Lowest dose to cause a symptom
TCLe	Lowest concentration to cause a symptom
TD _{to} , LD _{to} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC ₀ , LC ₁₀ , & LC ₀	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL	Median threshold limit
log Kow or log Koo	Coefficient of Oli/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL.	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances Ust
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class.)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	((a)	(9)	①	②	<u></u>	Ř
Class A	Clare B	Olass C	Class D1	Class D2	Close D3	Class E	Class F
Compressed	Florenskie	Oxidizing	Toxic	irritation	Infectious	Corresive	Reactive

EC (67/548/EEC) INFORMATION:

-0	鐅	*	*		-94	×	×
0	Ε	F.	N	0	т	36	Xn
Corrosive	Explosive	Planmoble	Harreful	Owlitzing	Toxic	Initiati	Hawital

CLP/GHS (1272/2008/EC) PICTOGRAMS:

>	③	③	\Diamond	③	③		③	(£)
GHB01	GH502	GH503	04504	OH965	GH908	GH907	GH900	GHB09
Explosive	Flammable	Owdper	Pressunzeo	Corrosive	Total	Hamful initoling	Health Hazard	H SVET TITLETT