

## SAFETY DATA SHEET

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier****Product Name:** VITAMIN POWER**Product Code:** N2297**1.2 Relevant identified uses of the substance or mixture and uses advised against****Use of substance / mixture:** Nail Conditioner**1.3 Details of the supplier of the safety data sheet****Company Name:** Pure NailsUnit 10 Saracen Close  
Gillingham Business Park  
Gillingham, Kent  
ME8 0QN**Telephone:** 01634 671122**Website:** www.purenails.co**E-mail:** marketing@purenails.co**1.4 Emergency telephone number**

01634 671122

## SECTION 2: HAZARDS IDENTIFICATION

**2.1 Classification of the substance or mixture****Classification according to WE/1272/2008 (CLP):**

Flam Liq. 2	H225	Highly flammable liquid and vapour
Eye Irrit. 2	H319	Causes serious eye irritation
STOT SE 3	H336	May cause drowsiness or dizziness

**GHS/CLP Classification:****Signal word: Danger****Hazard statements:**

Eye Irrit. 2	H319	Causes serious eye irritation
Flam Liq.2	H225	Highly flammable liquid and vapour
STOT SE 3	H336	May cause drowsiness or dizziness
	EUH066	Repeated exposure May cause skin dryness or cracking

**Precautionary statements:**

P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P243	Take precautionary measures against static discharge.
P305+P351+P313	IF IN EYES: Rinse cautiously with water for several minutes. Get medical advice/attention.

**2.2 Label Elements**

NDA

**2.3 Other Hazards**

NDA

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**3.1 Substances**

Nitrocellulose with nitrogen content &lt;12,2% and at a concentration &lt;20% in a blend of solvents

Chemical Identity and concentration range	CAS No.	EINECS No.	GHS/CLP

Ethyl Acetate	25.0-50.0%	141-78-6	205-500-4	Flamm. Liq. 2 H225; Eye Irrit. 2 H319; STOT SE 3 H336; EUH066
Butyl Acetate	25.0-50.0%	123-86-4	204-658-1	Flamm. Liq. 3 H226; STOT SE 3 H336; EUH066
Nitrocellulose	10.0-25.0%	9004-70-0	N/E	Flamm. Liq. 1 H224
Isopropyl Alcohol	5.0-10.0%	67-63-0	200-661-7	Flamm. Liq. 2 H225; Eye Irrit. 2 H319; STOT SE 3 H336

Full text of H-phrases is provided in section 16.

### 3.2 Mixtures

NDA

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

#### First aid for skin:

Remove contaminated clothing and wash before reuse. Remove and destroy contaminated shoes. Flush with plenty of water.

#### First aid for eye:

Immediately wash the eyes with plenty of water for at least 10 min holding the eye open. Obtain medical attention urgently.

#### First aid in case of ingestion:

Get medical attention IMMEDIATELY.

#### First aid in case of inhalation:

Remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Get medical attention.

### 4.2 Most important symptoms and effects both acute and delayed

#### Effects of overexposure:

Cause eye irritation. Harmful if swallowed. May cause nose and throat irritation. Causes skin irritation. May affect the brain or nervous system, causing dizziness, headache or nausea. Harmful if inhaled.

#### Other effects of overexposure may include:

Narcosis, conjunctivitis, loss of coordination, vomiting, lacrimation, redness and swelling of eyes, difficulty with speech, reduced visibility, abdominal pain, swelling and redness of skin, fatigue, cough, dermatitis, drowsiness, unconsciousness.

#### Primary Route(S) of entry:

Inhalation, skin contact, eyes.

#### Medical conditions that can be aggravated:

No information available.

#### Chronic health hazards:

#### Repeated Overexposure to this product may cause:

Lung damage, liver abnormalities, kidney damage, central nervous system damage, blood effects.

#### Notice:

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents of this package may be harmful or fatal.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media

Foam, carbon dioxide or dry chemical

### 5.2 Special hazards arising from the substance or mixture

Water may be ineffective in fighting fire. If water is used to cool closed containers to prevent pressure build-up, fog nozzles are preferred. Full protective equipment, including self-contained breathing apparatus is needed to protect fire-fighters from exposure to coatings hazardous ingredients and hazardous decomposition products

### 5.3 Advice for firefighters

During emergency conditions, overexposure to decomposition products may cause a health hazard; symptoms may not be immediately apparent. Obtain medical attention.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Wear appropriate safety equipment as listed in Section 8. Absorb on inert material and dispose of as below.

### 6.2 Environmental precautions

Prevent further leakage or spillage. Do not discharge into the drains/ surface waters/ groundwater

### 6.3 Methods and material for containment and cleaning up

Dispose in accordance with federal, state and local regulations. Incineration is the preferred method of disposal.

### 6.4 Reference to other sections

Disposal of the product - Section 13

Personal protection – Section 8

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

When using, do not eat, drink or smoke. Take off contaminated clothing immediately. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and/ or exhaust in work rooms.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in well-ventilated area. Keep containers closed when not in use. Store away from ignition sources. All equipment should be grounded. Avoid strong oxidizing agents, store in a clean, dry area. All precautions must be observed. Empty container may retain product residues (vapour or liquid).

### 7.3 Specific end use(s)

NDA

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

Chemical Identity/ CAS	NDS [mg/m <sup>3</sup> ]	NDSch [mg/m <sup>3</sup> ]	NDSP	DSB
Ethyl Acetate 141-78-6	200	950	-	-
Butyl Acetate 123-86-4	200	950	-	-
Isopropyl Alcohol 67-63-0	900	1200	-	-

### 8.2 Exposure controls

Good personal hygiene practices are always required when handling chemicals. These practices include, but are not limited to washing when safety equipment is removed, at the end of each shift when going on breaks and especially if contamination occurs

#### 8.2.1 Occupational exposure controls

##### Respiratory protection

Wear an appropriate, properly fitted respirator (NIOSH/ MSHA approved) during application and handling unless air monitoring demonstrates vapour/ mist levels below applicable limits. Follow respirator manufacturers recommendations for selection and use.

##### Hand protection

Chemical resistant protective gloves (such as Neoprene or Butyle Rubber) should be worn when handling this product. Check with glove manufacturer to determine proper glove type)

##### Eye protection

Splash-proof chemical goggles should be worn.

**Ventilation**

Sufficient ventilation must be provided to maintain airborne concentrations below Limits as listed in Section 8.

**Other protective equipment**

Impervious clothing and boots should be worn. Eye bath and safety shower should be provided.

**8.2.2 Environmental exposure controls**

Any reject of product in the sewer stream must be avoided

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**9.1 Information on physical and chemical properties**

<b>Appearance</b>	Viscous liquid	
<b>Colour</b>	Blue	
<b>Odor &amp; Odor Threshold</b>	Fruity (Esters)	
<b>Olfactive Threshold</b>	50 ppm (Ethyl Acetate)	
<b>Melting Point</b>	-84°C (Ethyl Acetate)	
<b>Boiling Point</b>	77°C at 1013 hPa (Ethyl Acetate)	
<b>Boiling Range</b>	77 to 130°C	
<b>Specific Gravity</b>	0.960-0.980	
<b>Vapor Pressure (hPa)</b>	100 (20°C) (Ethyl Acetate)	
<b>Vapor Density (Relative: Air=1)</b>	3.04 (Ethyl Acetate)	
<b>Flash Point</b>	-5°C	
<b>Auto-ignition Temperature</b>	460°C	
<b>Flammable Limit(%v/v)</b>	<u>Upper</u>	<u>Lower</u>
Ethyl Acetate	11.0	2.2
Buthyl Acetate	7.6	1.7
Isopropanol	12.0	1.8
<b>pH</b>	Not applicable	
<b>Solubility In Water (20°C)</b>	Insoluble	
<b>Water/ Octanol Distribution Coeff</b>	Log Kow=0.60 (Ethyl Acetate)	
<b>Evaporation Rate</b>	Slower than ether	
<b>Viscosity (Brookfield)</b>	140 to 280 mPas	

**9.2 Other information**

NDA

## SECTION 10: STABILITY AND REACTIVITY

**10.1 Reactivity**

Material is stable under non-emergency conditions.

**10.2 Chemical stability**

Material will not undergo hazardous polymerization.

**10.3 Possibility of hazardous reactions**

NDA

**10.4 Conditions to avoid**

Heat, sparks, open flame.

**10.5 Incompatible materials**

Sodium hydroxide, nitric acid, oxidizers, acids, alkali, metal, amines.

**10.6 Hazardous decomposition products**

Methane, oxides of nitrogen. Carboxylic acids, various hydrocarbons, oxides of carbon, aldehydes, hydrogen cyanide, acids.

## SECTION 11: TOXICOLOGICAL INFORMATION

**11.1 Information on toxicological effects**

Ingredient	LD50 (Oral, Rat)	LC50 (Inhal, Rat)	LC (Dermal, Rabbit)
Butyl acetate	14000 mg/kg	2000 ppm	-
Ethyl acetate	11300 mg/kg	1600 ppm (8h)	-

Isopropyl alcohol	5840 mg/kg	16000 ppm (8h)	13000 mg/kg
-------------------	------------	----------------	-------------

**Skin contact:** Prolonged contact can cause crack in skin.

**Eye contact:** Can cause irritation of the conjunctive. Can cause injury of the cornea.

**Ingestion:** Important ingestion can cause nausea and a great narcosis with weakness, drowsiness and loss of consciousness.

**Inhalation:** Can cause irritation of the nose and the throat. At high concentration can cause narcosis.

**Sensitization:** N/DA

**Mutagenicity:** In accordance with 29CFR1910.1200, this product contains no ingredients listed by NTP, IRAC or OSHA as carcinogenic

**Sub-chronic Toxicity:** N/DA

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

Any reject of product in the sewer stream must be avoided Water hazard class WGK1: Slightly hazardous for water.

### 12.2 Persistence and degradability

NDA

### 12.3 Bioaccumulative potential

NDA

### 12.4 Mobility in soil

NDA

### 12.5 Results of PBT and vPvB assessment

NDA

### 12.6 Other adverse effects

NDA

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Incinerate in a furnace where permitted under national and local regulations

## SECTION 14: TRANSPORT INFORMATION

### 14.1 UN Number

UN 1266

### 14.2 UN Proper Shipping Name

PERFUMERY PRODUCTS (Source of danger: Ethyl acetate, Butyl acetate, Nitrocellulose, Isopropyl alcohol)

### 14.3 Transport hazard class(es)

3

### 14.4 Packing group

II

### 14.5 Environmental Hazards

Slightly hazardous for water.

### 14.6 Special precautions for user

Limited Quantity: 5l/30kg (gross)

Certified packaging: Internal packaging: metal, glass, plastic; External packaging: Carton 4G

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

NDA

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP and ODS's), as defined by the U.S. Clean Air Act: This product does not contain any ODS's (Ozone Depleting Substances).
------------------------	---

Clean Water Act: Priority Pollutant	This product contains no chemicals listed under the U. S. Clean Water Act Priority Pollutant List.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are: <ul style="list-style-type: none"> <li>• Immediate (acute) health hazard</li> <li>• Delayed (chronic) health hazard</li> <li>• Reactive hazard</li> </ul>
RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261)
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances.
SARA Title III: Section 302 (RQ)	This product contains the following chemicals regulated under Section 302 as extremely hazardous chemical for emergency release notification (CERCLA List)
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: <ul style="list-style-type: none"> <li>• Immediate (acute) health hazard</li> <li>• Delayed (chronic) health hazard</li> <li>• Reactive hazard</li> </ul>
SARA Title III: Section 313:	This product contains following chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
TSCA Section 8(b): Inventory: TSCA Significant New Use Rule:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements. None of the chemicals listed have a SNUR under TSCA.
EINECS: European Inventory:	Nail conditioner: <b>Hazard statements: H225</b> Highly flammable liquid and vapour, <b>H319</b> Causes serious eye irritation; <b>H336</b> May cause drowsiness or dizziness <b>Precautionary statements: P210</b> Keep away from heat/sparks/open flames/hot surfaces. – No smoking; <b>P243</b> Take precautionary measures against static discharge; <b>P305+P351+P313</b> IF IN EYES: Rinse cautiously with water for several minutes. Get medical advice/attention

## 15.2 Chemical safety assessment

NDA

## SECTION 16: OTHER INFORMATION

### Full range of H-Phrases from Section 2 and 3.

Flam. Liq. 1	H224	Extremely flammable liquid and vapour
Flam. Liq. 2	H225	Highly flammable liquid and vapour
Flam. Liq. 3	H226	Flammable liquid and vapour
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness
	EUH066	Repeated exposure may cause skin dryness or cracking.

### P-Phrases

P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P243	Take precautionary measures against static discharge.
P305+P351+P313	IF IN EYES: Rinse cautiously with water for several minutes. Get medical advice/ attention

### Disclaimer/Statement of Liability:

All information appearing herein is based upon data obtained from the manufacturers and/or recognised technical sources. While the information is believed to be accurate, Pure Nails, makes no representation as to

VITAMIN POWER

# PURENAILS

its accuracy or sufficiency. Judgement as to the suitability of information herein for purchasers purposes are necessarily purchasers responsibility. Therefore, although reasonable care has been taken in the preparation of such information, Pure Nails, extends no warranties, makes no representations or assumes no responsibility as to accuracy or suitability of such information for application to purchasers intended purpose or for consequences of its use.