


# Indoor Flexible LED Display Modules


Flexible Indoor Full Color SMD LED Module  
SMD LEDs fixed on bared flexible PCB,  
used for LED display screen that has curve or ribbon.






# LED Display Modules Dimensions


---




240\*120mm



200\*150mm



256\*128mm



320\*160mm

# LED Flexible Modules Parameters

240\*120MM

Models	Pixel/m <sup>2</sup>	Resolution	Dimension	Scan	Refresh Rate	LED Model	Brightness/m <sup>2</sup>
HKXR1.25	640000	192*96	240*120mm	1/48	≥3840Hz	SMD1010	700-900cd
HKXR1.5625	409600	128*96	200*150mm	1/48	≥3840Hz	SMD1212	700-900cd
HKXR1.579	401111	152*76	240*120mm	1/38	≥3840Hz	SMD1212	700-900cd
HKXR1.667	360000	144*72	240*120mm	1/24	≥3840Hz	SMD1212	700-900cd
HKXR1.875	284444	128*64	240*120mm	1/32	≥3840Hz	SMD1212	700-900cd

# LED Flexible Modules Parameters

240\*120mm

Models	Pixel/m²	Resolution	Dimension	Scan	Refresh Rate	LED Model	Brightness/m²
HKXR2.0	250000	120*60	240*120mm	1/30	≥3840Hz	SMD1515	700-900cd
HKXR2.5	160000	96*48	240*120mm	1/24	≥1920Hz	SMD1515	700-900cd
HKXR3	111111	80*40	240*120mm	1/20	≥1920Hz	SMD2121	700-900cd
HKXR4	62500	60*30	240*120mm	1/15	≥1920Hz	SMD2121	700-900cd

# LED Flexible Modules Parameters

256*128mm							
Models	Pixel/m <sup>2</sup>	Resolution	Dimension	Scan	Refresh Rate	LED Model	Brightness/m <sup>2</sup>
HKXR2	250000	128*64	256*128mm	1/32	≥1920Hz	SMD1515	700-900cd
HKXR4	62500	64*32	256*128mm	1/16	≥1920Hz	SMD2121	700-900cd
320*160mm							
Models	Pixel/m <sup>2</sup>	Resolution	Dimension	Scan	Refresh Rate	LED Model	Brightness/m <sup>2</sup>
HKXR1.86	288906	172*160	320*160mm	1/43	≥3840Hz	SMD1212	700-900cd
HKXR2	250000	160*80	320*160mm	1/40	≥3840Hz	SMD1515	700-900cd
HKXR2.5	160000	128*64	320*160mm	1/32	≥1920Hz	SMD1515	700-900cd
HKXR3	105625	104*52	320*160mm	1/26	≥1920Hz	SMD2121	700-900cd



# Product Applications

---



## Features:

- The module is soft, unique in selection and easy to install;
- The mask is made of silicone, which is smooth and has no color difference;
- It is flexible and can be made into any shape according to needs;
- When it is made into a cylindrical shape, the picture is smooth and beautiful. The signal lines and power lines between the cabinets adopt KUAI quick-connect connectors, which are easy and fast to install and can be used with professional audio and video processing systems;
- The product supports a variety of signal inputs, such as AV, DP, VGA, DVI, YPbPr, HDMI, SDI, H-SDI, etc.;
- Standard interface definition, supporting multiple control card drivers, such as Lingxingyu series, Colorlight, Nova, Depuda, Zhongqing, Mooncell, etc.










LED Column Display

Made with HKXR2.5

32SQM





LED Ball

Product Used: HKXR2

400SQM



LANCÔME  
兰蔻菁纯  
11月甄享礼遇

LANCÔME  
ABSOLUE


Lancome branding  
HKXR3  
26SQM



LED Tape Screen

HKXR4

70SQM







LED Display Tree  
HKXR1.56  
31SQM



LED Display Tree

HKXR1.5625

68SQM

