



ENVIRO WB SEALER

WATER BASED SEALER FOR ENVIRO STAINS



ENVIRO WB SEALER IS A TOUGH NON-YELLOWING ACRYLIC SEALER FOR USE INTERIOR AND EXTERIOR TO SEAL AND PROTECT SURFACES DECORATED WITH ENVIRO WB STAIN.

PRODUCT HIGHLIGHTS

- **Non-flammable:** Enviro WB Sealer has no flammable hazard when used indoors or out.
- **No hazardous fumes or odors:** It is not necessary to wear a protective breathing apparatus, and normal ventilation is adequate.
- **Fast Drying:** Enviro WB Sealer dries to the touch in 30 to 45 minutes, and can be recoated in one hour normally. Two coats are recommended, but the floor can be walked on the same day, usually after 12 hours.
- **Non-slip and water resistant:** The coating is not glossy, and does not present a hazardous walking surface wet or dry.
- Extra protection in interior applications. After the coating has dried overnight it can be top coated with EZ-Glo acrylic polish to produce a glossy, renewable wear surface. With normal easy regular maintenance, the Enviro Sealer will never wear out or need replacing.
- Available in 1 gallon and 5 gallon.

USES

Enviro WB Sealer is used as a final protective coating over Enviro Stained concrete floors, counter tops, etc. for use indoors and out with low odor and no flammable hazard.

QUICK LOOK:

Type: Water dispersed acrylic polymer coating

Toxicity: Non-toxic

VOC's: Less than 100gm/L

Flammability: Non-flammable

Composition: Acrylic copolymer emulsion

Color: Colorless

Odor: Slight

Coverage: 250-300 sq.ft. per gallon

**Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,
PLEASE SEE SDS.



Manufactured In The USA By



*Product warranty for one year from date of manufacture

For more information on EZChem USA and all products manufactured by EZChem please visit our website: www.ezchemusa.com



ENVIRO WB SEALER

HOW TO USE:

After Enviro Stain application has been rinsed and thoroughly dry, usually 24 hours, apply Enviro WB Sealer in two thin uniform coats using a roller.

Allow the coating to dry for one hour before applying the second coat.

In heavy traffic areas, a third coat can be applied as above, or apply two coats of EZ-Glo polish as a renewable wear surface. Allow 24 hours drying before walking on floor.

Note: A small test area is recommended. Enviro WB Sealer can be used over other colorants for protection but will not "pop" color on Acid Stained floors.

PRECAUTIONARY STATEMENT:

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash before reuse. Dispose of contents/container according to local, state and federal regulations.

FIRST AID:

EYES: Flush with quantities of water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

IF SWALLOWED: Drink two glasses of water. Get Immediate Medical Help.

SKIN: Wash with soap and water.

IN CASE OF FIRE:

This product is not flammable.

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053