

TECHNICAL DATA SHEET



GFRC SCC

SINGLE COMPONENT COMPLETE GFRC MIX

SCC (SELF-CONSOLIDATING) GFRC MIX

AVAILABLE IN STANDARD OR FAST SET

40 GROSSET DRIVE, SUITE 200, KIRKWOOD, NY 13795
1 (800) 475-1975 • (607) 775-1948 • WWW.TRINIC.US • @TRINICLLC   

DESCRIPTION

Superior strength balanced GFRC complete mix. This is a complete blend of white Portland cement, graded quartzite sand, silica fume, Plasticizer, and Trinic's revolutionary admix blend. The proportions in this mix are designed to provide maximum strength for both compression and flexibility as well as superior consolidation. As with all of our products, the GFRC SCC premix is third-party tested so you know that you're working with the best materials.

BENEFITS OF USE

- Just add water and fiber and start pouring
- High performance minimum of 11,000 psi premix
- No freezing or molding worries
- Strongest premix available
- Custom blends available upon request

DOSAGE RECOMMENDATIONS

- Trinic SCC Premix contains all of the components necessary to make high performance GFRC, just add water
- Add 6 - 7 lbs of water per bucket. You will be casting GFRC with a water to cement ratio of between .24 and .28 with an ultimate strength in excess of 11,000 psi
- Each 50 lb bucket of dry material yields about .40 cubic feet of end product

TEMPERATURE / CURE RATE

- Trinic SCC Premix will cure out and be ready to demold the next day
- Add Stage II Accelerator for quicker cure rates
- Cover with plastic and heating blankets for best results
- Cure with equal air flow underneath to help prevent curling and warpage
- If you get it wet, wet down the whole piece including the bottom to prevent moisture loss or gain on one side, which could cause curling

PACKAGING

45 lb. Bags

50 lb. Bags

2,400 lb. Supersacks Available Upon Request

COVERAGE / YIELD

0.40 cubic feet per 50 lb bucket

SHELF LIFE / STORAGE

Shelf life: 1 year

Storage: store in sealed container, keep away from moisture

DISPOSAL

Follow all federal, state, and local regulations when disposing of this product.

LIMITATIONS

No known limitations if used properly

WARRANTY

Warranty of this product, when used according to the directions, is limited to refund of purchase price, or replacement of product (if defective), at manufacturer / seller's option. Trinic products shall not be liable for cost of labor or direct and/or incidental consequential damages.

SAFETY DATA SHEET

SDS for all Trinic products can be found on our website or by contacting us directly.