



REMOTE-CONTROLLED MODEL



NEW INTELLIGENT REMOTE CONTROL

Precise control over the machine - two sensitive thumbsticks control its position and offset, including integrated mapping on the offset. A wide range of functions. Super light and easy to use with ergonomic rubber grip.

INTUITIVE TOUCHSCREEN PANEL / HMI

Our new HMI provides essential operating information and implements operators' instructions. HMI functionality includes:

- indications of power supply and power consumption,
- · machine load and hours worked,
- tool holder rpm and option to choose rpm setting with tool input,
- · water supply and lights activation,
- · maintenance reminders,
- password activation and shutoff, etc.


See back page for more features.

L25RE









157x73x110 cm

Horsepower	10 HP / 7.5 KW
Voltage (50-60 Hz)	1 or 3 ph x 200-240V
Amperage (max)	45 Amp
Dedicated Breaker Requirement	45 Amp
Generator Recommendation	33KW
Weight of Machine	983 lbs / 446 kg
Grinding Pressure Weights UP	364 lbs / 165 kg
Grinding Pressure Weights DOWN	436 lbs / 198 kg
Attachment Speed	300-1100 rpm
Working Width	25in / 655mm
Tool Holder Diameter	3x9in / 3x225mm
Tool Diameter	3x9in / 3x225mm
Vacuum Hose Port	Camlock E250
Water feeding (with pump)	Peripheral & Front Mist
Water tank capacity	5.2gal / 20L
Cable Length	57 ft / 17.4 m
AMG Battery RC Battery (rechargeable)	12 V/2x7 AH AA 1.2V
Machine Size LxWxH	76x28x47 in 197x71x120 cm
Crate size LxWxH	62x29x43 in

L25RE

- DUST-PROOF GRINDING HEAD WITH LOW-FRICTION CHAIN GEAR PLANETARY DRIVE
- DUST SUPPRESSION FINE MISTING SYSTEM WITH HIGH PRESSURE SPRAY NOZZLES
- ADDED PROTECTION AGAINST EXCESSIVE VOLTAGE
- EASY-TO-USE INTEGRATED WEIGHTS
- IMPROVED DUST COLLECTION EFFICIENCY
- LED LIGHTS IN FRONT & BACK
- NEW ADJUSTABLE HANDLE BAR
- NEW THIRD WHEEL DESIGN
- CHARGING PHONE STATION WITH DUAL USB 2.0 PORTS
- A DURABLE STAINLESS STEEL CUP HOLDER



















