

ELECTRIC MODEL



<image>

Horsepower	20HP / 15KW
Voltage (50/60 Hz)*	3ph x 200-240V
Amperage (max)	60 Amp
Dedicated Breaker Requirement	60 Amp
Generator Recommendation	45KW
Weight of Machine	1455 lbs / 660 kg
Grinding Pressure Weights Pos. 1	540 lbs / 245 kg
Grinding Pressure Weights Pos. 2	652 lbs / 296 kg
Grinding Pressure Weights Pos. 3	750 lbs / 340 kg
Grinding Pressure Weights Pos. 4	870 lbs / 395 kg
Attachment Speed	300-1100 rpm
Working Width	32in / 814mm
Tool Holder Diameter	3x9in / 3x225mm
Vacuum Hose Port	Camlock E300
Water feeding (with pump)	Peripheral & Front Mist
Water tank capacity	12 gal / 46 L
Cable Length	57 ft / 17.4 m
Machine Size LxWxH	100x34x52 in / 254x86x132 cm
Crate size LxWxH	63x37x63 in / 160x95x160 cm

*Also offered in HV - 3ph x 380/480V, 32 Amp



*Also offerred with 13.2" heads - L3213E

- DUST-PROOF GRINDING HEAD WITH LOW-FRICTION CHAIN GEAR PLANETARY DRIVE
- DUST SUPPRESSION FINE MISTING SYSTEM WITH HIGH
 PRESSURE SPRAY NOZZLES
- EASY-TO-USE INTEGRATED WEIGHTS
- IMPROVED DUST COLLECTION EFFICIENCY
- ADDED PROTECTION AGAINST EXCESSIVE VOLTAGE
- LED LIGHTS IN FRONT & BACK
- NEW ADJUSTABLE HANDLE BAR
- CHARGING PHONE STATION WITH DUAL USB 2.0 PORTS
- A DURABLE STAINLESS STEEL CUP HOLDER

The grinding heads are now with counter-clockwise rotation. Use the BLUE pcd's and carbide scrapers.



