



BonTique™ Liquid Antiquing Agent

BonTique™ Liquid Antiquing Agent is a proprietary blend of water soluble cementitious and other coloring agents designed for the use in providing secondary color and/or highlighting to decorative stamped concrete, stampable overlay or any other concrete surface.

PRODUCT FEATURES AND BENEFITS

- Easy to use, mixes with water.
- Can be applied in two easy methods: Pour out and broom in or spray apply with pump up sprayer.
- Contains zero VOC.
- No need to apply secondary coloring to overlays.
- Requires no messy clean up.

PRIOR TO APPLICATION

- Surface to be treated must be clean and free of any curing agents, sealers, dirt, dust, debris or other contaminants that may interfere with the proper adhesion of BonTique™ Liquid Antiquing Agent.
- If BonTique™ Liquid Antiquing Agent is to be applied to a non-textured surface, a minimal surface profiling is required to insure proper bonding to the non-textured surface. A profile equal to the ICRI CSP-1 profile is recommended.

APPLICATION METHODS

- Soft flagged tip broom.
- Pump-up sprayer.

MIXING INSTRUCTIONS

- Pour one gallon of clean potable water into a clean five gallon bucket.
- Mix in 6 ounces of BonTique Liquid Antiquing Agent into the water and mix thoroughly until product is completely dissolved.
- Add mixed product to pump up sprayer, if using spray applied method of application. Shake sprayer regularly to keep product suspended in water throughout application.

PRODUCT APPLICATION Option #1

- Lightly pre-wet the surface to be treated with BonTique™ Liquid Antiquing Agent with water to assist in the distribution of material.
- Apply BonTique™ Liquid Antiquing Agent that has been mixed to entire surface as a color wash, using a flagged tipped broom to massage into or out of the low lying areas as needed or desired.
- Should any brush marks remain after the initial application of BonTique™ Liquid Antiquing Agent, immediately mist the surface with water and lightly broom to eliminate.

PRODUCT APPLICATION Option #2

- Lightly pre-wet the surface to be treated with BonTique™ Liquid Antiquing Agent with water to assist in the distribution of material.
- Apply BonTique™ Liquid Antiquing Agent to entire surface area with pump-up sprayer, highlighting areas as desired.
- Use a soft flagged tip broom to back brush or move applied product into or out of low lying areas as needed.
- Should any brush marks remain after the initial application, immediately mist surface with water and lightly broom to eliminate.

SEALING

- Allow 2-4 hours before sealing. With the use of a soft flag tipped broom, lightly broom area to remove any excess laitance that may be present.
- Use solvent based or water based sealers.

MAINTENANCE

- Proper sealer maintenance is crucial to the ultimate success of any decorative concrete project.
- Ensure that sealer is checked at regular intervals and reapplied as necessary.

PRODUCT LIMITATIONS

- Product should be applied when surface temperature is between 50-90 °F.
- Proper surface profiling is necessary for non-textured concrete surfaces. (See prior to application section)
Note: Colors shown in our printed literature and at www.bontool.com approximate the final color, after a coat of sealer has been applied. Many factors outside of our control affect the final outcome of the project. Please consider mix ratio, hydration, cement, aggregate, cure time and other factors upon review of the final project. It is recommended to perform a test pour.

PACKAGING AND COVERAGE INFORMATION

Packaging: BonTique™ Liquid Antiquing Agent is available in 1-gallon buckets, containing approximately 3 lbs. of powder.
Coverage: Approximately 2,000-3,000 sq. ft. per 3 lb. container.

PRODUCT SHELF LIFE/STORAGE

BonTique™ Liquid Antiquing Agent should be stored indoors, away from heat or direct sunlight. Do not store below 40 °F. If the Liquid freezes, discard.
Shelf life: 24 months from date of manufacture in unopened, original container.

PRODUCT HANDLING

Prior to using BonTique™ Liquid Antiquing Agent please reference the corresponding Safety Data Sheet to ensure safe handling.

WARRANTY

BonTique™ Liquid Antiquing Agent is a proprietary product, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over the product use, no warranty is made as to the effects of such use (neither expressed nor implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product.