Printing date 09/03/2021

Reviewed on 09/03/2021

1 Identification

Product identifier

FORM RETARDER

· Trade name: CSE pro

Article number: CSE.pro (USA)

· Application of the substance / the mixture Surface active agent

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

HEBAU GmbH

An der Eisenschmelze 13 87527 Sonthofen, GERMANY

Tel./Phone: +49 8321 6736-0; Fax: -36

EMERGENCY: CHEMTREC 800-424-9300 CC#8519

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements
- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Naphtha (petroleum), hydrotreated light

Kieselguhr, soda ash flux-calcined

Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

Printing date 09/03/2021 Reviewed on 09/03/2021

Trade name: CSE pro

(Contd. of page 1)

Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local regulations.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

- · Other hazards
- Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:			
EC number: 920-750-0	Naphtha (petroleum), hydrotreated light	>25-≤50%	
CAS: 68855-54-9 EINECS: 272-489-0	Kieselguhr, soda ash flux-calcined	>10-≤25%	
CAS: 77-92-9 EINECS: 201-069-1	citric acid	>10-≤25%	

Additional information: Benzene (CAS 71-43-2) < 0,1%

4 First-aid measures

- Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- *After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed. No further relevant information available.

US

(Contd. on page 3)

Printing date 09/03/2021 Reviewed on 09/03/2021

Trade name: CSE pro

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

None of the ingredients is listed.

PAC-2:

None of the ingredients is listed.

PAC-3:

None of the ingredients is listed.

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

IS -

Printing date 09/03/2021 Reviewed on 09/03/2021

Trade name: CSE pro

(Contd. of page 3)

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters
- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Filter A

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

KCL Camatril ®: 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:

Fluid

Color: Different according to coloring

(Contd. on page 5)

Printing date 09/03/2021 Reviewed on 09/03/2021

Trade name: CSE pro

•	
	(Contd. of pag
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	107 °C (224.6 °F)
Flash point:	< 23 °C (< 73.4 °F)
Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive
	air/vapor mixtures are possible.
Explosion limits:	
Lower:	0.9 Vol %
Upper:	6.8 Vol %
Vapor pressure at 20 °C (68 °F):	35 hPa (26.3 mm Hg)
Density at 20 °C (68 °F):	1 g/cm³ (8.3 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	38.7 %
VOC content:	38.70 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- *Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: No irritant effect.

(Contd. on page 6)

Printing date 09/03/2021 Reviewed on 09/03/2021

Trade name: CSE pro

on the eye: Irritating effect.

(Contd. of page 5)

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

*Uncleaned packagings:

14 Transport information

•Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number	100
DOT, ADR, IMDG, IATA	UN1866
UN proper shipping name	
DOT	Resin solution
ADR	1866 RESIN SOLUTION, ENVIRONMENTALLY

RESIN SOLUTION (Naphtha (petroleum), IMDG hydrotreated light), MARINE POLLUTANT

(Contd. on page 7)

Printing date 09/03/2021

Reviewed on 09/03/2021

Trade name: CSE pro

	(Contd. of page
IATA	RESIN SOLUTION
Transport hazard class(es)	
DOT	
AMMAC COUR	
Class	3 Flammable liquids
Label	3
ADR, IMDG	
Class	3 Flammable liquids
Label	3
IATA	
Class	2 Elammahla liquida
Class Label	3 Flammable liquids 3
Packing group DOT, ADR, IMDG, IATA	II .
Environmental hazards:	Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light
Marine pollutant:	Yes
Cresial marking (ADD):	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special precautions for user Hazard identification number (Kemler code):	Warning: Flammable liquids 33
EMS Number:	F-E, <u>S-E</u>
Stowage Category	В
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
ADR Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 n
IMDG Limited quantities (LQ)	5L
	(Contd. on page

Safety Data Sheet

Printing date 09/03/2021 Reviewed on 09/03/2021

Trade name: CSE pro

Contd. of page 7)

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

UN 1866 RESIN SOLUTION, 3, II,

ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- No further relevant information available.
- Sara

	Section 355 (extremely hazardous substances):	
1	None of the ingredients is listed.	

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

68855-54-9	Kieselguhr, soda ash flux-calcined	ACTIVE
77-92-9	citric acid	ACTIVE

Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Cancerogenity categories
- EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







GHS02 GHS07 GHS08

- Signal word Danger
- Hazard-determining components of labeling: Naphtha (petroleum), hydrotreated light

(Contd. on page 9)

(Contd. of page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/03/2021 Reviewed on 09/03/2021

Trade name: CSE pro

Kieselguhr, soda ash flux-calcined

Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Forschung und Entwicklung
- *Contact: Herr Herrfeld
- Date of preparation / last revision 09/03/2021 / -
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations

Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

* Data compared to the previous version altered.

US