

Product Name: SureSeal Pigmented WB Revision Date 08/01/13

MATERIAL SAFETY DATA SHEET

Complying with 1907/2006/EEC Regulation of 18 December 2006 ("REACH" Regulation) and Regulation (EC) No 1272/2008 (CLP)

SECTION 1 Product and Company Identification

Product

Product Name: SureSeal Pigmented WB Product Description: Finishing aid Intended Use: Acrylic cementitious sealer

Company

Manufacturer:	SureCrete Design Products, Inc.
	15246 Citrus Country Drive
	Dade City, FL 33523
	USA
Contact:	352-567-7973 (telephone general)
	800-424-9300 (telephone emergency – Chemtrec)
	813-469-1408 (telephone 24 hour emergency)
	813-469-1419 (telephone 24 hour emergency)
	info@surecretedesign.com (e-mail)
	352-521-0973 (facsimile)

SECTION 2 Hazards Identification

According to EC Directive 2001/59/EC Most Important Hazards Health Hazards: R36: Irritating to eyes

GHS – Classification

Health Hazards: H320: causes eye irritation

SECTION 3 Composition / Information on Ingredients

This material is regulated as a mixture

Ingredient	CAS #	EC#	% (by weight)	
Hazardous				
Trimethyl Pentanediol	25265-77-4	NE	<5%	
Monoisbutyrate				
Non Hazardous				
Acrylic Copolymer		REACH exempted	<35%	
Calcined caolin clay	1332-58-7	310-194-1	<8%	
Nepheline Syenite	37244-96-5	NE	<5%	

SECTION 4 First Aid Measures

Eye Contact: Rinse with running water for 15 mins. Hold eyelids apart while irrigating.

Skin Contact: Wash affected area thoroughly with soap and water. Wash clothing before reuse.



Product Name: SureSeal Pigmented WB Revision Date 08/01/13



Inhalation: Move to fresh air. Administer artificial respiration if not breathing. If breathing is difficult, give oxygen. Get medical attention

Ingestion: Get medical attention immediately. Do not induce vomiting.

SECTION 5 Fire Fighting Measures

Extinguishing Media:

Appropriate: Foam, CO₂, Dry chemical, water fog **Inappropriate**: Solid streams of water

Fire Fighting Procedures: Cool containers to prevent pressure buildup and possible explosion when exposed to extreme heat. Full protective equipment, including self-contained breathing apparatus required.

Unusual Fire and Explosion Hazard: Closed containers can explode due to buildup of pressure when exposed to extreme heat.

Hazardous Combustion Products: Smoke, fumes, vapors, oxides of carbon

Flammability Properties

Flash Point (Method): >100°C / 212°F Flammable Limits (Approximate volume % in air): LEL: none UEL: none Autoignition Temperature: not determined

SECTION 6 Accidental Release Measures

Personal precautions: Evacuate personnel to safe areas. Ventilate area.

Environmental precautions: Prevent entry into waterways.

Methods for clean-up: Small spills may be cleaned up with paper toweling and disposed into approved container. Larger spills absorb onto sand, vermiculite, or any other inert, non-combustible material. Scoop into containers for later appropriate disposal.

SECTION 7 Handling and Storage

Handling: Avoid contact with eyes, skin, and clothing. Avoid handling of vapor or mist. Do not permit eating, drinking, smoking near material. Remove all potential sources of ignition.

Storage: Keep containers tightly closed, in dry, cool, well ventilated place. Keep out of reach of children.


SECTION 8 Exposure Control / Personal Protection

Exposure limit values: TLV – ACGIH 100 ppm (TWA), 150 ppm (STEL)

OSHA-PEL 150 ppm / 900 mg/m³ (TWA)

Occupational exposure controls: Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.

Respiratory protection: Wear suitable NIOSH approved respirator when ventilation is inadequate





Hand protection: Chemically compatible gloves Eye protection: Safety glasses with side shields Skin protection: Minimize skin contact with appropriate long-sleeved clothing Hygiene measures: Observe good industrial hygienic practices. Frequently launder or discard proactive clothing, equipment.

Environmental exposure controls: Emissions from work process equipment should be checked against requirements of appropriate environmental protection legislation. In some cases alteration to work process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9 Physical and Chemical Properties

General

Physical state: liquid Color: white Odor: characteristic acrylic

Safety Data

pH: not available Boiling point: >100°C / 212°F Flash point: >100°C / 212°F Flammable limits (approximate volume % in air): LEL: none UEL: none Autoignition temperature: >100°C / 212°F Vapor pressure (mm Hg.): 17 mm/Hg @ 20°C / 68°F Water solubility: miscible Vapor density (air = 1): >1 Specific gravity (water = 1): 1.01 – 1.04

SECTION 10 Stability and Reactivity

Stability: Stable under normal conditions

Conditions to avoid: temperature extremes

Materials to avoid: Strong acids and bases

Hazardous decomposition products: material does not decompose at ambient temperatures

Hazardous polymerization: can occur under limited conditions

Acute Toxicity			
Route of Exposure	Conclusion / Remarks		
Inhalation			
Irritation: data available	Elevated temperatures or mechanical action may form vapors, mist, or fumes that may be irritating to the eyes, nose, throat, or lungs based on available literature		
Ingestion			

SECTION 11 Toxicological Information



Toxicity: LD50 > 2000 mg/kg (rat)	Low toxicity
Inhalation	
Irritation	High concentrations may cause central nervous system depression resulting in
	headaches, dizziness, and nausea
Skin	
Irritation: data available	Not irritating to the skin based on available literature
Eye	
Irritation: data available	Moderately irritating to the eyes based on available literature

Chronic / Other Effects

Mutagens / Teratogens / Carcinogens: none known

SECTION 12 Ecological Information

Ecotoxicity: Material expected to have low toxicity to aquatic organisms

Mobility: Material dissolves in water. Under extreme circumstances may contaminate ground water.

Persistence and degradability

Biodegradation: readily biodegradable *Atmospheric oxidation:* expected to degrade rapidly in atmosphere *Bioaccumulation potential:* extremely low potential to bioaccumulate

SECTION 13 Disposal Considerations

Methods of disposal: This material may be safely incinerated or landfilled in accordance with federal, state, and local environmental control regulations.

Section 14 Transport Information

International transport regulations

This product is not regulated for transport.

Regulatory	UN	Proper shipping name	Class	Packing group	Additional	Marine pollutant
Information	number				information	
ADR/RID class					none	
IMDG class					none	
IATA class					none	

National Fire Protection Association Hazard Ratings (NFPA)

Health hazard1Flammability0Stability0



SECTION 15 Regulatory Information

TSCA (USA - Toxic Substance Control Act)

All components of this product are listed on the U.S. Toxic Substances Control Act Inventory (TSCA Inventory) or are exempted from listing because of low volume or polymer exemption has been granted with 40 CFR 723.50

SARA Title III (USA – Superfund Amendments and Reauthorization Act)

311/312 Hazard categories Immediate Health 313 Reportable Ingredients: None

CERCLA (USA – Comprehensive Response Compensation and Liability Act) None

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

There are no chemicals present known to the state of California to cause cancer or reproductive toxicity.

CPR (Canadian Controlled Products Regulations)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Cotrolled Products Regulations. WHMIS Classification : D2B

IDL (Canadian Ingredient Disclosure List)

Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in section 3.

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)

Components of this product identified by CAS number are listed on the DSL or NDSL, or otherwise are in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as hazardous are listed in Section 3 unless otherwise indicated.

EINECS (European Inventory of Existing Commercial Chemical Substances)

Risk phrases: R36: irritating to eye Safety advice: S02: keep out of reach of children S24/25: Avoid contact with skin and eye

Precautionary statementsP280: wear protective gloves, clothing, eye and face protectionP303+P361+P353: if on skin / hair: remove / take off immediately all contaminated clothing; rinse with water

SECTION 16 Other Information

National Paint and Coating Hazardous Materials Identification System - HMIS (R)

Health hazard rating -1Flammability rating -0Instability rating -0 6

Product Name: SureSeal Pigmented WB Revision Date 08/01/13



Personal protection - C (safety glasses, gloves, apron)

Full text of R-phrases referred to in section 2:

R36: irritating to eye

Full text of hazard statements referred to in section 2:

H320: causes eye irritation

Recommended restriction: for use by trained professionals, having read the complete MSDS

Key Legend:

ACGIH – American Conference of Governmental Industrial Hygienists OSHA – Occupational Safety and Health Administration NTP – National Toxicology Program IARC – International Agency for Research on Cancer R – Risk Phrases S – Safety Phrases

Date of printing 05/03/12

According to Regulation (EC) No. 1907/2006 (REACH), Annex II, Commission Directive 2001/59/EC and REGULATION (EC) No. 1272/2008 (CLP)

To the best of our knowledge the information contained here is accurate. However, neither the above named manufacturer nor any of its distributors assumes any liability whatsoever for the accuracy or the completeness of the information contained herein. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.