12w 5 Colour Track Light Installation Instructions

	Product Specifica	Dimensions		
Model No.	HCP-1021201	HCP-1031201	74.8	
Material	Aluminiun	Aluminium + Plastic		
Colour	Black	White		
IP Rating	IP:	IP20		
Track Type	Single	Single Circuit		
Input Voltage	24	240v		
Protection Class	1 (Requir	1 (Requires Earth)		
Lamp Base	Built i	Built in LED		
Lamp Wattage	1x 1	1x 12w		
Colour Temp	5-Colour - 2700k, 3000	5-Colour - 2700k, 3000k, 4000k, 5000k, 5700k		
Lumens	747lm, 778lm, 856	747lm, 778lm, 8561lm, 923lm, 970lm		
CRI	> {	> 90		
Dimmable	Yes - Triac	-Ø62-		
Warranty	5 Years Re	5 Years Replacement*		

*⊾ Ha√i*t

Important Safety Issues:

- This product must be installed by a qualified electrician according to AS/NZS 3000.
- Ensure all electrical mains are disconnected before any installation.
- Modification of this product will void any warranty.
- Havit Commercial does not take responsibility for wrong installation, incorrect use, or use of installation material that does not belong to the system.
- Aluminium and 304SS fittings must not be installed within 5km of any salt water environments.
- All o-rings and seals must be in place correctly to maintain warranty
- This form may be updated at any time due to product improvements, please check online installation form for most current version.

Steps for Installation:

- 1. Make sure that the electrical circuit is free of voltage (master switch off)
- 2. Slide locking pin on base to open position
- 3. Insert track light into track making sure connection points are on correct side of track
- 4. Slide locking pin into closed position
- 5. Fitting is set to 2700k, while fitting is switched off slide switch on back to desired colour twmperature
- 6. Direct light fitting to desired position by twisting left and right or up and down making sure not to twist too far to avoid damaging fitting.
- 7. Repeat these steps if more than 1 fitting is being installed
- 8. All connections must be carried out carefully, inspect all contacts before switching back on the electric circuit.

Steps for Installation of Coloured Inner Ring:

- 1. Make sure that the electrical circuit is free of voltage (master switch off)
- 2. Remove inner ring from fitting by twisting Anticlockwise
- 3. Remove lens by pushing gently on locking tab.
- 4. Insert lens to ne coloured ring and lock into place.
- 5. Insert new coloured inner ring and twist clockwise until it locks into place

Must be installed by a licensed electrician

Contact Details:		Warranty Terms & Conditions*	www.havitcommercial.com.au
8/133 Beauchamp Road Matraville NSW 2036 Australia	Tel: 02 9381 8383 Email: sales@havitcommercial.com.au Web: www.havitcommercial.com.au		