

Indoor Luminaire Photometric Data


Description Information

Luminary Name: HCP-813024-2700K RA90 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Date: 2020/09/27
Manufacture: Havit Commercial	Shld. Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department	Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H): 0.050m*0.000m*0.080m	Lum. Area (m2): 0.016	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25
		Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 815.460	Luminary Flux(lm): 815.457	Field Angle(10%Imax): 77.3(°)
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 806.196lm 98.86%
Rated Voltage(V):	Luminary EER(lm/W): 64.361	Up Lumens&Percent: 9.261lm 1.14%
Tested Power(W): 12.670	Max. Candela(cd): 2336.787	S/MH: C0_a180=0.315 C90_270=0.300
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=0.0	CIE Type: Semi-Direct
Tested Electrics (V, A, pf): 240.2, 0.055, 0.945	Beam Angle(50%Imax): 18.6(°)	ErP Φ use(90°): 741.759lm
Lamp Size (W*L*H): 0.050m*0.000m*0.080m	Left=-9.2°, Right=9.4°	IRF(%): 607.605

C Plane Distribution Diagram




C0 Space ISO Illuminance Curve



2D Plane Light Intensity Distribution Curve


Lum. Name: HCP-813024-2700K RA90 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/09/27

C Plane Distribution Diagram



3D Light Intensity Distribution Modal

Lum. Name: HCP-813024-2700K RA90 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/09/27



Curves: 3D Model — Fixture — Vert. HUD — Hori. HUD —
View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

Zonal Flux Tabulation

Zone (γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone (γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	2.21	2.21	0.27	0.27	47.0-48.0	4.47	763.87	0.55	93.67
1.0-2.0	6.45	8.67	0.79	1.06	48.0-49.0	3.63	767.51	0.45	94.12
2.0-3.0	10.23	18.89	1.25	2.32	49.0-50.0	3.07	770.58	0.38	94.50
3.0-4.0	13.38	32.27	1.64	3.96	50.0-51.0	2.66	773.24	0.33	94.82
4.0-5.0	15.89	48.16	1.95	5.91	51.0-52.0	2.33	775.57	0.29	95.11
5.0-6.0	17.75	65.91	2.18	8.08	52.0-53.0	2.06	777.62	0.25	95.36
6.0-7.0	19.00	84.91	2.33	10.41	53.0-54.0	1.86	779.48	0.23	95.59
7.0-8.0	19.73	104.64	2.42	12.83	54.0-55.0	1.71	781.20	0.21	95.80
8.0-9.0	20.12	124.76	2.47	15.30	55.0-56.0	1.59	782.78	0.19	95.99
9.0-10.0	20.27	145.03	2.49	17.78	56.0-57.0	1.48	784.26	0.18	96.17
10.0-11.0	20.14	165.17	2.47	20.25	57.0-58.0	1.39	785.65	0.17	96.34
11.0-12.0	19.80	184.97	2.43	22.68	58.0-59.0	1.30	786.95	0.16	96.50
12.0-13.0	19.44	204.41	2.38	25.07	59.0-60.0	1.23	788.18	0.15	96.65
13.0-14.0	19.14	223.54	2.35	27.41	60.0-61.0	1.16	789.33	0.14	96.80
14.0-15.0	18.90	242.44	2.32	29.73	61.0-62.0	1.09	790.43	0.13	96.93
15.0-16.0	18.70	261.14	2.29	32.02	62.0-63.0	1.04	791.46	0.13	97.06
16.0-17.0	18.54	279.69	2.27	34.30	63.0-64.0	0.98	792.44	0.12	97.18
17.0-18.0	18.41	298.09	2.26	36.56	64.0-65.0	0.93	793.38	0.11	97.29
18.0-19.0	18.30	316.39	2.24	38.80	65.0-66.0	0.89	794.26	0.11	97.40
19.0-20.0	18.21	334.60	2.23	41.03	66.0-67.0	0.84	795.11	0.10	97.50
20.0-21.0	18.13	352.73	2.22	43.26	67.0-68.0	0.81	795.91	0.10	97.60
21.0-22.0	18.08	370.81	2.22	45.47	68.0-69.0	0.77	796.68	0.09	97.70
22.0-23.0	18.06	388.87	2.21	47.69	69.0-70.0	0.74	797.42	0.09	97.79
23.0-24.0	18.06	406.93	2.21	49.90	70.0-71.0	0.71	798.12	0.09	97.87
24.0-25.0	18.07	425.00	2.22	52.12	71.0-72.0	0.67	798.80	0.08	97.96
25.0-26.0	18.11	443.11	2.22	54.34	72.0-73.0	0.64	799.44	0.08	98.04
26.0-27.0	18.18	461.28	2.23	56.57	73.0-74.0	0.62	800.06	0.08	98.11
27.0-28.0	18.26	479.55	2.24	58.81	74.0-75.0	0.59	800.65	0.07	98.18
28.0-29.0	18.36	497.90	2.25	61.06	75.0-76.0	0.56	801.20	0.07	98.25
29.0-30.0	18.47	516.37	2.26	63.32	76.0-77.0	0.53	801.74	0.07	98.32
30.0-31.0	18.57	534.94	2.28	65.60	77.0-78.0	0.50	802.24	0.06	98.38
31.0-32.0	18.65	553.58	2.29	67.89	78.0-79.0	0.48	802.72	0.06	98.44
32.0-33.0	18.69	572.28	2.29	70.18	79.0-80.0	0.45	803.17	0.06	98.49
33.0-34.0	18.66	590.94	2.29	72.47	80.0-81.0	0.42	803.59	0.05	98.54
34.0-35.0	18.47	609.41	2.26	74.73	81.0-82.0	0.40	803.99	0.05	98.59
35.0-36.0	18.09	627.49	2.22	76.95	82.0-83.0	0.37	804.37	0.05	98.64
36.0-37.0	17.51	645.00	2.15	79.10	83.0-84.0	0.35	804.71	0.04	98.68
37.0-38.0	16.71	661.72	2.05	81.15	84.0-85.0	0.32	805.04	0.04	98.72
38.0-39.0	15.75	677.47	1.93	83.08	85.0-86.0	0.30	805.33	0.04	98.76
39.0-40.0	14.67	692.14	1.80	84.88	86.0-87.0	0.27	805.60	0.03	98.79
40.0-41.0	13.50	705.64	1.66	86.53	87.0-88.0	0.23	805.83	0.03	98.82
41.0-42.0	12.30	717.94	1.51	88.04	88.0-89.0	0.20	806.03	0.02	98.84
42.0-43.0	11.03	728.97	1.35	89.39	89.0-90.0	0.17	806.20	0.02	98.86
43.0-44.0	9.68	738.65	1.19	90.58	90.0-91.0	0.15	806.35	0.02	98.88
44.0-45.0	8.27	746.92	1.01	91.59	91.0-92.0	0.14	806.49	0.02	98.90
45.0-46.0	6.89	753.80	0.84	92.44	92.0-93.0	0.13	806.62	0.02	98.92
46.0-47.0	5.60	759.40	0.69	93.13	93.0-94.0	0.12	806.74	0.01	98.93


Zonal Flux Tabulation - (Cont.)

Zone (γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone (γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.11	806.85	0.01	98.94	141.0-142.0	0.16	810.90	0.02	99.44
95.0-96.0	0.11	806.96	0.01	98.96	142.0-143.0	0.16	811.06	0.02	99.46
96.0-97.0	0.10	807.06	0.01	98.97	143.0-144.0	0.16	811.22	0.02	99.48
97.0-98.0	0.09	807.15	0.01	98.98	144.0-145.0	0.17	811.39	0.02	99.50
98.0-99.0	0.09	807.24	0.01	98.99	145.0-146.0	0.17	811.56	0.02	99.52
99.0-100.0	0.08	807.32	0.01	99.00	146.0-147.0	0.17	811.73	0.02	99.54
100.0-101.0	0.08	807.39	0.01	99.01	147.0-148.0	0.17	811.91	0.02	99.56
101.0-102.0	0.07	807.47	0.01	99.02	148.0-149.0	0.17	812.08	0.02	99.59
102.0-103.0	0.07	807.53	0.01	99.03	149.0-150.0	0.17	812.25	0.02	99.61
103.0-104.0	0.07	807.60	0.01	99.04	150.0-151.0	0.17	812.43	0.02	99.63
104.0-105.0	0.06	807.66	0.01	99.04	151.0-152.0	0.17	812.60	0.02	99.65
105.0-106.0	0.06	807.72	0.01	99.05	152.0-153.0	0.17	812.77	0.02	99.67
106.0-107.0	0.06	807.78	0.01	99.06	153.0-154.0	0.17	812.94	0.02	99.69
107.0-108.0	0.06	807.84	0.01	99.07	154.0-155.0	0.16	813.10	0.02	99.71
108.0-109.0	0.06	807.89	0.01	99.07	155.0-156.0	0.16	813.26	0.02	99.73
109.0-110.0	0.06	807.95	0.01	99.08	156.0-157.0	0.16	813.42	0.02	99.75
110.0-111.0	0.06	808.01	0.01	99.09	157.0-158.0	0.15	813.58	0.02	99.77
111.0-112.0	0.06	808.06	0.01	99.09	158.0-159.0	0.15	813.73	0.02	99.79
112.0-113.0	0.06	808.12	0.01	99.10	159.0-160.0	0.15	813.87	0.02	99.81
113.0-114.0	0.06	808.18	0.01	99.11	160.0-161.0	0.14	814.01	0.02	99.82
114.0-115.0	0.06	808.23	0.01	99.11	161.0-162.0	0.14	814.15	0.02	99.84
115.0-116.0	0.06	808.29	0.01	99.12	162.0-163.0	0.13	814.28	0.02	99.86
116.0-117.0	0.06	808.35	0.01	99.13	163.0-164.0	0.13	814.41	0.02	99.87
117.0-118.0	0.06	808.41	0.01	99.14	164.0-165.0	0.12	814.53	0.01	99.89
118.0-119.0	0.06	808.48	0.01	99.14	165.0-166.0	0.11	814.64	0.01	99.90
119.0-120.0	0.06	808.54	0.01	99.15	166.0-167.0	0.11	814.75	0.01	99.91
120.0-121.0	0.07	808.61	0.01	99.16	167.0-168.0	0.10	814.85	0.01	99.93
121.0-122.0	0.07	808.68	0.01	99.17	168.0-169.0	0.09	814.95	0.01	99.94
122.0-123.0	0.07	808.75	0.01	99.18	169.0-170.0	0.09	815.03	0.01	99.95
123.0-124.0	0.08	808.83	0.01	99.19	170.0-171.0	0.08	815.11	0.01	99.96
124.0-125.0	0.08	808.90	0.01	99.20	171.0-172.0	0.07	815.18	0.01	99.97
125.0-126.0	0.08	808.99	0.01	99.21	172.0-173.0	0.06	815.25	0.01	99.97
126.0-127.0	0.09	809.07	0.01	99.22	173.0-174.0	0.06	815.30	0.01	99.98
127.0-128.0	0.09	809.16	0.01	99.23	174.0-175.0	0.05	815.35	0.01	99.99
128.0-129.0	0.09	809.25	0.01	99.24	175.0-176.0	0.04	815.39	0.00	99.99
129.0-130.0	0.10	809.35	0.01	99.25	176.0-177.0	0.03	815.42	0.00	99.99
130.0-131.0	0.10	809.45	0.01	99.26	177.0-178.0	0.02	815.44	0.00	100.00
131.0-132.0	0.11	809.56	0.01	99.28	178.0-179.0	0.01	815.45	0.00	100.00
132.0-133.0	0.11	809.67	0.01	99.29	179.0-180.0	0.00	815.46	0.00	100.00
133.0-134.0	0.12	809.79	0.01	99.30					
134.0-135.0	0.12	809.91	0.01	99.32					
135.0-136.0	0.13	810.03	0.02	99.33					
136.0-137.0	0.13	810.16	0.02	99.35					
137.0-138.0	0.14	810.30	0.02	99.37					
138.0-139.0	0.14	810.44	0.02	99.38					
139.0-140.0	0.15	810.59	0.02	99.40					
140.0-141.0	0.15	810.74	0.02	99.42					

Rectangle ISO Lighting Intensity Diagram

Lum. Name: HCP-813024-2700K RA90 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/09/27

ISO Lighting Intensity Curve




Maximum Light Intensity(cd): 2336.79

Maximum Cand.@Angle: H=0.0°,V=0.0°

Plane ISO-Illuminance Diagram

Lum. Name: HCP-813024-2700K RA90 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/09/27


Plane ISO-Illuminance Curve



3D Plane ISO Illuminance Diagram

Lum. Name: HCP-813024-2700K RA90 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/09/27

3D Plane Illuminance Model




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

Space ISO Illuminance Diagram

Lum. Name: HCP-813024-2700K RA90 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/09/27

Space ISO Illuminance Curve



Curves:

[Unit: lx]

[E_{Max}] = 2336.787

— [E_{Max}*90%]=2103.108

— [E_{Max}*80%]=1869.430

— [E_{Max}*70%]=1635.751

— [E_{Max}*60%]=1402.072

— [E_{Max}*50%]=1168.394

— [E_{Max}*40%]=934.715

— [E_{Max}*30%]=701.036

— [E_{Max}*20%]=467.357

— [E_{Max}*10%]=233.679


Space Plane Maximum Illuminance and @Angle:2336.79lx,0.0deg

Plane Maximum Lighting Intensity and @Angle:2336.787cd,0deg

Illuminance-Distance Diagram

Lum. Name: HCP-813024-2700K RA90 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/09/27

Illuminance-Distance Curve



Indoor Luminance Limiting Curves

Lum. Name: HCP-813024-2700K RA90 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/09/27


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama (deg)	45	50	55	60	65	70	75	80	85
C0	9111	3658	2232	1787	1550	1451	1465	1625	2312
C90	7880	2940	1902	1544	1328	1223	1186	1266	1652

Luminance Limiting Curve




Luminous Size: Length(m)=0.000 Width(m)=-0.050 Height(m)=0.080 Area(m^2)=0.015708

Luminous Type: Without Luminous Side

Luminous Curves: C0-C180 Color: — C90-C270 Color: —

Indoor Budgetary Estimate Table

Lum. Name: HCP-813024-2700K RA90 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/09/27



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

Indoor Coefficient of Utilization Table

Lum. Name: HCP-813024-2700K RA90 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/09/27

Coefficients of Utilization – Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization (%)																	
0	119	119	119	119	116	116	116	116	110	110	110	106	106	106	101	101	101	99
1	113	110	107	105	110	108	105	103	103	102	100	100	98	97	96	95	94	92
2	107	102	98	94	105	100	96	93	97	94	91	94	91	89	91	89	87	85
3	102	95	90	86	99	93	89	85	91	87	83	88	85	82	86	83	81	79
4	96	89	83	79	94	87	82	78	85	81	77	83	79	76	81	78	75	73
5	91	83	77	73	90	82	76	72	80	75	71	78	74	71	77	73	70	68
6	87	78	72	68	85	77	71	67	75	70	67	74	69	66	72	69	66	64
7	83	73	67	63	81	73	67	63	71	66	62	70	65	62	69	65	62	60
8	79	69	63	59	78	69	63	59	68	62	59	66	62	58	65	61	58	57
9	75	66	60	56	74	65	60	56	64	59	55	63	59	55	62	58	55	54
10	72	62	57	53	71	62	56	53	61	56	53	60	56	52	59	55	52	51

Unified Glare Rating Table

Lum. Name: HCP-813024-2700K RA90 15D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Havit Commercial	Test Machine: GON-2000	Test Date: 2020/09/27

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H Y=2H	16.0	17.1	16.4	17.4	17.8	15.5	16.6	15.9	16.9	17.3
	16.0	16.9	16.4	17.3	17.7	15.5	16.4	15.9	16.8	17.1
	16.0	16.9	16.4	17.3	17.7	15.4	16.3	15.9	16.7	17.1
	16.0	16.8	16.5	17.2	17.6	15.4	16.2	15.9	16.6	17.0
	16.0	16.8	16.5	17.2	17.6	15.4	16.2	15.9	16.6	17.0
	16.1	16.8	16.5	17.2	17.6	15.4	16.1	15.9	16.5	17.0
X=4H Y=2H	15.8	16.7	16.3	17.1	17.5	15.3	16.2	15.7	16.6	17.0
	15.9	16.6	16.3	17.0	17.4	15.3	16.0	15.7	16.4	16.9
	15.9	16.5	16.3	17.0	17.4	15.3	15.9	15.8	16.4	16.9
	16.0	16.5	16.5	17.0	17.5	15.4	15.9	15.8	16.4	16.9
	16.0	16.5	16.5	17.0	17.5	15.4	15.9	15.9	16.4	16.9
	16.1	16.5	16.6	17.1	17.6	15.4	15.9	15.9	16.4	16.9
X=8H Y=4H	15.8	16.3	16.3	16.8	17.3	15.2	15.7	15.7	16.2	16.7
	15.9	16.4	16.5	16.9	17.4	15.3	15.7	15.8	16.3	16.8
	16.0	16.4	16.6	17.0	17.5	15.4	15.8	15.9	16.3	16.8
	16.2	16.5	16.8	17.1	17.7	15.5	15.8	16.0	16.3	16.9
X=12H Y=4H	15.8	16.2	16.3	16.7	17.2	15.2	15.6	15.7	16.1	16.6
	15.9	16.3	16.5	16.8	17.4	15.3	15.7	15.8	16.2	16.7
	16.1	16.4	16.6	16.9	17.5	15.4	15.7	15.9	16.2	16.8
Variations with the observer position at spacings										
S=1.0H	0.2/−0.2					0.3/−0.3				
S=1.5H	0.4/−0.4					0.5/−0.5				
S=2.0H	0.5/−0.6					0.7/−0.7				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	0.7					0.6				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	2336.79	2336.79	2336.79	2336.79
γ 1.0	2334.97	2239.31	2317.86	2277.52
γ 2.0	2250.04	2133.34	2223.89	2204.22
γ 3.0	2116.75	1997.68	2089.86	2085.29
γ 4.0	1968.16	1847.27	1941.87	1942.08
γ 5.0	1805.71	1692.46	1786.87	1789.13
γ 6.0	1640.18	1533.32	1628.60	1636.53
γ 7.0	1485.48	1372.58	1471.34	1474.61
γ 8.0	1343.11	1228.65	1327.60	1322.28
γ 9.0	1213.56	1106.37	1197.17	1193.69
γ 10.0	1088.96	998.69	1078.06	1081.11
γ 11.0	975.85	895.94	966.90	976.46
γ 12.0	879.16	807.13	869.80	875.49
γ 13.0	799.96	735.79	790.22	793.42
γ 14.0	732.30	677.91	722.37	728.37
γ 15.0	676.80	628.24	666.93	672.88
γ 16.0	628.44	585.78	621.46	625.16
γ 17.0	587.22	549.47	580.83	584.74
γ 18.0	551.99	518.38	544.27	548.69
γ 19.0	521.63	490.35	513.69	517.84
γ 20.0	494.20	464.79	486.94	489.23
γ 21.0	470.41	443.20	463.03	464.88
γ 22.0	449.24	423.76	441.37	443.03
γ 23.0	430.68	406.85	423.67	424.15
γ 24.0	414.01	391.36	406.59	406.49
γ 25.0	399.64	377.90	391.94	391.00
γ 26.0	386.56	366.00	378.68	377.05
γ 27.0	375.61	355.77	367.30	365.15
γ 28.0	364.90	345.66	356.12	354.79
γ 29.0	355.75	337.04	346.65	345.79
γ 30.0	347.01	328.58	337.29	337.52
γ 31.0	339.23	320.57	328.37	329.97
γ 32.0	330.88	311.93	320.00	322.45
γ 33.0	323.45	302.99	312.08	314.41
γ 34.0	314.05	292.08	302.63	305.22
γ 35.0	302.53	278.26	290.63	293.20
γ 36.0	288.83	262.38	277.31	279.05
γ 37.0	271.80	245.08	260.74	262.42
γ 38.0	252.10	225.68	241.10	243.98
γ 39.0	231.52	206.30	221.44	224.01
γ 40.0	209.32	186.21	199.29	203.98
γ 41.0	187.79	166.51	178.32	184.85
γ 42.0	166.57	147.06	157.71	165.70
γ 43.0	144.51	126.86	135.84	146.74
γ 44.0	122.64	107.35	114.75	126.96
γ 45.0	101.20	87.53	93.62	107.02
γ 46.0	81.94	70.15	75.42	87.43

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	64.88	53.92	58.90	70.08
γ 48.0	51.58	42.35	46.15	54.73
γ 49.0	43.05	34.59	37.96	43.64
γ 50.0	36.93	29.68	32.04	36.45
γ 51.0	32.07	25.87	27.35	31.37
γ 52.0	27.61	22.66	23.38	26.88
γ 53.0	24.19	20.35	20.48	23.58
γ 54.0	21.95	18.54	18.41	21.16
γ 55.0	20.11	17.14	16.84	19.26
γ 56.0	18.48	15.96	15.12	17.59
γ 57.0	17.23	14.93	13.90	16.18
γ 58.0	16.08	13.97	12.90	14.74
γ 59.0	15.04	13.01	12.02	13.66
γ 60.0	14.03	12.13	11.17	12.71
γ 61.0	13.17	11.37	10.46	11.88
γ 62.0	12.34	10.65	9.79	11.17
γ 63.0	11.61	9.97	9.20	10.49
γ 64.0	10.90	9.38	8.62	9.85
γ 65.0	10.29	8.81	8.15	9.30
γ 66.0	9.72	8.29	7.69	8.80
γ 67.0	9.19	7.80	7.30	8.36
γ 68.0	8.70	7.35	6.95	7.97
γ 69.0	8.24	6.97	6.64	7.59
γ 70.0	7.79	6.57	6.35	7.26
γ 71.0	7.39	6.20	6.09	6.95
γ 72.0	6.99	5.82	5.80	6.65
γ 73.0	6.65	5.46	5.53	6.37
γ 74.0	6.28	5.14	5.27	6.09
γ 75.0	5.96	4.82	5.02	5.83
γ 76.0	5.63	4.53	4.77	5.57
γ 77.0	5.32	4.24	4.52	5.31
γ 78.0	5.01	3.96	4.27	5.04
γ 79.0	4.71	3.70	4.02	4.78
γ 80.0	4.43	3.45	3.78	4.53
γ 81.0	4.17	3.22	3.54	4.28
γ 82.0	3.93	2.99	3.30	4.03
γ 83.0	3.70	2.76	3.08	3.78
γ 84.0	3.44	2.51	2.85	3.55
γ 85.0	3.16	2.26	2.62	3.34
γ 86.0	2.83	1.99	2.37	3.10
γ 87.0	2.50	1.70	2.11	2.82
γ 88.0	2.19	1.38	1.82	2.55
γ 89.0	1.82	1.12	1.44	2.04
γ 90.0	1.65	0.98	1.25	1.77
γ 91.0	1.56	0.90	1.17	1.65
γ 92.0	1.47	0.84	1.08	1.55
γ 93.0	1.39	0.78	1.00	1.46

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	1.31	0.71	0.92	1.37
γ 95.0	1.24	0.65	0.86	1.28
γ 96.0	1.16	0.61	0.78	1.20
γ 97.0	1.10	0.55	0.73	1.12
γ 98.0	1.04	0.51	0.68	1.05
γ 99.0	0.99	0.47	0.63	0.99
γ 100.0	0.93	0.44	0.59	0.94
γ 101.0	0.89	0.42	0.55	0.88
γ 102.0	0.85	0.38	0.53	0.85
γ 103.0	0.81	0.37	0.51	0.81
γ 104.0	0.79	0.35	0.47	0.78
γ 105.0	0.76	0.34	0.47	0.76
γ 106.0	0.73	0.33	0.46	0.73
γ 107.0	0.71	0.33	0.45	0.71
γ 108.0	0.70	0.33	0.46	0.70
γ 109.0	0.69	0.33	0.46	0.70
γ 110.0	0.68	0.33	0.47	0.69
γ 111.0	0.68	0.33	0.48	0.69
γ 112.0	0.67	0.34	0.50	0.70
γ 113.0	0.67	0.35	0.52	0.70
γ 114.0	0.67	0.36	0.54	0.72
γ 115.0	0.67	0.37	0.57	0.73
γ 116.0	0.68	0.39	0.59	0.75
γ 117.0	0.69	0.40	0.63	0.77
γ 118.0	0.70	0.42	0.66	0.79
γ 119.0	0.71	0.44	0.69	0.81
γ 120.0	0.73	0.47	0.74	0.84
γ 121.0	0.75	0.51	0.78	0.87
γ 122.0	0.78	0.53	0.82	0.91
γ 123.0	0.81	0.59	0.88	0.94
γ 124.0	0.86	0.62	0.93	0.98
γ 125.0	0.90	0.67	0.98	1.02
γ 126.0	0.95	0.73	1.03	1.07
γ 127.0	0.99	0.79	1.10	1.11
γ 128.0	1.05	0.85	1.16	1.16
γ 129.0	1.11	0.92	1.22	1.23
γ 130.0	1.17	0.99	1.30	1.28
γ 131.0	1.24	1.07	1.38	1.34
γ 132.0	1.31	1.15	1.45	1.41
γ 133.0	1.38	1.23	1.55	1.48
γ 134.0	1.47	1.31	1.63	1.56
γ 135.0	1.55	1.40	1.74	1.65
γ 136.0	1.65	1.51	1.83	1.75
γ 137.0	1.75	1.62	1.96	1.85
γ 138.0	1.85	1.71	2.06	1.96
γ 139.0	1.96	1.83	2.18	2.06
γ 140.0	2.07	1.94	2.30	2.17

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	2.17	2.07	2.42	2.29
γ 142.0	2.28	2.18	2.53	2.39
γ 143.0	2.40	2.29	2.65	2.51
γ 144.0	2.51	2.40	2.77	2.62
γ 145.0	2.62	2.51	2.88	2.73
γ 146.0	2.73	2.62	2.99	2.84
γ 147.0	2.83	2.73	3.09	2.93
γ 148.0	2.93	2.83	3.19	3.02
γ 149.0	3.03	2.92	3.28	3.11
γ 150.0	3.12	2.99	3.34	3.19
γ 151.0	3.20	3.10	3.44	3.24
γ 152.0	3.29	3.16	3.50	3.32
γ 153.0	3.37	3.24	3.58	3.38
γ 154.0	3.44	3.31	3.64	3.45
γ 155.0	3.51	3.38	3.72	3.50
γ 156.0	3.58	3.43	3.79	3.56
γ 157.0	3.65	3.49	3.86	3.61
γ 158.0	3.72	3.56	3.92	3.68
γ 159.0	3.78	3.63	3.99	3.73
γ 160.0	3.86	3.68	4.05	3.78
γ 161.0	3.92	3.75	4.12	3.83
γ 162.0	3.99	3.81	4.17	3.89
γ 163.0	4.05	3.88	4.23	3.93
γ 164.0	4.11	3.94	4.29	3.97
γ 165.0	4.16	4.01	4.34	4.01
γ 166.0	4.22	4.06	4.39	4.07
γ 167.0	4.26	4.12	4.42	4.11
γ 168.0	4.32	4.18	4.47	4.14
γ 169.0	4.36	4.24	4.51	4.18
γ 170.0	4.40	4.27	4.55	4.23
γ 171.0	4.43	4.31	4.58	4.26
γ 172.0	4.45	4.34	4.60	4.29
γ 173.0	4.48	4.37	4.62	4.31
γ 174.0	4.49	4.38	4.64	4.34
γ 175.0	4.52	4.38	4.64	4.35
γ 176.0	4.53	4.41	4.64	4.36
γ 177.0	4.52	4.41	4.65	4.37
γ 178.0	4.53	4.43	4.65	4.38
γ 179.0	4.55	4.42	4.64	4.40
γ 180.0	4.53	4.53	4.53	4.53