## Adhesive Backed 3 mil Matte White Vinyl Permanent Gray Adhesive & 88# Liner for Solvent, Latex & UV Printers

- Can be used for interior and exterior signage.
- Uses include outdoor signage, promotional and point of purchase graphics, trade show displays.
- Compatible with OEM Solvent, Latex & UV Curable Inks

## Construction

Product Number:	D30MPWxx78G
Adhesive:	Permanent Gray Acrylic
Film:	3 mil Vinyl
Liner:	88# Lay Flat Liner, Poly Coated 2 Sides
Finish:	Matte White
Gloss Level:	>10 (avg.) @ 60°

## **Typical Performance Values**

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability:	Outdoor - 5 years Unprinted
Minimum Application Temperature:	+40° F (Minimum for Substrate)
Service Temperature Range:	-40° F to +180° F
Temperature Resisitance:	-65° F to + 225° F
Chemical Resistance:	Resistant to alkalies, mild acids, most petroleum based oil, grease and aliphatic solvents and salts.
Typical Adhesion Values:	180° Peel Test <u>Substrate</u> Stainless Steel  3 lb/in
Shelf Life:	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity

Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. The purchaser must assume all risks for any use, operation and application of the material. All information given serves only to describe the product and is not to be regarded as assured properties in the legal sense. Specifications subject to change without notice, errors and omissions excepted. The material is sold without warranty and purchaser should refer to Southern Sign Supply Terms and Conditions.

