





- SAE 578 Color Temperature Certified
- Preconfigured spot, flood, or scene optics
- Available with White illumination
- Warning lights require remote flasher, purchased separately
- Individual control of each set of optics
- Increase clarity with Whelen's all-new, patent pending Proclera™ Silicone Optics
- Hard-coated lenses minimize environmental damage from sand, sun, salt, and road chemicals
- Extruded and die-cast aluminum powder coated housing available in gray
- Screwless lens retainer design provides a clean finish and the improved ability to adjust optic configuration
- 100% solid-state electronics
- Rated IP67 for dust and water resistance
- Rear mounting track for flexible mounting configurations
- Bail bracket mount standard
- Includes 30" cable, connector, and heat shrink tubing. Some assembly required
- Dual voltage (10-30 VDC input)
- Five year warranty

FORWARD LIGHT ARRAY

Designed to deliver maximum light intensity, the low-profile Apex Series is available in multiple spot, flood, and scene optic combinations. Increase clarity with Whelen's all-new, patent pending Proclera™ Silicone Optics. The Apex Series features optional integrated warning and clearance lights for optimal illumination and visibility.

Notes:

- Module count is per 3 LEDs (each silicone optic)
- Overall size does not include mounting hardware or cable entry
 - Side bail brackets add 2" to width
 - Depth to cable entry is 3.22"
- Current draw is calculated at 12.8VDC

MODEL	DEL PART# DESCRIPTION		
FLAPX30	01-0690889-00	APEX 30"	
FLAPX44	01-0690889-01	APEX 44"	
SIZE (Modules)	DIMENSIONS (Inches)	CURRENT DRAW (Amps)	

	SIZE (Modules)	DIN	DIMENSIONS (Inches)		CURRENT DRAW (Amps)
		W	Н	D	(Allips)
	8	30	2/0	2.15	7.2
	12	44	2.48		10.8
		_			



WARNING: These products may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit flywat.com/regulatory.



WWW.FLYWAT.COM/GSE

1-772-267-6615