





The compact and economic Control
Switch is engineered for complete control
of numerous auxiliary light functions.
Designed for simplistic usage, all models are
equipped with LED indicators and include
press-on labels for customization.

SPECS

- Complete control of four, or six, auxiliary light functions
- 25 amp switches
- Rocker-style single pole/single throw switches with 'active' LED indicators
- Individual spade-type fuses conveniently located on rear mounted fuse strip
- Ignition controlled backlighted legend windows for easy visibility in any light
- Backlight circuit can be connected to vehicle dimmer switch to control backlight intensity
- 72 press-on legend tabs for customization
- Gray epoxy-finished steel housing
- Common ground post for ease of installing
- 12 VDC
- Two year warranty

MODEL	PART#	DESCRIPTION
FLSWI4	01-0690891-000	Control Switch 4 25amp
FLSWI6	01-0690892-000	Control Switch 6 25amp



WARNING: These products may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit flywat.com/regulatory.

FLSW14

- Flying leads connection
- Includes an adjustable two position universal bail bracket strap mounting kit for over or under dash mounting
- Dimensions: 2-3/4" (70mm) H x 3" (76mm) W x 4" (102mm) D
- Adjustable bail bracket overall heights: 2-3/4"
 (70mm) H (lower bracket position), 3-1/4" (83mm)
 H (higher bracket position)

FLSW16

- Terminal block for easy installation
- One 10 amp momentary switch in the last position in place of the standard On/Off switch
- Includes an adjustable two position universal bail bracket strap mounting kit for over or under dash mounting
- Dimensions: 3-3/8" (86mm) H x 6" (152mm) W x 3-9/16" (91mm) D
- Adjustable bracket overall heights: 3-3/8" (86mm)
 H (lower bracket position), 3-3/4" (96mm) H (higher bracket position)



WWW.FLYWAT.COM/GSE

1-772-267-6615