POLYMER MACHINE The economically priced stamp making machine



CONTROL PANEL

The control panel is clearly defined and user-friendly. The menu is easy to navigate, which speeds up adjusting exposure times.



DOUBLE-SIDED EXPOSURE UNIT

This double-sided exposure unit with 6 lamps on the top and the bottom enables efficient and clean works.



INTEGRATED SPACERS

The spacers, integrated into the lower glass panel, match the text plate thickness.



WASH OUT UNIT

The rotating wash out unit has a soft brushes ensure gentle washing.



BLOW PIPE

Used to eliminate the air bubbles that are formed when pouring in the resin.



POST-EXPOSURE

The plates achieve their optimum final thickness in the post-exposure.



SELF-ADHESIVE RUBBER

Pad which makes sticking the exposed polymer plate easy.

PRODUCT DESCRIPTION

Model	Exposure Area	Machine Size	No. of UV Lamp	Power Supply
PM-A3	320x470mm	690x845x760mm	Up: 6 pcs Down: 6 pcs	220V/50 Hz
PM-A4N	200x270mm	450x532x830mm	Up: 6 pcs Down: 6 pcs	220V/50Hz
PM-A4 Exp	200x270mm	450x550x450mm	Up: 6 pcs Down: 6 pcs	220V/50Hz







PM-A4N

PM-EXA4



