



SECTION A-A

NOTES:

1. MATERIALS:
 1-BODY: PC MAKROLON RX 1805-451118
 2-HANDLE: HDPE MARLEX 9006 WHITE
 3-LOCKING RING: PC MAKROLON RX 1805
2. VENDOR SHALL CERTIFY FOR EACH SHIPMENT THAT EACH SHIPMENT IS TRACEABLE TO VENDOR'S LOTS AND VENDOR'S SUPPLIER(S) LOTS.
3. MATERIAL COMPATIBLE WITH ETO AND GAMMA STERILIZATION.
4. FLASH:
 INTERNAL FLASH: NOT TO EXCEED .006 IN. NO BRITTLE OR LOOSE FLASH ALLOWED.
 EXTERNAL FLASH: NOT TO EXCEED .012 IN. NO BRITTLE OR LOOSE FLASH ALLOWED.
5. ALL DIMENSIONS ARE FOR REFERENCE UNLESS OTHERWISE SPECIFIED.
 *INDICATES INSPECTION DIMENSIONS
6. PRE-STERILIZATION PRESSURE RATING: 25 PSI.
7. LUERS/LUER LOCKS PER ISO 594
8. BULK PACKAGE USING DOUBLE POLY BAGS.

REVISION HISTORY					
REV.	DESCRIPTION:	DRWN:	DATE:	CHKD/APVD:	DATE:
C	BODY MATERIAL CHANGE PER ECO 1858	RR	8-15-16	RM	8-15-16
B	LOCKING RING MATERIAL CHANGE PER ECO 1750	RR	9-4-15	RR	9-4-15
A	INITIAL RELEASE	RP	1-6-2006	RM	1-6-2006

DRAWING SPECIFICATIONS:
 UNLESS OTHERWISE NOTED
 • DIMENSIONS ARE IN MILLIMETERS
 • BREAK ALL SHARP EDGES
 • CORNER RADIUS = N/A
 • SURFACE FINISH = A3
 • TOLERANCES:
 ANGLES = ± .5°
 X.X = ± 0.1
 X.XX = ± 0.05
 X.XXX = ± 0.02

THIS DRAWING IS PROPRIETARY TO VITALMED, INC. REPRODUCTION OR USE WITHOUT WRITTEN AUTHORIZATION IS PROHIBITED.

VITALMED, INC.®

VITALMED, INCORPORATED
 LAKEVILLE, MASSACHUSETTS 02347

DESCRIPTION: STOPCOCK 1 WAY, HI FLOW W/ FEMALE LUER & MALE LUER WITH LOCKING RING

MATERIAL:	SEE NOTES	SCALE:	N/A	DRWG NO:	21352	REV:	C
FINISH:	N/A	SHEET:	1 OF 1				
DRWN:	RR	DATE:	8/15/16	CHKD:	SP	DATE:	8/15/16
		APVD:	RM	DATE:	8/15/16		