




SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



DESCRIPTION

Small aperture 12V Downlight delivers over 600 lumens of lighting output. More than a traditional 50W MR16 Halogen Lamp. Dimmable MLV or ELV depending on the transformer used.

Need help with your LED lighting projects? Our lighting experts are here to help! Contact us today for assistance with lighting plan or installation instructions.

KEY FEATURES

- IC Airtight for use with direct contact to insulation
- The height allows for use in 2 x 4 construction
- 38° Standard beam with optional 28° and 60°
- Remodel requires no frame
- Wet Location Rated for Indoor and Outdoor Use
- JA8-1016-E, UL, and Energy Star Listed
- Life Span 50,000 Hours L70

SPECIFICATIONS

- Brightness:** 625 Lumen - 3000K
675 Lumen - 4000K
- Power (Watts):** 6 Watt
- Voltage:** 12V AC
- LED CCT:** 3000K or 4000K
- CRI:** 93+
- Dimmable:** Yes, MLV/ELV
- Environment:** Wet Location
- Cut-out:** 2 in diameter
- Dimensions:** 2.25 in L x 2.25 in W x 2.875 in H
- Finish:** White, Haze w/ White, Black w/White, Black, or Bronze options
- Manufacturer:** Elumalight
- Rating:** JA8-1016-E, UL, and Energy Star Listed
- Avg. Lifetime:** ± 30,000 - 50,000 hours
- Required:** The LED downlight requires 12V AC Transformer (daisy chain up to 6 lights). Sold separately.

APPLICATIONS

- LED Bathroom Lighting
- Residential Ceiling Down Lighting
- Commercial Ceiling Down Lighting
- Living Room Lighting
- Office Lighting
- LED Kitchen Lighting
- Pot Lights

