

# **EL-141-3S-CW/WW** LED Swivel Downlight Scoop 3.6W

## **SPECIFICATION SHEET**

JOB NAME:

LOCATION:

QUOTE/REF#:

### DESCRIPTION

The 3.6 Watt LED Scoop Downlight is one of our most powerful and efficient recessed fixtures. The LED Scoop downlight is a fully recessed LED light that adds brightness, focused illumination to any space.

The EL-141-3S fits into walls, ceilings, cabinetry, under countertops, bars, display cases, home entertainment centers, and retail window displays. The LED Swivel fixture is made of cast aluminum and features an adjustable gimbal design with a 359° rotation and 45° axial swivel for the desired lighting direction. Available in Satin Nickel finish with 3000K Warm White or 5000K Cool White LED CCT options.

The LED recessed gimbal lights can fit into tight spaces for easy installation. It is adjustable as a spotlight and can swivel to the beam directions desired.

### **KEY FEATURES**

- Maintenance-free
- Solid-State Construction
- No IR or UV radiation
- Suitable for flat ceiling or under-cabinet installations
- Easy to mounting and install with tension spring clamps
- LEDs Chipsets are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Long lifespan: Up to 50,000 hours

### **APPLICATIONS**

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways,

US

- Downlighting or Uplighting Recessed Applications
- Under-cabinet, Under-Counter, or accent lighting



#### **SPECIFICATIONS**

Brightness:	300 Lumens
Power (Watts):	3.6 watt
Input Voltage:	350 mA
LED CCT:	3000K or 5000K
IP Rating:	IP20
Environment:	Indoor Use - Dry Location
Beam Angle:	15 - 40°
LED Density:	3 LEDs
Cut-out:	3 in / 76.2 mm Diameter
Diameter:	3.5 in / 88.9 mm
Gimbal Depth:	1.75 in / 44.45 mm
Finish:	Satin Nickel
Manufacturer:	Elumalight
Rating:	UL, ETL Listed
Avg. Lifetime:	± 30,000 - 50,000 hours
Required:	The LED 3.6 Watt Scoop requires 350mA LED Power Supply, optional power cord, 350mA Connection block if connecting more than one fixture in an area, and 350mA Closed Loop if not using all ports in connection block. Sold separately.