

EL-141-6/6W LED Swivel Down Light 7.2 Watt

SPECIFICATION SHEET

JOB NAME: LOCATION: QUOTE/REF#:



SPECIFICATIONS

Brightness: 600 Lumens Power (Watts): 7.2 Watt Input Voltage: 350 mA

3000K or 5000K **LED CCT:**

IP Rating:

Indoor Use - Dry Location **Environment:**

15° **Beam Angle: LED Density:** 6 LEDs

Cut-out: 3.5 in / 88.9 mm Diameter

Diameter: 3.88 in / 98.55 mm **Gimbal Depth:** 2.06 in / 52.32 mm

Satin Nickel Finish: Manufacturer: Elumalight Rating: UL, ETL Listed

± 30,000 - 50,000 hours Avg. Lifetime:

Required:

The LED Swivel Downlight requires 350mA LED Power Supply, optional power cord, 350mA Connection block if connecting more than one fixture in an area, and 350mA Closed Loop if not using all ports in connection block. Sold separately.

DESCRIPTION

The 7.2 Watt LED Swivel Downlight is one of our powerful and efficient recessed fixtures. It is a fully recessed LED light that adds brightness, focused illumination to any space.

The EL-141-6 fits into walls, ceilings, cabinetry, under countertops, bars, display cases, home entertainment centers, and retail window displays. It is made of cast aluminum and features an adjustable gimbal design for directed lighting with 15° axial swivels.

The LED recessed gimbal light can fit into tight spaces for easy installation. It is adjustable as a spotlight and can swivel to the beam directions desired and equivalent to a 75-watt MR-16 halogen light. Available in 3000K Warm White or 5000K Cool White LED CCT options in Satin Nickel finish.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- No IR or UV radiation
- Suitable for flat ceiling or under-cabinet installations
- Easy to mounting and install with tension spring clamps
- LEDs Chipsets are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Long lifespan: Up to 50,000 hours

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways,
- **Downlighting or Uplighting Recessed Applications**
- Under-cabinet, Under-Counter, or accent lighting









