

EL-150-4G Zircon Mini LED Display Light

SPECIFICATION SHEET





SPECIFICATIONS

Brightness: 100 Lumens Power (Watts): 1.2 watt Input Voltage: 350mA

LED CCT: 6000K Cool White

CRI:

Dimmable: Yes, with Dimmable Driver

IP Rating: **IP20**

Environment: Indoor Use - Dry Location

Beam Angle:

Overall Height: 4.25 in / 107.95 mm

Adjustable Gooseneck

Base Diameter: 1 in / 25.4 mm wide **LED Driver:** 350mA LED Driver

Manufacturer: Elumalight Rating: **ETL Listed**

Avg. Lifetime: ± 30,000 - 50,000 hours

Requires the 2, 3, or 6 Ports Connector Block and 350mA LED Driver, Sold Separately. * Required:

DESCRIPTION

Flexible, Bright, and focused lighting to bring out the sparkle of your gems. LED Ruby Jewelry Case lighting is an economical solution with a long lifespan! The Short Flexible Gooseneck LED Display Light stands just 4.25 in. tall and fits nicely in any modern display and it's High-Tech look blends well with most jewelry glass cases. It includes 6.5 in power feed with plug for easy Plug and Play install. Connect up to six light fixtures using our convenient connection blocks, fasten lead from connection blocks, fasten lead from connection blocks. tion block into a power supply for a virtually labor free set-up.

KEY FEATURES

- Bright and Smooth spotlighting solution
- Integrated LED chipsets
- Flexible Gooseneck allows for any desired lighting direc-
- Easy Installation
- No RF interference
- Up to 50,000 hours Lifespan
- **ETL Listed**

APPLICATIONS

- Tradeshow
- Exhibit
- **Retail Displays**
- **Jewelry Case**







