

EL-170-3RS Quartz LED Display Light

SPECIFICATION SHEET



SPECIFICATIONS

Brightness: 300 Lumens Power: 3.6 watt **Input Voltage:** 350mA

LED CCT: 6000K Cool White

CRI:

Dimmable: Yes, with Dimmable Driver

IP Rating: **IP20**

Environment: Indoor Use - Dry Location

15° **Beam Angle:**

Overall Height: 13.6 in / 346.2 mm long Base Diameter: 1.5 in / 38.1 mm wide

350mA LED Driver Required, Sold Separately **LED Driver:**

Manufacturer: Elumalight **ETL Listed** Rating:

Avg. Lifetime: ± 30,000 - 50,000 hours

Requires the 2, 3, or 6 Ports Connector Block and 350mA LED Driver, Sold Separately. * Required:

JOB NAME: LOCATION: QUOTE/REF#:

DESCRIPTION

Efficiently placed LED lights to enhance visual merchandising and ultimately lead to great customer experience and improved sales performance. Make your showcase, retail display, or cabinet shine with display case jewelry light fixtures from Step 1 Dezigns.

Tri-diode display unit with the pivoting head: 0° - 90°. Includes screw-down mounting plate, 19" cord and plug for easy "Plug and Play" install. Plug up to six light fixtures using our convenient connection blocks, fasten lead from connection block into a power supply for a virtually labor free set-up.

KEY FEATURES

- Bright and Smooth spotlighting solution
- Integrated LED chipsets
- Adjustable Pivot Head from 0 90°
- Easy Installation
- No RF interference
- Up to 50,000 hours Lifespan
- **ETL Listed**

APPLICATIONS

- Tradeshow
- Exhibit
- **Retail Displays**
- Jewelry Case







