

# SPECIFICATION SHEET



## SPECIFICATIONS

Brightness:	4459 Lumens (4 Ft 4000K) 4501 Lumens (4 Ft 5000K) 7680 Lumens (8 Ft 4000K)
Power:	7723 Lumens (8 Ft 5000K) 36 Watts (4 Ft)
Power.	68 Watts (8 Ft)
Input Voltage:	100-277V AC, 50/60Hz
LED CCT:	4000K or 5000K options
Beam Angle:	127°
CRI:	80+
Dimmable:	Yes
IP Rating:	IP20
Environment:	Dry Locations
Dimensions:	48 in L x 3.7 in W x 2.6 in H <b>(EL-1940)</b>
	96 in L x 3.7 in W x 2.6 in H <b>(EL-1941)</b>
Mounting:	Surface mounting for ceiling or wall mounting, compatible with most ceiling types.
Finish:	White
Manufacturer:	Elumalight
Rating:	cETLus Listed
Avg. Lifetime:	± 30,000 - 50,000 hours
Warranty:	5 Year Limited

# EL-1940 | EL-1941

LED Linear Dimmable Strip Lights

JOB NAME: LOCATION:

QUOTE/REF#:

# DESCRIPTION

The LED Linear Dimmable Strip Light utilizes high quality LED chips that allow high brightness and long lifespan. It uses 80% led energy in comparison to traditional light bulbs.

The lampshade adopts materials that are durable and resistant to ultraviolet light. It will not yellow after long-term use. It gets rid of glare, emits soft light, and is non-dazzling.

It has an input voltage of 100-277V AC and it is instant-on which means that the LED fixture will reach 100% brightness when it is turned on.

## **KEY FEATURES**

- Energy-efficient LED Chipsets
- Even and soft light illumination without hotspots
- Installation with buckles makes installation fast and easy
- 80+ LED color indexing prevents eye fatigue
- Category I protection grade against shock
- Static matte white coating
- Normal use environment: -20 ~ 45°C

#### APPLICATIONS

- Garages
- Carports
- Walkways
- Warehouse
- Retail Stores
- Restrooms
- Commercial Buildings
- Offices



1200 (47.3")/ 2394 (94.3")



© 2020 Step 1 Dezigns, Inc. All Rights Reserved. Specifications are subject to change without notice.

630 Terminal Way, Costa Mesa, CA 92627 sales@step1dezigns.com | www.step1dezigns.com TF: 800.822.8527 |T: 949.270.0250 | FAX: 949.270.0253