

SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



SPECIFICATIONS

Brightness:	650 Lumens
Power (Watts):	9 Watt
Voltage:	120V AC
LED CCT:	3000K
CRI:	90+
Dimmable:	Yes, Triac/ELV
Environment:	Wet or Dry Location
Aperture:	2 in diameter
Dimensions:	3.125 in D x 2.625 in H
Finish:	White
Trims:	Reflector - EL-210-30K-WH Baffle - EL-214-30K-WH
Manufacturer:	Elumalight
Rating:	Energy Star, cULus Wet Listed, CEC Title 24, Meets ASTM-E283 Airtight Requirements
Avg. Lifetime:	± 30,000 - 50,000 hours
Warranty:	5 Year Limited

DESCRIPTION

The 2" LED Round Downlights are suitable for use with a 2 in. diameter recessed housings. It produces even illumination without diode image. It is suitable for use in fixtures installed in insulated ceilings, new construction, remodel housings, and 2 in. recessed fixtures installations with 2-wire connector.

The low profile unit is CA Title 24 compliant, meets ENERGY STAR requirements, and UL wet listed. It produces 650 lumens at 90+ CRI. Available in Round Reflector or Baffle trim options.

KEY FEATURES

- Easy to Install
- Even Lighting Illumination
- Low-heat dissipation
- Long lifespan 50000 hours
- Energy Star Listed
- cULus Wet Listed
- CEC Title 24 Listed
- Meets ASTM-E283 Air Tight requirements

APPLICATIONS

- LED Bathroom Lighting
- Residential Ceiling Down Lighting
- Commercial Ceiling Down Lighting
- Living Room Lighting
- Office Lighting
- LED Kitchen Lighting
- Pot Lights

